

Safety Data Sheet

according to UK REACH Regulation

Etchant according to KALLING 1

Revision date: 18.07.2023

Product code: 18835.xxxxx

Page 1 of 15

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Etchant according to KALLING 1

UFI: 925P-815C-W00F-Y7X7

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Use as laboratory reagent..Intended for scientific research and development.

Uses advised against

Any non-intended use.

1.3. Details of the supplier of the safety data sheet

Company name: MORPHISTO GmbH
Street: Schumannstr. 142/144
Place: D-63069 Offenbach
Telephone: +49 (0) 69 / 400 3019-60 Telefax: +49 (0) 69 / 400 3019-64
E-mail: info@morphisto.de
Contact person: Morphisto GmbH
E-mail: gefahrstoffmanagement@morphisto.de
Internet: http://www.morphisto.de

1.4. Emergency telephone number:

Poison Information Center Mainz, Germany, Tel: +49(0)6131/19240

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Met. Corr. 1; H290
Flam. Liq. 2; H225
Skin Corr. 1; H314
Eye Dam. 1; H318
STOT SE 3; H335

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

hydrochloric acid %
Copper(II) chloride

Signal word: Danger

Pictograms:



Hazard statements

H225 Highly flammable liquid and vapour.
H290 May be corrosive to metals.
H314 Causes severe skin burns and eye damage.
H335 May cause respiratory irritation.

Safety Data Sheet

according to UK REACH Regulation

Etchant according to KALLING 1

Revision date: 18.07.2023

Product code: 18835.xxxxx

Page 2 of 15

Precautionary statements

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P260 Do not breathe mist/vapours/spray.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P310 Immediately call a POISON CENTER/doctor.

Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

Pictograms:



Hazard statements

H314

Precautionary statements

P260-P280-P303+P361+P353-P305+P351+P338-P310

2.3. Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulating and toxic (PBT) or very persistent and very bioaccumulating (vPvB) at levels of 0.1% or higher. Ecological information: The substance/mixture does not contain any components that are considered to be hazardous according to REACH Article 57(f) or Commission Delegated Regulation (EU) 2017/2100 or Commission Delegated Regulation (EU) 2018/605 in amounts of 0.1 % or more have endocrine disrupting properties. Toxicological information: The substance/mixture does not contain any components that are to be classified according to REACH Article 57(f) or Commission Delegated Regulation (EU) 2017/2100 or Commission Delegated Regulation (EU) 2018/605 in quantities of 0.1 % or more have endocrine disrupting properties.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Safety Data Sheet

according to UK REACH Regulation

Etchant according to KALLING 1

Revision date: 18.07.2023

Product code: 18835.xxxxx

Page 3 of 15

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
64-17-5	Ethanol, Ethylalkohol			25 - < 30 %
	200-578-6	603-002-00-5	01-2119457610-43	
	Flam. Liq. 2, Eye Irrit. 2; H225 H319			
7647-01-0	hydrochloric acid ... %			10 - < 15 %
	231-595-7	017-002-01-X	01-2119484862-27	
	Met. Corr. 1, Skin Corr. 1B, Eye Dam. 1, STOT SE 3; H290 H314 H318 H335			
7447-39-4	Copper(II) chloride			1 - < 5 %
	231-210-2		01-2119970306-36	
	Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Dam. 1, Aquatic Acute 1, Aquatic Chronic 2; H312 H302 H315 H318 H400 H411			
78-93-3	butanone			< 1 %
	201-159-0	606-002-00-3	01-2119457290-43	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
64-17-5	200-578-6	Ethanol, Ethylalkohol	25 - < 30 %
		inhalation: LC50 = 124,7 mg/l (vapours); dermal: LD50 = >2000 mg/kg; oral: LD50 = >5000 mg/kg Eye Irrit. 2; H319: >= 50 - 100	
7647-01-0	231-595-7	hydrochloric acid ... %	10 - < 15 %
		Skin Corr. 1B; H314: >= 25 - 100 Skin Irrit. 2; H315: >= 10 - < 25 Eye Irrit. 2; H319: >= 10 - < 25 STOT SE 3; H335: >= 10 - 100	
7447-39-4	231-210-2	Copper(II) chloride	1 - < 5 %
		dermal: LD50 = 1224 mg/kg; oral: LD50 = 584 mg/kg	
78-93-3	201-159-0	butanone	< 1 %
		dermal: LD50 = >2000 mg/kg; oral: LD50 = 2054 mg/kg	

Further Information

This product contains no substances of very high concern (SVHC) (>0,1%) which are included in the Candidate List according to Article 59 of REACH.

SECTION 4: First aid measures
4.1. Description of first aid measures
General information

First aider: Pay attention to self-protection! Remove affected person from the danger area and lay down. Take off immediately all contaminated clothing. Wash contaminated clothing before reuse. Provide fresh air. If unconscious but breathing normally, place in recovery position and seek medical advice. Never give anything by mouth to an unconscious person or a person with cramps. IF exposed or if you feel unwell: Immediately call a POISON CENTER or doctor/physician.

After inhalation

Provide fresh air. Medical treatment necessary. Lung irritation Irritation to respiratory tract IF exposed: Immediately call a POISON CENTER or doctor/physician. If unconscious but breathing normally, place in recovery position and seek medical advice.

Safety Data Sheet

according to UK REACH Regulation

Etchant according to KALLING 1

Revision date: 18.07.2023

Product code: 18835.xxxxx

Page 4 of 15

After contact with skin

Causes burns. After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist. Danger of blindness!

After ingestion

Rinse mouth immediately and drink 1 glass of water. Ingestion causes nausea, weakness and central nervous system effects. Rinse mouth thoroughly with water. Let water be drunk in little sips (dilution effect). Observe risk of aspiration if vomiting occurs. Do NOT induce vomiting. Adverse human health effects and symptoms: Gastric perforation. Call a physician immediately. Do not allow a neutralisation agent to be drunk.

4.2. Most important symptoms and effects, both acute and delayed

Ingestion causes burns of the upper digestive and Respiratory tract., Causes severe skin burns and eye damage., Cough, Dyspnoea, Headache, Dizziness, Nausea, Vomiting, May cause irritation.. Headaches and dizziness may occur, proceeding to fainting or unconsciousness; large doses may result in coma and death.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically., Regulation of the blood circulation, possible shock treatment.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Water spray jet, Carbon dioxide (CO₂), Foam, Extinguishing powder. Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Highly flammable. Vapours can form explosive mixtures with air. In case of fire may be liberated: Carbon monoxide, Carbon dioxide, Chlorine (Cl₂), Hydrogen chloride (HCl).

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment. The danger areas must be delimited and identified using relevant warning and safety signs.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Explosion risk. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up**For cleaning up**

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

Safety Data Sheet

according to UK REACH Regulation

Etchant according to KALLING 1

Revision date: 18.07.2023

Product code: 18835.xxxxx

Page 5 of 15

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Cover drains. Treat the recovered material as prescribed in the section on waste disposal. Provide adequate ventilation. Clear contaminated areas thoroughly.

6.4. Reference to other sections

Safe handling: see section 7
 Personal protection equipment: see section 8
 Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray. Wear personal protection equipment. Use extractor hood (laboratory).

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat, drink, smoke, sniff.

Further information on handling

Wash hands and face before breaks and after work and take a shower if necessary.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaust at critical locations. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Protect from direct sunlight. Unsuitable container/equipment material: Metal.

Hints on joint storage

Do not store together with: Oxidizing agent. Pyrophoric or self-heating substances.

Further information on storage conditions

Recommended storage temperature: 15-25 °C.

7.3. Specific end use(s)

See section 1.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
78-93-3	Butan-2-one (methyl ethyl ketone)	200	600		TWA (8 h)	WEL
		300	899		STEL (15 min)	WEL
64-17-5	Ethanol	1000	1920		TWA (8 h)	WEL
7647-01-0	Hydrogen chloride (gas and aerosol mists)	1	2		TWA (8 h)	WEL
		5	8		STEL (15 min)	WEL

Safety Data Sheet

according to UK REACH Regulation

Etchant according to KALLING 1

Revision date: 18.07.2023

Product code: 18835.xxxxx

Page 6 of 15

Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
78-93-3	Butan-2-one	butan-2-one	70 µmol/L	urine	Post shift

DNEL/DMEL values

CAS No	Substance	DNEL type	Exposure route	Effect	Value
64-17-5	Ethanol, Ethylalkohol	Worker DNEL, acute	inhalation	local	1900 mg/m ³
		Worker DNEL, long-term	dermal	systemic	343 mg/kg bw/day
		Worker DNEL, long-term	inhalation	systemic	950 mg/m ³
		Consumer DNEL, acute	inhalation	local	950 mg/m ³
		Consumer DNEL, long-term	dermal	systemic	206 mg/kg bw/day
		Consumer DNEL, long-term	inhalation	systemic	114 mg/m ³
		Consumer DNEL, long-term	oral	systemic	87 mg/kg bw/day
7447-39-4	Copper(II) chloride	Worker DNEL, long-term	inhalation	systemic	1 mg/m ³
		Worker DNEL, long-term	inhalation	local	1 mg/m ³
		Worker DNEL, long-term	dermal	systemic	137 mg/kg bw/day

PNEC values

CAS No	Substance	Environmental compartment	Value
64-17-5	Ethanol, Ethylalkohol	Freshwater	0,96 mg/l
		Freshwater (intermittent releases)	2,75 mg/l
		Marine water	0,79 mg/l
		Marine water (intermittent releases)	2,75 mg/l
		Freshwater sediment	3,6 mg/kg
		Marine sediment	2,9 mg/kg
		Secondary poisoning	0,72 mg/kg
		Micro-organisms in sewage treatment plants (STP)	580 mg/l
		Soil	0,63 mg/kg
7447-39-4	Copper(II) chloride	Freshwater	0,0078 mg/l
		Marine water	0,0052 mg/l
		Freshwater sediment	87 mg/kg
		Marine sediment	676 mg/kg
		Micro-organisms in sewage treatment plants (STP)	0,23 mg/l
		Soil	65 mg/kg

Additional advice on limit values

 DNEL - hydrochloric acid (7647-010-0): 15 mg/m³ (Acute - local effects), 8 mg/m³ (Long-term - local effects)

PNEC - hydrochloric acid (7647-010-0): 0,036 mg/L (freshwater), 0,045 mg/L (intermittent releases), 0,036 mg/L (marine water)

Safety Data Sheet

according to UK REACH Regulation

Etchant according to KALLING 1

Revision date: 18.07.2023

Product code: 18835.xxxxx

Page 7 of 15

8.2. Exposure controls



Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray. Use extractor hood (laboratory).

Individual protection measures, such as personal protective equipment

Eye/face protection

Suitable eye protection: goggles. Suitable face protection: goggles. Safety goggles with side protection. In case of increased risk add protective face shield.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Tested protective gloves are to be worn:

Recommended material: Butyl caoutchouc (butyl rubber), Layer thickness: 0,7mm, Breakthrough time >480min.
Recommended material: CR (polychloroprene, chloroprene rubber), Layer thickness: 0,65mm, Breakthrough time 60min.

Recommended material: NBR (Nitrile rubber), Layer thickness: 0,5mm, Breakthrough time >120min.

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Take recovery periods for skin regeneration. Protect skin by using skin protective cream.

Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection. In case of inadequate ventilation wear respiratory protection.

Type A, ABEK2-P2

Thermal hazards

Flame-retardant protective clothing. Wear anti-static footwear and clothing.

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	liquid	
Colour:	gelblich-grünlich	
Odour:	stingingalcoholic	
Melting point/freezing point:		not determined
Boiling point or initial boiling point and boiling range:		56,1 °C
Flammability:		not applicable
Lower explosion limits:		3,1 vol. %
Upper explosion limits:		27,7 vol. %
Flash point:		12 °C

Safety Data Sheet

according to UK REACH Regulation

Etchant according to KALLING 1

Revision date: 18.07.2023

Product code: 18835.xxxxx

Page 8 of 15

Auto-ignition temperature:	400 °C
Decomposition temperature:	not determined
pH-Value:	not determined
Viscosity / kinematic:	not determined
Water solubility:	completely miscible
Solubility in other solvents	not determined
Partition coefficient n-octanol/water:	not determined
Vapour pressure:	190 hPa
(at 20 °C)	
Vapour pressure:	not determined
Density (at 20 °C):	0,97 g/cm ³
Bulk density:	not determined
Relative vapour density:	not determined
Particle characteristics:	not applicable

9.2. Other information
Information with regard to physical hazard classes
Explosive properties

The product is not: Explosive. The product is not: not explosive. Formation of explosible dust/air mixtures

Self-ignition temperature

Solid:

not applicable

Gas:

not applicable

Oxidizing properties

Not oxidising.

Other safety characteristics

Evaporation rate:

not determined

Solid content:

not determined

Sublimation point:

not applicable

Softening point:

not applicable

Pour point:

not applicable

Viscosity / dynamic:

not determined

Flow time:

not determined

SECTION 10: Stability and reactivity
10.1. Reactivity

Possibility of hazardous reactions. Corrosive to metals. Highly flammable.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Exothermic reaction with: Base, Peroxides, Oxidizing agent. Oxidising agent, strong, Alkalis (alkalis).

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

10.5. Incompatible materials

Metal. Keep away from: Base, Oxidizing agent, Peroxides. Metal

10.6. Hazardous decomposition products

 In case of fire may be liberated: Chlorine (Cl₂). Hydrogen chloride (HCl).

SECTION 11: Toxicological information

Safety Data Sheet

according to UK REACH Regulation

Etchant according to KALLING 1

Revision date: 18.07.2023

Product code: 18835.xxxxx

Page 9 of 15

11.1. Information on hazard classes as defined in GB CLP Regulation
Toxicocinetics, metabolism and distribution

LD50

900 mg/kg (rabbit) (ECHA)

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) 38421 mg/kg; ATE (dermal) 80526 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64-17-5	Ethanol, Ethylalkohol				
	oral	LD50 >5000 mg/kg	Rat	ECHA Dossier	
	dermal	LD50 >2000 mg/kg	Rabbit	ECHA Dossier	
	inhalation (4 h) vapour	LC50 124,7 mg/l	Rat	ECHA Dossier	
7447-39-4	Copper(II) chloride				
	oral	LD50 584 mg/kg	Rat	RTECS	
	dermal	LD50 1224 mg/kg	Rat	MSDS external	OECD 402
78-93-3	butanone				
	oral	LD50 2054 mg/kg	Ratte	SDB Lieferant	
	dermal	LD50 >2000 mg/kg	Rabbit	ECHA Dossier	

Irritation and corrosivity

Causes severe skin burns and eye damage. (On basis of test data)

Causes serious eye damage. (On basis of test data)

Sensitising effects

Based on available data, the classification criteria are not met.

Safety Data Sheet

according to UK REACH Regulation

Etchant according to KALLING 1

Revision date: 18.07.2023

Product code: 18835.xxxxx

Page 10 of 15

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation. (hydrochloric acid ... %)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

Other information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
64-17-5	Ethanol, Ethylalkohol					
	Acute fish toxicity	LC50 mg/l	14200	96 h	Pimephales promelas (fathead minnow)	ECHA Dossier
	Acute algae toxicity	ErC50	275 mg/l	72 h	Chlorella vulgaris	ECHA Dossier
	Acute crustacea toxicity	EC50 mg/l	5012	48 h	Ceriodaphnia dubia (water flea)	ECHA Dossier
	Crustacea toxicity	NOEC	9,6 mg/l	9 d	Daphnia magna	ECHA Dossier
7647-01-0	hydrochloric acid ... %					
	Acute fish toxicity	LC50	862 mg/l	96 h	Leuciscus idus	
7447-39-4	Copper(II) chloride					
	Acute fish toxicity	LC50 mg/l	0,0028	96 h	Oncorhynchus mykiss	ECOTOX
	Acute crustacea toxicity	EC50 mg/l	0,00557	48 h	Ceriodaphnia dubia (water flea)	ECOTOX
78-93-3	butanone					
	Acute fish toxicity	LC50 mg/l	2993	96 h	Pimephales promelas	ECHA Dossier OECD 203
	Acute algae toxicity	ErC50 mg/l	1972	72 h	Pseudokirchnerella subcapitata	ECHA Dossier OECD 201
	Acute crustacea toxicity	EC50	308 mg/l	48 h	Daphnia magna	ECHA Dossier OECD 202

12.2. Persistence and degradability

The product has not been tested.

Safety Data Sheet

according to UK REACH Regulation

Etchant according to KALLING 1

Revision date: 18.07.2023

Product code: 18835.xxxxx

Page 11 of 15

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
64-17-5	Ethanol, Ethylalkohol			
	other guideline	84%	20	ECHA Dossier
	Biodegradable.			
78-93-3	butanone			
		98%	28	ECHA Dossier
	Readily biodegradable (according to OECD criteria).			

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
64-17-5	Ethanol, Ethylalkohol	-0,31
78-93-3	butanone	0,3

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations
13.1. Waste treatment methods
Disposal recommendations

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

110105 WASTES FROM CHEMICAL SURFACE TREATMENT AND COATING OF METALS AND OTHER MATERIALS; NON-FERROUS HYDRO-METALLURGY; wastes from chemical surface treatment and coating of metals and other materials (for example galvanic processes, zinc coating processes, pickling processes, etching, phosphating, alkaline degreasing, anodising); pickling acids; hazardous waste

List of Wastes Code - used product

110105 WASTES FROM CHEMICAL SURFACE TREATMENT AND COATING OF METALS AND OTHER MATERIALS; NON-FERROUS HYDRO-METALLURGY; wastes from chemical surface treatment and coating of metals and other materials (for example galvanic processes, zinc coating processes, pickling processes, etching, phosphating, alkaline degreasing, anodising); pickling acids; hazardous waste

List of Wastes Code - contaminated packaging

Safety Data Sheet

according to UK REACH Regulation

Etchant according to KALLING 1

Revision date: 18.07.2023

Product code: 18835.xxxxx

Page 12 of 15

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information
Land transport (ADR/RID)

14.1. UN number or ID number: UN 2924
14.2. UN proper shipping name: FLAMMABLE LIQUID, CORROSIVE, N.O.S. (Ethanol, Hydrogen chloride (HCl))
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3+8



Classification code: FC
 Special Provisions: 274
 Limited quantity: 1 L
 Excepted quantity: E2
 Transport category: 2
 Hazard No: 338
 Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 2924
14.2. UN proper shipping name: FLAMMABLE LIQUID, CORROSIVE, N.O.S. (Ethanol, Hydrogen chloride (HCl))
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3+8



Classification code: FC
 Special Provisions: 274
 Limited quantity: 1 L
 Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number or ID number: UN 2924
14.2. UN proper shipping name: FLAMMABLE LIQUID, CORROSIVE, N.O.S. (Ethanol, Hydrogen chloride (HCl))
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3+8



Marine pollutant: -

Safety Data Sheet

according to UK REACH Regulation

Etchant according to KALLING 1

Revision date: 18.07.2023

Product code: 18835.xxxxx

Page 13 of 15

Special Provisions: 274
 Limited quantity: 5 L
 Excepted quantity: E1
 EmS: F-E, S-C
 Segregation group: acids

Other applicable information (marine transport)

Stowage category B

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 2924
14.2. UN proper shipping name: FLAMMABLE LIQUID, CORROSIVE, N.O.S. (Ethanol, Hydrogen chloride (HCl))
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3+8



Special Provisions: A3
 Limited quantity Passenger: 0,5 L
 Passenger LQ: Y342
 Excepted quantity: E2

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Combustible liquid. Warning: strongly corrosive.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information
15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture
EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

2010/75/EU (VOC): 26,35 % (255,595 g/l)
 2004/42/EC (VOC): 26,35 % (255,595 g/l)
 Information according to 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).
 Water hazard class (D): 2 - obviously hazardous to water

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

Ethanol, Ethylalkohol
 hydrochloric acid ... %
 Copper(II) chloride
 butanone

SECTION 16: Other information

Safety Data Sheet

according to UK REACH Regulation

Etchant according to KALLING 1

Revision date: 18.07.2023

Product code: 18835.xxxxx

Page 14 of 15

Changes

This data sheet contains changes from the previous version in section(s): 5,7,8,9,10,11,15.

Rev. 1,0; 29.05.2020 Revision

Rev. 2,0; 18.07.2023; general adjustment(s)

Abbreviations and acronyms

CLP: Classification, labelling and Packaging

REACH: Registration, Evaluation and Authorization of Chemicals

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

UN: United Nations

CAS: Chemical Abstracts Service

DNEL: Derived No Effect Level

DMEL: Derived Minimal Effect Level

PNEC: Predicted No Effect Concentration

ATE: Acute toxicity estimate

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

LL50: Lethal loading, 50%

EL50: Effect loading, 50%

EC50: Effective Concentration 50%

ErC50: Effective Concentration 50%, growth rate

NOEC: No Observed Effect Concentration

BCF: Bio-concentration factor

PBT: persistent, bioaccumulative, toxic

vPvB: very persistent, very bioaccumulative

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Regulations concerning the international carriage of dangerous goods by rail

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

(Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)

IMDG: International Maritime Code for Dangerous Goods

EmS: Emergency Schedules

MFAG: Medical First Aid Guide

IATA: International Air Transport Association

ICAO: International Civil Aviation Organization

MARPOL: International Convention for the Prevention of Marine Pollution from Ships

IBC: Intermediate Bulk Container

VOC: Volatile Organic Compounds

SVHC: Substance of Very High Concern

 For abbreviations and acronyms, see table at <http://abbrev.esdscom.eu>

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Met. Corr. 1; H290	On basis of test data
Flam. Liq. 2; H225	On basis of test data
Skin Corr. 1; H314	On basis of test data
Eye Dam. 1; H318	On basis of test data
STOT SE 3; H335	Calculation method

Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.

H290 May be corrosive to metals.

H302 Harmful if swallowed.

Safety Data Sheet

according to UK REACH Regulation

Etchant according to KALLING 1

Revision date: 18.07.2023

Product code: 18835.xxxxx

Page 15 of 15

H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)