

Safety Data Sheet

according to UK REACH Regulation

Alkaline Alcohol (with KOH)

Revision date: 21.09.2023

Product code: 12437.xxxxx

Page 1 of 16

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Alkaline Alcohol (with KOH)

UFI: JSE3-013H-9006-S3NF

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Use as laboratory reagent. The product is intended for research, analysis and scientific education.

Uses advised against

Any non-intended use.

1.3. Details of the supplier of the safety data sheet

Company name:	MORPHISTO GmbH	
Street:	Schumannstr. 142/144	
Place:	D-63069 Offenbach	
Telephone:	+49 (0) 69 / 400 3019-60	Telefax: +49 (0) 69 / 400 3019-64
E-mail:	info@morphisto.de	
Contact person:	Morphisto GmbH	
E-mail:	gefahrstoffmanagement@morphisto.de	
Internet:	http://www.morphisto.de	

1.4. Emergency telephone number:

Poison Information Center Mainz, Germany, Tel: +49(0)6131/19240

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****GB CLP Regulation**

Met. Corr. 1; H290
Flam. Liq. 2; H225
Eye Irrit. 2; H319

Full text of hazard statements: see SECTION 16.

2.2. Label elements**GB CLP Regulation****Signal word:** Danger**Pictograms:****Hazard statements**

H225	Highly flammable liquid and vapour.
H290	May be corrosive to metals.
H319	Causes serious eye irritation.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P234	Keep only in original packaging.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P337+P313	If eye irritation persists: Get medical advice/attention.
P390	Absorb spillage to prevent material damage.

Safety Data Sheet

according to UK REACH Regulation

Alkaline Alcohol (with KOH)

Revision date: 21.09.2023

Product code: 12437.xxxxx

Page 2 of 16

Labelling of packages where the contents do not exceed 125 ml
Signal word: Danger

Pictograms:

2.3. Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulating and toxic (PBT) or very persistent and very bioaccumulating (vPvB) at levels of 0.1% or higher. Ecological information: The substance/mixture does not contain any components that are considered to be hazardous according to REACH Article 57(f) or Commission Delegated Regulation (EU) 2017/2100 or Commission Delegated Regulation (EU) 2018/605 in amounts of 0.1 % or more have endocrine disrupting properties. Toxicological information: The substance/mixture does not contain any components that are to be classified according to REACH Article 57(f) or Commission Delegated Regulation (EU) 2017/2100 or Commission Delegated Regulation (EU) 2018/605 in quantities of 0.1 % or more have endocrine disrupting properties.

SECTION 3: Composition/information on ingredients
3.2. Mixtures
Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
64-17-5	ethanol			70 - < 75 %
	200-578-6	603-002-00-5	01-2119457610-43	
	Flam. Liq. 2, Eye Irrit. 2; H225 H319			
67-63-0	2-propanol			< 1 %
	200-661-7	603-117-00-0	01-2119457558-25	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336			
78-93-3	butanone			< 1 %
	201-159-0	606-002-00-3	01-2119457290-43	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
3734-33-6	Denatoniumbenzoate			< 1 %
	223-095-2			
	Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Dam. 1, Aquatic Chronic 3; H332 H302 H315 H318 H412			

Full text of H and EUH statements: see section 16.

Safety Data Sheet

according to UK REACH Regulation

Alkaline Alcohol (with KOH)

Revision date: 21.09.2023

Product code: 12437.xxxxx

Page 3 of 16

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
64-17-5	200-578-6	ethanol	70 - < 75 %
		inhalation: LC50 = 124,7 mg/l (vapours); dermal: LD50 = >2000 mg/kg; oral: LD50 = >5000 mg/kg Eye Irrit. 2; H319: >= 50 - 100	
67-63-0	200-661-7	2-propanol	< 1 %
		dermal: LD50 = >5000 mg/kg; oral: LD50 = >5000 mg/kg	
78-93-3	201-159-0	butanone	< 1 %
		dermal: LD50 = >2000 mg/kg; oral: LD50 = 2054 mg/kg	
3734-33-6	223-095-2	Denatoniumbenzoate	< 1 %
		inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = >2000 mg/kg; oral: ATE = 500 mg/kg	

Further Information

This product contains no substances of very high concern (SVHC) (>0,1%) which are included in the Candidate List according to Article 59 of REACH.

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Take off immediately all contaminated clothing.

First aider: Pay attention to self-protection!

After inhalation

Provide fresh air. Remove person to fresh air and keep comfortable for breathing. In case of respiratory tract irritation, consult a physician.

After contact with skin

Take off contaminated clothing and wash it before reuse. Take off immediately all contaminated clothing. Wash with plenty of water. In case of skin irritation, seek medical treatment.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

Observe risk of aspiration if vomiting occurs. Rinse mouth thoroughly with water. Let water be drunken in little sips (dilution effect). Do NOT induce vomiting. Never give anything by mouth to an unconscious person or a person with cramps. In all cases of doubt, or when symptoms persist, seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Water spray jet, Carbon dioxide (CO₂), Foam, Extinguishing powder
In case of major fire and large quantities: Atomized water.

Unsuitable extinguishing media

High power water jet.

Safety Data Sheet

according to UK REACH Regulation

Alkaline Alcohol (with KOH)

Revision date: 21.09.2023

Product code: 12437.xxxxx

Page 4 of 16

5.2. Special hazards arising from the substance or mixture

Highly flammable. Vapours can form explosive mixtures with air. In case of fire may be liberated: Gas/vapours, irritant. Carbon monoxide Carbon dioxide (CO₂).

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. In case of fire and/or explosion do not breathe fumes.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Remove all sources of ignition. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment. Remove persons to safety. Ventilate affected area.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Explosion risk. Do not allow to enter into surface water or drains. Cover drains. Prevent spread over a wide area (e.g. by containment or oil barriers). In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up**For cleaning up**

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Ventilate affected area.

Treat the recovered material as prescribed in the section on waste disposal.

Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray. Provide adequate ventilation as well as local exhaustion at critical locations.

Avoid contact with skin, eyes and clothes.

Wear suitable protective clothing. (See section 8.)

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air. Flammable vapours can accumulate in head space of closed systems. Heating causes rise in pressure with risk of bursting.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat, drink, smoke, sniff. The usual precautions for handling chemicals should be considered.

Always close containers tightly after the removal of product.

Safety Data Sheet

according to UK REACH Regulation

Alkaline Alcohol (with KOH)

Revision date: 21.09.2023

Product code: 12437.xxxxx

Page 5 of 16

Further information on handling

General protection and hygiene measures: See section 8.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Unsuitable container/equipment material: Metal. Protect from direct sunlight. Ensure adequate ventilation of the storage area.

Make sure spills can be contained (e.g. sump pallets or kerbed areas).

Hints on joint storage

Do not store together with: Oxidizing agent. Pyrophoric or self-heating substances. Do not store together with: Gas. Explosives. Flammable solids. Pyrophoric liquids and solids. Self-heating substances and mixtures.

Substances or mixtures which, in contact with water, emit flammable gases. Oxidizing liquids. Oxidizing solids. ammonium nitrate. Self-reactive substances and mixtures. Organic peroxides. Non-combustible toxic substances. Radioactive substances. Infectious substances.

Further information on storage conditions

Keep the packing dry and well sealed to prevent contamination and absorption of humidity.

Protect against: UV-radiation/sunlight. heat. Humidity frost.

storage temperature: 15-25°C

7.3. Specific end use(s)

See section 1.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
78-93-3	Butan-2-one (methyl ethyl ketone)	200	600		TWA (8 h)	WEL
		300	899		STEL (15 min)	WEL
64-17-5	Ethanol	1000	1920		TWA (8 h)	WEL
1310-58-3	Potassium hydroxide	-	2		STEL (15 min)	WEL
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL

Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
78-93-3	Butan-2-one	butan-2-one	70 µmol/L	urine	Post shift

Safety Data Sheet

according to UK REACH Regulation

Alkaline Alcohol (with KOH)

Revision date: 21.09.2023

Product code: 12437.xxxxx

Page 6 of 16

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
64-17-5	ethanol			
Worker DNEL, acute		inhalation	local	1900 mg/m ³
Worker DNEL, long-term		dermal	systemic	343 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	950 mg/m ³
Consumer DNEL, acute		inhalation	local	950 mg/m ³
Consumer DNEL, long-term		dermal	systemic	206 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	114 mg/m ³
Consumer DNEL, long-term		oral	systemic	87 mg/kg bw/day
67-63-0	2-propanol			
Worker DNEL, long-term		inhalation	systemic	500 mg/m ³
Consumer DNEL, long-term		inhalation	systemic	89 mg/m ³
Worker DNEL, long-term		dermal	systemic	888 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	26 mg/kg bw/day
Consumer DNEL, long-term		dermal	systemic	319 mg/kg bw/day
1310-58-3	potassium hydroxide			
Worker DNEL, long-term		inhalation	local	1 mg/m ³
Consumer DNEL, long-term		inhalation	local	1 mg/m ³

PNEC values

CAS No	Substance	Value
64-17-5	ethanol	
Freshwater		0,96 mg/l
Freshwater (intermittent releases)		2,75 mg/l
Marine water		0,79 mg/l
Marine water (intermittent releases)		2,75 mg/l
Freshwater sediment		3,6 mg/kg
Marine sediment		2,9 mg/kg
Secondary poisoning		0,72 mg/kg
Micro-organisms in sewage treatment plants (STP)		580 mg/l
Soil		0,63 mg/kg
67-63-0	2-propanol	
Freshwater		140,9 mg/l
Marine water		140,9 mg/l
Freshwater sediment		552 mg/kg
Marine sediment		552 mg/kg
Secondary poisoning		160 mg/kg
Soil		28 mg/kg

8.2. Exposure controls

Safety Data Sheet

according to UK REACH Regulation

Alkaline Alcohol (with KOH)

Revision date: 21.09.2023

Product code: 12437.xxxxx

Page 7 of 16


Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray. Provide adequate ventilation as well as local exhaustion at critical locations.

Individual protection measures, such as personal protective equipment
Eye/face protection

Suitable eye protection: goggles. Tightly sealed safety glasses. (EN 166)

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. In case of prolonged or frequently repeated skin contact: Wear suitable gloves.

Suitable material: Butyl rubber.

Thickness of glove material: 0,5 mm

Breakthrough time \geq 480 min. penetration time (maximum wearing period): ~ 120 min. (estimated)

In the case of wanting to use the gloves again, clean them before taking off and air them well. Before using check leak tightness / impermeability.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it.

Skin protection

Wear fire resistant or flame retardant clothing.

Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500 (D).

Respiratory protection

In case of inadequate ventilation wear respiratory protection. With correct and proper use, and under normal conditions, breathing protection is not required.

Respiratory protection necessary at:

Generation/formation of aerosols exceeding exposure limit values

Insufficient ventilation.

Suitable respiratory protective equipment: Combination filtering device (EN 14387) Type: A/P1-3

The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.

Thermal hazards

Flame-retardant protective clothing. Wear anti-static footwear and clothing

Environmental exposure controls

Do not allow uncontrolled discharge of product into the environment.

SECTION 9: Physical and chemical properties
9.1. Information on basic physical and chemical properties

Physical state:	liquid.	
Colour:	colourless	
Odour:	alcoholic	
Melting point/freezing point:		not applicable

Safety Data Sheet

according to UK REACH Regulation

Alkaline Alcohol (with KOH)

Revision date: 21.09.2023

Product code: 12437.xxxxx

Page 8 of 16

Boiling point or initial boiling point and boiling range:	not determined
Flammability:	not determined
Lower explosion limits:	not determined
Upper explosion limits:	not determined
Flash point:	0-<21 °C
Auto-ignition temperature:	not determined
Decomposition temperature:	not determined
pH-Value:	not determined
Viscosity / kinematic: (at 20 °C)	not determined
Water solubility: (at 20 °C)	miscible.
Solubility in other solvents	not determined
Partition coefficient n-octanol/water:	not determined
Vapour pressure: (at 20 °C)	not determined
Density (at 20 °C):	not determined
Relative vapour density:	not determined
Particle characteristics:	not applicable

9.2. Other information
Information with regard to physical hazard classes

Explosive properties

The product is not: Explosive.

Oxidizing properties

none.

Other safety characteristics

Evaporation rate:	not determined
Solvent separation test:	not determined
Solvent content:	not determined
Solid content:	not determined
Viscosity / dynamic: (at 40 °C)	not determined
Flow time:	not determined

SECTION 10: Stability and reactivity
10.1. Reactivity

Corrosive to metals. Highly flammable

10.2. Chemical stability

The product is stable under normal storage conditions.

10.3. Possibility of hazardous reactions

Refer to chapter 10.5.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. Keep away from heat. In use may form flammable/explosive vapour-air mixture.

Heating causes rise in pressure with risk of bursting.

10.5. Incompatible materials

Keep away from: Metal. Materials to avoid: Oxidizing agents, strong. Reducing agents, strong. Strong acid. strong alkalis.

Safety Data Sheet

according to UK REACH Regulation

Alkaline Alcohol (with KOH)

Revision date: 21.09.2023

Product code: 12437.xxxxx

Page 9 of 16

10.6. Hazardous decomposition products

 In case of fire may be liberated: Gas/vapours, irritant. Carbon monoxide Carbon dioxide (CO₂).

SECTION 11: Toxicological information
11.1. Information on hazard classes as defined in GB CLP Regulation
Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64-17-5	ethanol				
	oral	LD50 >5000 mg/kg	Rat	ECHA Dossier	
	dermal	LD50 >2000 mg/kg	Rabbit	ECHA Dossier	
	inhalation (4 h) vapour	LC50 124,7 mg/l	Rat	ECHA Dossier	
67-63-0	2-propanol				
	oral	LD50 >5000 mg/kg	Rat	ECHA Dossier	
	dermal	LD50 >5000 mg/kg	Rabbit	ECHA Dossier	
78-93-3	butanone				
	oral	LD50 2054 mg/kg	Ratte	SDB Lieferant	
	dermal	LD50 >2000 mg/kg	Rabbit	ECHA Dossier	
3734-33-6	Denatoniumbenzoate				
	oral	ATE 500 mg/kg			
	dermal	LD50 >2000 mg/kg	Rat	suppliers SDS.	
	inhalation vapour	ATE 11 mg/l			
	inhalation dust/mist	ATE 1,5 mg/l			

Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Safety Data Sheet

according to UK REACH Regulation

Alkaline Alcohol (with KOH)

Revision date: 21.09.2023

Product code: 12437.xxxxx

Page 10 of 16

11.2. Information on other hazards

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

Other information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
64-17-5	ethanol					
	Acute fish toxicity	LC50 mg/l	14200	96 h	Pimephales promelas (fathead minnow)	ECHA Dossier
	Acute algae toxicity	ErC50	275 mg/l	72 h	Chlorella vulgaris	ECHA Dossier
	Acute crustacea toxicity	EC50 mg/l	5012	48 h	Ceriodaphnia dubia (water flea)	ECHA Dossier
	Crustacea toxicity	NOEC	9,6 mg/l	9 d	Daphnia magna	ECHA Dossier
67-63-0	2-propanol					
	Acute fish toxicity	LC50 mg/l	9640	96 h	Pimephales promelas	ECHA Dossier OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	1800	96 h	Scenedesmus quadricauda	ECHA Dossier
	Acute crustacea toxicity	EC50 mg/l	>10000	48 h	Daphnia magna (24h)	ECHA Dossier OECD Guideline 202
78-93-3	butanone					
	Acute fish toxicity	LC50 mg/l	2993	96 h	Pimephales promelas	ECHA Dossier OECD 203
	Acute algae toxicity	ErC50 mg/l	1972	72 h	Pseudokirchnerella subcapitata	ECHA Dossier OECD 201
	Acute crustacea toxicity	EC50	308 mg/l	48 h	Daphnia magna	ECHA Dossier OECD 202
3734-33-6	Denatoniumbenzoate					
	Acute fish toxicity	LC50 mg/l	>1000	96 h	Oncorhynchus mykiss (Rainbow trout)	suppliers SDS.
	Acute crustacea toxicity	EC50	13 mg/l	48 h	Daphnia magna (Big water flea)	suppliers SDS.

12.2. Persistence and degradability

The product has not been tested.

Safety Data Sheet

according to UK REACH Regulation

Alkaline Alcohol (with KOH)

Revision date: 21.09.2023

Product code: 12437.xxxxx

Page 11 of 16

CAS No	Chemical name	Method	Value	d	Source
		Evaluation			
64-17-5	ethanol				
	other guideline		84%	20	ECHA Dossier
	Biodegradable.				
67-63-0	2-propanol				
	EU Method C.5/ EU Method C.6		53%	5	ECHA Dossier
	Easily biodegradable (concerning to the criteria of the OECD)				
78-93-3	butanone				
			98%	28	ECHA Dossier
	Readily biodegradable (according to OECD criteria).				

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
64-17-5	ethanol	-0,31
67-63-0	2-propanol	0,05
78-93-3	butanone	0,3

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

The product has not been tested.

Further information

Avoid release to the environment. Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation. Consult the local waste disposal expert about waste disposal. Non-contaminated packages may be recycled. According to (EWC) European Waste Catalogue, allocation of waste identity numbers/waste descriptions must be carried out in a specific way for every industry and process.

Control report for waste code/ waste marking according to (EWC) European Waste Catalogue:

List of Wastes Code - residues/unused products

160506 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; laboratory chemicals, consisting of or containing hazardous substances, including mixtures of laboratory chemicals; hazardous waste

List of Wastes Code - used product

160305 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; off-specification batches and unused products; organic wastes containing hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

Safety Data Sheet

according to UK REACH Regulation

Alkaline Alcohol (with KOH)

Revision date: 21.09.2023

Product code: 12437.xxxxx

Page 12 of 16

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Wash with plenty of water. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information
Land transport (ADR/RID)

14.1. UN number or ID number: UN 2924
14.2. UN proper shipping name: FLAMMABLE LIQUID, CORROSIVE, N.O.S. (ethanol,potassium hydroxide)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3+8



Classification code: FC
 Special Provisions: 274
 Limited quantity: 1 L
 Excepted quantity: E2
 Transport category: 2
 Hazard No: 338
 Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 2924
14.2. UN proper shipping name: FLAMMABLE LIQUID, CORROSIVE, N.O.S. (ethanol,potassium hydroxide)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3+8



Classification code: FC
 Special Provisions: 274
 Limited quantity: 1 L
 Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number or ID number: UN 2924
14.2. UN proper shipping name: FLAMMABLE LIQUID, CORROSIVE, N.O.S. (ethanol, potassium hydroxide)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3+8



Special Provisions: 274

Safety Data Sheet

according to UK REACH Regulation

Alkaline Alcohol (with KOH)

Revision date: 21.09.2023

Product code: 12437.xxxxx

Page 13 of 16

Limited quantity: 1 L
 Excepted quantity: E2
 EmS: F-E, S-C

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 2924
14.2. UN proper shipping name: FLAMMABLE LIQUID, CORROSIVE, N.O.S. (ethanol, potassium hydroxide)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3+8



Special Provisions: A3
 Limited quantity Passenger: 0.5 L
 Passenger LQ: Y340
 Excepted quantity: E2
 IATA-packing instructions - Passenger: 352
 IATA-max. quantity - Passenger: 1 L
 IATA-packing instructions - Cargo: 363
 IATA-max. quantity - Cargo: 5 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: Combustible liquid. strongly corrosive. See section 8.

14.7. Maritime transport in bulk according to IMO instruments

not relevant.

SECTION 15: Regulatory information
15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture
EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

2010/75/EU (VOC): not determined
 2004/42/EC (VOC): not determined
 Information according to 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

Additional information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).
 Water hazard class (D): 1 - slightly hazardous to water

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

ethanol
 2-propanol
 butanone

Safety Data Sheet

according to UK REACH Regulation

Alkaline Alcohol (with KOH)

Revision date: 21.09.2023

Product code: 12437.xxxxx

Page 14 of 16

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 2,3,4,5,6,7,8,9,10,11,12,13,14,15,16.

Rev. 1.00; Initial release: 21.01.2019

Rev. 2,0; 21.09.2023; general adjustment(s)

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

AwSV: Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen

AGW: Arbeitsplatzgrenzwert

AVV: Abfallverzeichnisverordnung

CAS Chemical Abstracts Service

CLP: Classification, Labelling and Packaging of substances and mixtures

DNEL: Derived No Effect Level

d: day(s)

EAKV: Europäisches Abfallverzeichnis gemäß Entwurf Abfallverzeichnisverordnung

EINECS: European INventory of Existing Commercial chemical Substances

ELINCS: European List of Notified Chemical Substances

ECHA: European Chemicals Agency

EWC: European Waste Catalogue

IARC: INTERNATIONAL AGENCY FOR RESEARCH ON CANCER

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

GefStoffV: Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany)

h: hour

LOAEL: Lowest observed adverse effect level

LOAEC: Lowest observed adverse effect concentration

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NOAEL: No observed adverse effect level

NOAEC: No observed adverse effect level

NLP: No-Longer Polymers

N/A: not applicable

OECD: Organisation for Economic Co-operation and Development

PNEC: predicted no effect concentration

PBT: Persistent bioaccumulative toxic

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

REACH: Registration, Evaluation, Authorisation of Chemicals

SVHC: substance of very high concern

TRGS Technische Regeln fuer Gefahrstoffe

UN: United Nations

VOC: Volatile Organic Compounds

VwVwS: Verwaltungsvorschrift wassergefaehrdender Stoffe

WGK: Wassergefaehrdungsklasse

CLP: Classification, labelling and Packaging

REACH: Registration, Evaluation and Authorization of Chemicals

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

UN: United Nations

CAS: Chemical Abstracts Service

Safety Data Sheet

according to UK REACH Regulation

Alkaline Alcohol (with KOH)

Revision date: 21.09.2023

Product code: 12437.xxxxx

Page 15 of 16

DNEL: Derived No Effect Level
 DMEL: Derived Minimal Effect Level
 PNEC: Predicted No Effect Concentration
 ATE: Acute toxicity estimate
 LL50: Lethal loading, 50%
 EL50: Effect loading, 50%
 EC50: Effective Concentration 50%
 ErC50: Effective Concentration 50%, growth rate
 NOEC: No Observed Effect Concentration
 BCF: Bio-concentration factor
 PBT: persistent, bioaccumulative, toxic
 vPvB: very persistent, very bioaccumulative
 ADR: Accord européen sur le transport des marchandises dangereuses par Route
 (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 RID: Regulations concerning the international carriage of dangerous goods by rail
 ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
 (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation
 intérieures)
 EmS: Emergency Schedules
 MFAG: Medical First Aid Guide
 MARPOL: International Convention for the Prevention of Marine Pollution from Ships
 IBC: Intermediate Bulk Container
 For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety
 assessment, chapter R.20 (Table of terms and abbreviations).

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Met. Corr. 1; H290	On basis of test data
Flam. Liq. 2; H225	On basis of test data
Eye Irrit. 2; H319	Calculation method

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H290	May be corrosive to metals.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations. Classification according to Regulation (EC) No 1272/2008 [CLP]

- Classification procedure:

Health hazards: Calculation method.

Environmental hazards: Calculation method.

Physical hazards: On basis of test data and / or calculated and / or estimated.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of

Safety Data Sheet

according to UK REACH Regulation

Alkaline Alcohol (with KOH)

Revision date: 21.09.2023

Product code: 12437.xxxxx

Page 16 of 16

processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)