

Safety Data Sheet

according to UK REACH Regulation

Alcoholic nitric acid ~ 10% (Nital)

Revision date: 25.05.2023

Product code: 18169.xxxxx

Page 1 of 15

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Alcoholic nitric acid ~ 10% (Nital)

UFI: EW9M-51FY-W00U-EVU8

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Use as laboratory reagent.

The product is intended for research, analysis and scientific education.

Uses advised against

Any non-intended use.

1.3. Details of the supplier of the safety data sheet

Company name:	MORPHISTO GmbH	
Street:	Schumannstr. 142/144	
Place:	D-63069 Offenbach	
Telephone:	+49 (0) 69 / 400 3019-60	Telefax: +49 (0) 69 / 400 3019-64
e-mail:	info@morphisto.de	
Contact person:	Morphisto GmbH	
e-mail:	gefahrstoffmanagement@morphisto.de	
Internet:	http://www.morphisto.de	

1.4. Emergency telephone number:

Poison Information Center Mainz, Germany, Tel: +49(0)6131/19240

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****GB CLP Regulation**

Met. Corr. 1; H290
Flam. Liq. 2; H225
Skin Corr. 1B; H314
Eye Dam. 1; H318

Full text of hazard statements: see SECTION 16.

2.2. Label elements**GB CLP Regulation****Hazard components for labelling**

nitric acid ... %

Signal word: Danger

Pictograms:**Hazard statements**

H225	Highly flammable liquid and vapour.
H290	May be corrosive to metals.
H314	Causes severe skin burns and eye damage.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
------	--

Safety Data Sheet

according to UK REACH Regulation

Alcoholic nitric acid ~ 10% (Nital)

Revision date: 25.05.2023

Product code: 18169.xxxxx

Page 2 of 15

P260	Do not breathe mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.
P370+P378	In case of fire: Use sand, extinguishing powder or alcohol-resistant foam to extinguish.

Special labelling of certain mixtures

EUH071 Corrosive to the respiratory tract.

Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

Pictograms:


Hazard statements

H314

Precautionary statements

P303+P361+P353-P305+P351+P338-P310

2.3. Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulating and toxic (PBT) or very persistent and very bioaccumulating (vPvB) at levels of 0.1% or higher. Ecological information: The substance/mixture does not contain any components that are considered to be hazardous according to REACH Article 57(f) or Commission Delegated Regulation (EU) 2017/2100 or Commission Delegated Regulation (EU) 2018/605 in amounts of 0.1 % or more have endocrine disrupting properties. Toxicological information: The substance/mixture does not contain any components that are to be classified according to REACH Article 57(f) or Commission Delegated Regulation (EU) 2017/2100 or Commission Delegated Regulation (EU) 2018/605 in quantities of 0.1 % or more have endocrine disrupting properties.

SECTION 3: Composition/information on ingredients
3.2. Mixtures
Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
64-17-5	Ethanol, Ethylalkohol			85 - < 90 %
	200-578-6	603-002-00-5	01-2119457610-43	
	Flam. Liq. 2, Eye Irrit. 2; H225 H319			
7697-37-2	nitric acid ... %			5 - < 10 %
	231-714-2	007-030-00-3	01-2119487297-23	
	Ox. Liq. 3, Met. Corr. 1, Acute Tox. 3, Skin Corr. 1A, Eye Dam. 1; H272 H290 H331 H314 H318 EUH071			
78-93-3	butanone; ethyl methyl ketone			< 1 %
	201-159-0	606-002-00-3	01-2119457290-43	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			

Full text of H and EUH statements: see section 16.

Safety Data Sheet

according to UK REACH Regulation

Alcoholic nitric acid ~ 10% (Nital)

Revision date: 25.05.2023

Product code: 18169.xxxxx

Page 3 of 15

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
64-17-5	200-578-6	Ethanol, Ethylalkohol	85 - < 90 %
		inhalation: LC50 = 124,7 mg/l (vapours); dermal: LD50 = >2000 mg/kg; oral: LD50 = >5000 mg/kg Eye Irrit. 2; H319: >= 50 - 100	
7697-37-2	231-714-2	nitric acid ... %	5 - < 10 %
		inhalation: ATE 2,65 mg/l (vapours) Ox. Liq. 3; H272: >= 65 - 100 Skin Corr. 1A; H314: >= 20 - 100 Skin Corr. 1B; H314: >= 5 - < 20	
78-93-3	201-159-0	butanone; ethyl methyl ketone	< 1 %
		dermal: LD50 = >2000 mg/kg; oral: LD50 = 2054 mg/kg	

Further Information

Product does not contain listed SVHC substances > 0,1 % according to Regulation (EC) No. 1907/2006 Article 59 (REACH)

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove affected person from the danger area and lay down. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Take off immediately all contaminated clothing.

First aider: Pay attention to self-protection!

After inhalation

Provide fresh air. When in doubt or if symptoms are observed, get medical advice. Remove person to fresh air and keep comfortable for breathing. In case of respiratory tract irritation, consult a physician. In the case of lung irritation: Primary treatment using corticoide spray, eg. Auxiloson spray, Pulmicort-dosage-spray. (Auxiloson and Pulmicort are registered trademarks.)

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. Take off immediately all contaminated clothing.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

After ingestion

Observe risk of aspiration if vomiting occurs. Rinse mouth immediately and drink plenty of water. Adverse human health effects and symptoms: Gastric perforation. Call a physician immediately. Do not allow a neutralisation agent to be drunk. Rinse mouth thoroughly with water. Let water be drunken in little sips (dilution effect). Do NOT induce vomiting. Never give anything by mouth to an unconscious person or a person with cramps. In all cases of doubt, or when symptoms persist, seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water spray jet, Carbon dioxide (CO₂), Foam, Extinguishing powder. Carbon dioxide (CO₂). Dry extinguishing

Safety Data Sheet

according to UK REACH Regulation

Alcoholic nitric acid ~ 10% (Nital)

Revision date: 25.05.2023

Product code: 18169.xxxxx

Page 4 of 15

powder. alcohol resistant foam.

In case of major fire and large quantities: Atomized water.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Highly flammable. Vapours can form explosive mixtures with air. In case of fire may be liberated:
Gases/vapours, irritant. Carbon monoxide Carbon dioxide (CO₂). Nitrogen oxides (NO_x)

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit. In case of fire and/or explosion do not breathe fumes.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Use water spray jet to protect personnel and to cool endangered containers.
In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Remove all sources of ignition. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment. Remove persons to safety. Remove all sources of ignition. Ventilate affected area.

Avoid contact with skin, eyes and clothes.

Wear personal protection equipment (refer to section 8).

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Explosion risk. Do not allow to enter into surface water or drains. Cover drains. Prevent spread over a wide area (e.g. by containment or oil barriers). In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up**Other information**

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Ventilate affected area.

Treat the recovered material as prescribed in the section on waste disposal.

Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray. Provide adequate ventilation as well as local exhaustion at critical locations.

Avoid contact with skin, eyes and clothes.

Wear suitable protective clothing. (See section 8.)

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges.

Vapours can form explosive mixtures with air. Flammable vapours can accumulate in head space of closed systems. Heating causes rise in pressure with risk of bursting.

Safety Data Sheet

according to UK REACH Regulation

Alcoholic nitric acid ~ 10% (Nital)

Revision date: 25.05.2023

Product code: 18169.xxxxx

Page 5 of 15

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat, drink, smoke, sniff. The usual precautions for handling chemicals should be considered.

Always close containers tightly after the removal of product. Protect skin by using skin protective cream. Take off contaminated clothing and wash it before reuse.

Further information on handling

General protection and hygiene measures: See section 8.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaust at critical locations. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Protect from direct sunlight.

Ensure adequate ventilation of the storage area.

Make sure spills can be contained (e.g. sump pallets or kerbed areas).

Hints on joint storage

Do not store together with: Oxidizing agent. Pyrophoric or self-heating substances. Do not store together with: Gas. Explosives. Flammable solids. Pyrophoric liquids and solids. Self-heating substances and mixtures.

Substances or mixtures which, in contact with water, emit flammable gases. Oxidizing liquids. Oxidizing solids. ammonium nitrate. Self-reactive substances and mixtures. Organic peroxides. Non-combustible toxic substances. Radioactive substances. Infectious substances.

Further information on storage conditions

Keep the packing dry and well sealed to prevent contamination and absorption of humidity.

Protect against: UV-radiation/sunlight. heat. Humidity frost.

storage temperature: 15-25°C

7.3. Specific end use(s)

See section 1.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
78-93-3	Butan-2-one (methyl ethyl ketone)	200	600		TWA (8 h)	WEL
		300	899		STEL (15 min)	WEL
64-17-5	Ethanol	1000	1920		TWA (8 h)	WEL
7697-37-2	Nitric acid	1	2.6		STEL (15 min)	WEL

Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
78-93-3	Butan-2-one	butan-2-one	70 µmol/L	urine	Post shift

Safety Data Sheet

according to UK REACH Regulation

Alcoholic nitric acid ~ 10% (Nital)

Revision date: 25.05.2023

Product code: 18169.xxxxx

Page 6 of 15

DNEL/DMEL values

CAS No	Substance		
DNEL type	Exposure route	Effect	Value
64-17-5	Ethanol, Ethylalkohol		
Worker DNEL, acute	inhalation	local	1900 mg/m ³
Worker DNEL, long-term	dermal	systemic	343 mg/kg bw/day
Worker DNEL, long-term	inhalation	systemic	950 mg/m ³
Consumer DNEL, acute	inhalation	local	950 mg/m ³
Consumer DNEL, long-term	dermal	systemic	206 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	114 mg/m ³
Consumer DNEL, long-term	oral	systemic	87 mg/kg bw/day

PNEC values

CAS No	Substance	
Environmental compartment	Value	
64-17-5	Ethanol, Ethylalkohol	
Freshwater	0,96 mg/l	
Freshwater (intermittent releases)	2,75 mg/l	
Marine water	0,79 mg/l	
Marine water (intermittent releases)	2,75 mg/l	
Freshwater sediment	3,6 mg/kg	
Marine sediment	2,9 mg/kg	
Secondary poisoning	0,72 mg/kg	
Micro-organisms in sewage treatment plants (STP)	580 mg/l	
Soil	0,63 mg/kg	

8.2. Exposure controls



Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray. Provide adequate ventilation as well as local exhaustion at critical locations.

Individual protection measures, such as personal protective equipment

Eye/face protection

Suitable eye protection: goggles. Recommended eye protection brand: Tightly sealed safety glasses. (EN 166)

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. In case of prolonged or frequently repeated skin contact: Wear suitable gloves.

Suitable material: Butyl rubber.

Thickness of glove material: 0,5 mm

Breakthrough time >= 480 min. penetration time (maximum wearing period): ~ 120 min. (estimated)

In the case of wanting to use the gloves again, clean them before taking off and air them well. Before using check leak tightness / impermeability.

Safety Data Sheet

according to UK REACH Regulation

Alcoholic nitric acid ~ 10% (Nital)

Revision date: 25.05.2023

Product code: 18169.xxxxx

Page 7 of 15

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it.

Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing. Wear fire resistant or flame retardant clothing.

Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500 (D).

Respiratory protection

In case of inadequate ventilation wear respiratory protection. With correct and proper use, and under normal conditions, breathing protection is not required.

Respiratory protection necessary at:

exceeding exposure limit values

Insufficient ventilation.

Suitable respiratory protective equipment: gas filtering equipment (EN 141). Type: A

The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.

Environmental exposure controls

Do not allow uncontrolled discharge of product into the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	liquid	
Colour:	slightly yellowish	
Odour:	characteristic	
Melting point/freezing point:		not applicable
Boiling point or initial boiling point and boiling range:		78 (Ethanol.) °C
Flammability:		not applicable
Lower explosion limits:		not determined
Upper explosion limits:		not determined
Flash point:		12 °C
Auto-ignition temperature:		not determined
Decomposition temperature:		not determined
pH-Value:		not determined
Viscosity / kinematic: (at 20 °C)		not determined
Water solubility:		miscible.
Solubility in other solvents		not determined
Partition coefficient n-octanol/water:		not determined
Vapour pressure: (at 20 °C)		not determined
Density:		not determined
Relative vapour density:		not determined

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

The product is not: Explosive.

Self-ignition temperature

Safety Data Sheet

according to UK REACH Regulation

Alcoholic nitric acid ~ 10% (Nital)

Revision date: 25.05.2023

Product code: 18169.xxxxx

Page 8 of 15

Solid:	not applicable
Gas:	not applicable
Oxidizing properties	
none.	
Other safety characteristics	
Evaporation rate:	not determined
Solvent separation test:	not determined
Solvent content:	not determined
Solid content:	not determined
Viscosity / dynamic:	not determined
(at 40 °C)	
Flow time:	not determined

SECTION 10: Stability and reactivity**10.1. Reactivity**

Highly flammable. No information available.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Refer to chapter 10.5.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. Keep away from heat!

In use may form flammable/explosive vapour-air mixture.

Heating causes rise in pressure with risk of bursting.

10.5. Incompatible materials

Materials to avoid: Oxidizing agents, strong. Reducing agents, strong. Strong acid. strong alkalis.

10.6. Hazardous decomposition products

In case of fire may be liberated: Gas/vapours, irritant. Carbon monoxide Carbon dioxide (CO₂). Nitrogen oxides (NO_x)

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in GB CLP Regulation****Toxicokinetics, metabolism and distribution**

Adsorption.

Ethanol has a low molecular weight and has a good water and fat solubility. Therefore it can be adsorbed well in the entire gastrointestinal tract, lungs and the skin. After swallowing approximately 90% is taken up via the gastrointestinal tract. When inhaled, this value is 61%. Because of the rapid evaporation of ethanol the dermal adsorption is very limited; theoretically 21% can be accommodated, however, the absorption rate of uncovered skin is only 1 to 2%.

Distribution:

Regardless of the exposure pathway ethanol is distributed via the bloodstream throughout the body, comparable to the distribution of water. Highly perfused organs (brain, lung and liver) are passed quickly. An equal distribution between tissue and blood is reached after 1 to 1.5 h.

metabolism:

Even before the absorption a small proportion of ethanol is enzymatically metabolized in the stomach (alcohol dehydrogenase). After absorption ethanol is preferably metabolized in the liver (92-95%) and partly in the kidneys and lungs. Metabolism occurs usually in three steps: 1. oxidation of ethanol to acetaldehyde; 2. oxidation of acetaldehyde to acetate; 3. oxidation of acetate to carbon dioxide and water

Safety Data Sheet

according to UK REACH Regulation

Alcoholic nitric acid ~ 10% (Nital)

Revision date: 25.05.2023

Product code: 18169.xxxxx

Page 9 of 15

elimination:

The vast majority of ethanol is eliminated by metabolism, the excretion via breath, urine and sweat plays a minor role. The maximum elimination of ethanol is estimated on the 127 mg / kgbw / h.

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (inhalation vapour) 30,00 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64-17-5	Ethanol, Ethylalkohol				
	oral	LD50 >5000 mg/kg	Rat	ECHA Dossier	
	dermal	LD50 >2000 mg/kg	Rabbit	ECHA Dossier	
	inhalation (4 h) vapour	LC50 124,7 mg/l	Rat	ECHA Dossier	
7697-37-2	nitric acid ... %				
	inhalation vapour	ATE 2,65 mg/l			
78-93-3	butanone; ethyl methyl ketone				
	oral	LD50 2054 mg/kg	Ratte	SDB Lieferant	
	dermal	LD50 >2000 mg/kg	Rabbit	ECHA Dossier	

Irritation and corrosivity

Causes severe skin burns and eye damage.

Causes serious eye damage.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

Ethanol. (CAS-No.: 64-17-5):

In-vitro mutagenicity: No experimental indications of mutagenicity in-vitro exist.

Reproductive toxicity: Exposure time: 18 weeks; Species: CD-1 Mouse. Method: OECD Guideline 416; Result:

NOAEL = 20700 mg/kg/day. Developmental toxicity/teratogenicity: Exposure time: 19d; Species:

Sprague-Dawley Rat. Method: OECD Guideline 414; Result: NOAEL = 16000 ppm (maternal toxicity), Result:

NOAEL >= 20000 ppm (teratogenicity); Literature information: ECHA Dossier

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Ethanol. (CAS-No.: 64-17-5):

Subchronic oral toxicity: Exposure time: 90d; Species: Sprague-Dawley Rat. Method: OECD Guideline 408;

Result: NOAEL = 1280 mg/kg; Literature information: ECHA Dossier

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Safety Data Sheet

according to UK REACH Regulation

Alcoholic nitric acid ~ 10% (Nital)

Revision date: 25.05.2023

Product code: 18169.xxxxx

Page 10 of 15

11.2. Information on other hazards

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

Other information

Depending on the ingested quantity the following symptoms can be induced: a reduction of inhibitions, euphoria but also dysphoria, aggressiveness, impaired motoric skills, impaired responsiveness, blurred vision and fatigue.

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
64-17-5	Ethanol, Ethylalkohol					
	Acute fish toxicity	LC50 mg/l	14200	96 h	Pimephales promelas (fathead minnow)	ECHA Dossier
	Acute algae toxicity	ErC50	275 mg/l	72 h	Chlorella vulgaris	ECHA Dossier
	Acute crustacea toxicity	EC50 mg/l	5012	48 h	Ceriodaphnia dubia (water flea)	ECHA Dossier
	Crustacea toxicity	NOEC	9,6 mg/l	9 d	Daphnia magna	ECHA Dossier
78-93-3	butanone; ethyl methyl ketone					
	Acute fish toxicity	LC50 mg/l	2993	96 h	Pimephales promelas	ECHA Dossier OECD 203
	Acute algae toxicity	ErC50 mg/l	1972	72 h	Pseudokirchnerella subcapitata	ECHA Dossier OECD 201
	Acute crustacea toxicity	EC50	308 mg/l	48 h	Daphnia magna	ECHA Dossier OECD 202

12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
64-17-5	Ethanol, Ethylalkohol			
	other guideline	84%	20	ECHA Dossier
	Biodegradable.			
78-93-3	butanone; ethyl methyl ketone			
		98%	28	ECHA Dossier
	Readily biodegradable (according to OECD criteria).			

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
64-17-5	Ethanol, Ethylalkohol	-0,31
78-93-3	butanone; ethyl methyl ketone	0,3

12.4. Mobility in soil

The product has not been tested. .

12.5. Results of PBT and vPvB assessment

Safety Data Sheet

according to UK REACH Regulation

Alcoholic nitric acid ~ 10% (Nital)

Revision date: 25.05.2023

Product code: 18169.xxxxx

Page 11 of 15

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

The product has not been tested.

Further information

Avoid release to the environment. Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation. Dispose of waste according to applicable legislation. Consult the local waste disposal expert about waste disposal. Non-contaminated packages may be recycled. According to (EWC) European Waste Catalogue, allocation of waste identity numbers/waste descriptions must be carried out in a specific way for every industry and process. Control report for waste code/ waste marking according to (EWC) European Waste Catalogue:

List of Wastes Code - residues/unused products

160506 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; laboratory chemicals, consisting of or containing hazardous substances, including mixtures of laboratory chemicals; hazardous waste

List of Wastes Code - used product

160506 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; laboratory chemicals, consisting of or containing hazardous substances, including mixtures of laboratory chemicals; hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Wash with plenty of water. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number or ID number:	UN 2924
14.2. UN proper shipping name:	FLAMMABLE LIQUID, CORROSIVE, N.O.S. (Ethanol, Nitric acid)
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3+8



Classification code:	FC
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	338

Safety Data Sheet

according to UK REACH Regulation

Alcoholic nitric acid ~ 10% (Nital)

Revision date: 25.05.2023

Product code: 18169.xxxxx

Page 12 of 15

Tunnel restriction code: D/E

Marine transport (IMDG)

14.1. UN number or ID number: UN 2924
14.2. UN proper shipping name: FLAMMABLE LIQUID, CORROSIVE, N.O.S. (ethanol, nitric acid)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3+8



Special Provisions: 274
 Limited quantity: 1 L
 Excepted quantity: E2
 EmS: F-E, S-C

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 2924
14.2. UN proper shipping name: FLAMMABLE LIQUID, CORROSIVE, N.O.S. (ethanol, nitric acid)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3+8



Special Provisions: A3
 Limited quantity Passenger: 0.5 L
 Passenger LQ: Y340
 Excepted quantity: E2
 IATA-packing instructions - Passenger: 352
 IATA-max. quantity - Passenger: 1 L
 IATA-packing instructions - Cargo: 363
 IATA-max. quantity - Cargo: 5 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: Combustible liquid. strongly corrosive. See section 8.

14.7. Maritime transport in bulk according to IMO instruments

not relevant.

SECTION 15: Regulatory information
15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture
EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

2010/75/EU (VOC): 86,41 %
 2004/42/EC (VOC): not determined
 Information according to 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

Additional information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Safety Data Sheet

according to UK REACH Regulation

Alcoholic nitric acid ~ 10% (Nital)

Revision date: 25.05.2023

Product code: 18169.xxxxx

Page 13 of 15

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

Ethanol, Ethylalkohol

nitric acid ... %

butanone; ethyl methyl ketone

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 2,4,5,6,7,9,10,11,12,14,15,16.

Rev. 1.0; Initial release: 20.11.2018

Rev. 2.0; general adjustment(s)

Rev. 2,1; 25.05.2023; general adjustment(s)

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

AwSV: Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen

AGW: Arbeitsplatzgrenzwert

AVV: Abfallverzeichnisverordnung

CAS Chemical Abstracts Service

CLP: Classification, Labelling and Packaging of substances and mixtures

DNEL: Derived No Effect Level

d: day(s)

EAKV: Europäisches Abfallverzeichnis gemäß Entwurf Abfallverzeichnisverordnung

EINECS: European INventory of Existing Commercial chemical Substances

ELINCS: European List of Notified Chemical Substances

ECHA: European Chemicals Agency

EWC: European Waste Catalogue

IARC: INTERNATIONAL AGENCY FOR RESEARCH ON CANCER

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

GefStoffV: Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany)

h: hour

LOAEL: Lowest observed adverse effect level

LOAEC: Lowest observed adverse effect concentration

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NOAEL: No observed adverse effect level

NOAEC: No observed adverse effect level

NLP: No-Longer Polymers

N/A: not applicable

OECD: Organisation for Economic Co-operation and Development

PNEC: predicted no effect concentration

PBT: Persistent bioaccumulative toxic

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

REACH: Registration, Evaluation, Authorisation of Chemicals

Safety Data Sheet

according to UK REACH Regulation

Alcoholic nitric acid ~ 10% (Nital)

Revision date: 25.05.2023

Product code: 18169.xxxxx

Page 14 of 15

SVHC: substance of very high concern
 TRGS Technische Regeln fuer Gefahrstoffe
 UN: United Nations
 VOC: Volatile Organic Compounds
 VwVwS: Verwaltungsvorschrift wassergefaehrdender Stoffe
 WGK: Wassergefaehrungsklasse
 CLP: Classification, labelling and Packaging
 REACH: Registration, Evaluation and Authorization of Chemicals
 GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals
 UN: United Nations
 CAS: Chemical Abstracts Service
 DNEL: Derived No Effect Level
 DMEL: Derived Minimal Effect Level
 PNEC: Predicted No Effect Concentration
 ATE: Acute toxicity estimate
 LL50: Lethal loading, 50%
 EL50: Effect loading, 50%
 EC50: Effective Concentration 50%
 ErC50: Effective Concentration 50%, growth rate
 NOEC: No Observed Effect Concentration
 BCF: Bio-concentration factor
 PBT: persistent, bioaccumulative, toxic
 vPvB: very persistent, very bioaccumulative
 ADR: Accord européen sur le transport des marchandises dangereuses par Route
 (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 RID: Regulations concerning the international carriage of dangerous goods by rail
 ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
 (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation
 intérieures)
 EmS: Emergency Schedules
 MFAG: Medical First Aid Guide
 MARPOL: International Convention for the Prevention of Marine Pollution from Ships
 IBC: Intermediate Bulk Container
 For abbreviations and acronyms, see table at <http://abbrev.esdscom.eu>

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Met. Corr. 1; H290	On basis of test data
Flam. Liq. 2; H225	On basis of test data
Skin Corr. 1B; H314	Calculation method
Eye Dam. 1; H318	Calculation method

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H272	May intensify fire; oxidiser.
H290	May be corrosive to metals.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H336	May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH071	Corrosive to the respiratory tract.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of

Safety Data Sheet

according to UK REACH Regulation

Alcoholic nitric acid ~ 10% (Nital)

Revision date: 25.05.2023

Product code: 18169.xxxxx

Page 15 of 15

product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations. Classification according to Regulation (EC) No 1272/2008 [CLP]

- Classification procedure:

Health hazards: Calculation method.

Environmental hazards: Calculation method.

Physical hazards: On basis of test data and / or calculated and / or estimated.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)