

## Safety Data Sheet

according to UK REACH Regulation

### Ethanol 50 %, denatured (MEK/IPA/BTX)

Revision date: 27.03.2024

Product code: 11575.xxxxx

Page 1 of 17

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Ethanol 50 %, denatured (MEK/IPA/BTX)

UFI: KS11-Q14A-800K-JUAU

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Use as laboratory reagent. The product is intended for research, analysis and scientific education.

#### Uses advised against

Any non-intended use.

### 1.3. Details of the supplier of the safety data sheet

Company name: MORPHISTO GmbH  
Street: Schumannstr. 142/144  
Place: D-63069 Offenbach  
Telephone: +49 (0) 69 / 400 3019-60      Telefax: +49 (0) 69 / 400 3019-64  
E-mail: info@morphisto.de  
Contact person: Morphisto GmbH  
E-mail: gefahrstoffmanagement@morphisto.de  
Internet: http://www.morphisto.de

### 1.4. Emergency telephone number:

Poison Information Center Mainz, Germany, Tel: +49(0)6131/19240

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### GB CLP Regulation

Flam. Liq. 2; H225

Eye Irrit. 2; H319

Full text of hazard statements: see SECTION 16.

### 2.2. Label elements

#### GB CLP Regulation

Signal word: Danger

#### Pictograms:



#### Hazard statements

H225 Highly flammable liquid and vapour.  
H319 Causes serious eye irritation.

#### Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P337+P313 If eye irritation persists: Get medical advice/attention.

#### Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

**Safety Data Sheet**

according to UK REACH Regulation

**Ethanol 50 %, denatured (MEK/IPA/BTX)**

Revision date: 27.03.2024

Product code: 11575.xxxxx

Page 2 of 17

**Pictograms:**

**2.3. Other hazards**

This substance/mixture contains no components considered to be either persistent, bioaccumulating and toxic (PBT) or very persistent and very bioaccumulating (vPvB) at levels of 0.1% or higher. Ecological information: The substance/mixture does not contain any components that are considered to be hazardous according to REACH Article 57(f) or Commission Delegated Regulation (EU) 2017/2100 or Commission Delegated Regulation (EU) 2018/605 in amounts of 0.1 % or more have endocrine disrupting properties. Toxicological information: The substance/mixture does not contain any components that are to be classified according to REACH Article 57(f) or Commission Delegated Regulation (EU) 2017/2100 or Commission Delegated Regulation (EU) 2018/605 in quantities of 0.1 % or more have endocrine disrupting properties.

**SECTION 3: Composition/information on ingredients**
**3.2. Mixtures**
**Relevant ingredients**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
64-17-5	ethanol			50 - < 55 %
	200-578-6	603-002-00-5	01-2119457610-43	
	Flam. Liq. 2, Eye Irrit. 2; H225 H319			
67-63-0	2-propanol			< 1 %
	200-661-7	603-117-00-0	01-2119457558-25	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336			
78-93-3	butanone			< 1 %
	201-159-0	606-002-00-3	01-2119457290-43	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
3734-33-6	Denatoniumbenzoate			< 1 %
	223-095-2			
	Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Dam. 1, Aquatic Chronic 3; H332 H302 H315 H318 H412			

Full text of H and EUH statements: see section 16.

**Specific Conc. Limits, M-factors and ATE**

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
64-17-5	200-578-6	ethanol	50 - < 55 %
		inhalation: LC50 = 124,7 mg/l (vapours); dermal: LD50 = >2000 mg/kg; oral: LD50 = >5000 mg/kg Eye Irrit. 2; H319: >= 50 - 100	
67-63-0	200-661-7	2-propanol	< 1 %
		dermal: LD50 = >5000 mg/kg; oral: LD50 = >5000 mg/kg	
78-93-3	201-159-0	butanone	< 1 %
		dermal: LD50 = >2000 mg/kg; oral: LD50 = 2054 mg/kg	
3734-33-6	223-095-2	Denatoniumbenzoate	< 1 %
		inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = >2000 mg/kg; oral: ATE = 500 mg/kg	

**Safety Data Sheet**

according to UK REACH Regulation

**Ethanol 50 %, denatured (MEK/IPA/BTX)**

Revision date: 27.03.2024

Product code: 11575.xxxxx

Page 3 of 17

**Further Information**

This product contains no substances of very high concern (SVHC) (>0,1%) which are included in the Candidate List according to Article 59 of REACH.

**SECTION 4: First aid measures****4.1. Description of first aid measures****General information**

First aider: Pay attention to self-protection! Remove affected person from the danger area and lay down. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

**After inhalation**

Provide fresh air. If unconscious but breathing normally, place in recovery position and seek medical advice. In case of allergic symptoms, especially in the breathing area, seek medical advice immediately.

**After contact with skin**

Wash with plenty of water. Take off contaminated clothing and wash it before reuse. In case of skin irritation, seek medical treatment.

**After contact with eyes**

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

**After ingestion**

Observe risk of aspiration if vomiting occurs. Rinse mouth thoroughly with water. Let water be drunken in little sips (dilution effect). Seek medical advice.

**4.2. Most important symptoms and effects, both acute and delayed**

No information available.

**4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptomatically. Percutaneously absorbed and inhaled substance causes next to irritation of affected mucous membranes only an indicated impairment of the inhibitory functions of the central nervous system, clinically recognizable as the beginning of a euphoric stage. At the same time face and skin redness is caused by dilation of peripheral blood vessels in the body.

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**

Water spray jet, Carbon dioxide (CO<sub>2</sub>), Foam, Extinguishing powder.  
Co-ordinate fire-fighting measures to the fire surroundings.

**Unsuitable extinguishing media**

High power water jet.

**5.2. Special hazards arising from the substance or mixture**

Highly flammable. Vapours can form explosive mixtures with air. Vapours are heavier than air and will spread at floor level. In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO<sub>2</sub>).Nitrogen oxides (NO<sub>x</sub>).

**5.3. Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus. In case of fire and/or explosion do not breathe fumes. In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion.

**Additional information**

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

**SECTION 6: Accidental release measures**

**Safety Data Sheet**

according to UK REACH Regulation

**Ethanol 50 %, denatured (MEK/IPA/BTX)**

Revision date: 27.03.2024

Product code: 11575.xxxxx

Page 4 of 17

**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment. Ventilate affected area. Special danger of slipping by leaking/spilling product.

**For non-emergency personnel**

Ventilate affected area. Remove all sources of ignition. Remove product from area of fire. Consult an expert. Move undamaged containers from immediate hazard area if it can be done safely.

**For emergency responders**

Move undamaged containers from immediate hazard area if it can be done safely. Remove all sources of ignition.

**6.2. Environmental precautions**

Do not allow uncontrolled discharge of product into the environment. Explosion risk. Do not allow to enter into surface water or drains. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Prevent spread over a wide area (e.g. by containment or oil barriers). In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

**6.3. Methods and material for containment and cleaning up****For containment**

Seal off the sewer. Collect, embank and pump out. Observe possible material restrictions (section 10). Provide earthing of containers, equipment, pumps and ventilation facilities.

**For cleaning up**

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Ventilate affected area. Clear contaminated areas thoroughly.

**6.4. Reference to other sections**

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

**SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

Provide adequate ventilation as well as local exhaust at critical locations. If handled uncovered, arrangements with local exhaust ventilation have to be used. In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Wear personal protection equipment. (See section 8.) Always close containers tightly after the removal of product.

**Advice on protection against fire and explosion**

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air. Use non-sparking tools. Flammable vapours can accumulate in head space of closed systems. Heating causes rise in pressure with risk of bursting. Have fire-extinguishers in readiness before opening containers. Wear anti-static footwear and clothing. Ground and bond container and receiving equipment.

**Advice on general occupational hygiene**

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat, drink, smoke, sniff. Ensure cleanliness and dryness in the workplace. Take off contaminated clothing and wash it before reuse. Contaminated work clothing should not be allowed out of the workplace. Street clothing should be stored separately from work clothing. Always close containers tightly after the removal of product.

**7.2. Conditions for safe storage, including any incompatibilities**

## Safety Data Sheet

according to UK REACH Regulation

### Ethanol 50 %, denatured (MEK/IPA/BTX)

Revision date: 27.03.2024

Product code: 11575.xxxxx

Page 5 of 17

#### Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ensure adequate ventilation of the storage area. Provide adequate ventilation as well as local exhaustion at critical locations. Store in a place accessible by authorized persons only. Keep/Store only in original container. Protect from direct sunlight. Concentrated vapours are heavier than air. Suitable material for Container: Stainless steel. iron. solvent resistant plastics. Unsuitable materials for Container: Aluminium. Rubber. various plastics. Make sure spills can be contained, e.g. in sump pallets or kerbed areas.

#### Hints on joint storage

Do not store together with: Oxidizing agent. Pyrophoric or self-heating substances. Do not store together with: food and feed. pharmaceuticals. Infectious substances. Radioactive substances. Explosive substances. Oxidizing substances. Oxidizing liquids. Organic peroxides. Self-reactive substances and mixtures. Pyrophoric solids. Substances which in contact with water form flammable gases. Ammonium nitrate and preparations containing ammonium nitrate. Gas. Flammable solids. Pyrophoric liquids and solids. Self-heating substances and mixtures. Non-combustible toxic substances.

#### Further information on storage conditions

Recommended storage temperature: 15-25°C  
 Protect against: UV-radiation/sunlight. heat. Cold.  
 Store in a cool dry place.

#### 7.3. Specific end use(s)

Use as laboratory reagent. The product is intended for research, analysis and scientific education.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
78-93-3	Butan-2-one (methyl ethyl ketone)	200	600		TWA (8 h)	WEL
		300	899		STEL (15 min)	WEL
64-17-5	Ethanol	1000	1920		TWA (8 h)	WEL
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL

#### Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
78-93-3	Butan-2-one	butan-2-one	70 µmol/L	urine	Post shift

**Safety Data Sheet**

according to UK REACH Regulation

**Ethanol 50 %, denatured (MEK/IPA/BTX)**

Revision date: 27.03.2024

Product code: 11575.xxxxx

Page 6 of 17

**DNEL/DMEL values**

CAS No	Substance	Exposure route	Effect	Value
64-17-5	ethanol			
Worker DNEL, acute		inhalation	local	1900 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	343 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	950 mg/m <sup>3</sup>
Consumer DNEL, acute		inhalation	local	950 mg/m <sup>3</sup>
Consumer DNEL, long-term		dermal	systemic	206 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	114 mg/m <sup>3</sup>
Consumer DNEL, long-term		oral	systemic	87 mg/kg bw/day
67-63-0	2-propanol			
Worker DNEL, long-term		inhalation	systemic	500 mg/m <sup>3</sup>
Consumer DNEL, long-term		inhalation	systemic	89 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	888 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	26 mg/kg bw/day
Consumer DNEL, long-term		dermal	systemic	319 mg/kg bw/day
78-93-3	butanone			
Worker DNEL, long-term		inhalation	systemic	600 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	1161 mg/kg bw/day

**Safety Data Sheet**

according to UK REACH Regulation

**Ethanol 50 %, denatured (MEK/IPA/BTX)**

Revision date: 27.03.2024

Product code: 11575.xxxxx

Page 7 of 17

**PNEC values**

CAS No	Substance	Value
Environmental compartment		
64-17-5	ethanol	
Freshwater		0,96 mg/l
Freshwater (intermittent releases)		2,75 mg/l
Marine water		0,79 mg/l
Marine water (intermittent releases)		2,75 mg/l
Freshwater sediment		3,6 mg/kg
Marine sediment		2,9 mg/kg
Secondary poisoning		0,72 mg/kg
Micro-organisms in sewage treatment plants (STP)		580 mg/l
Soil		0,63 mg/kg
67-63-0	2-propanol	
Freshwater		140,9 mg/l
Marine water		140,9 mg/l
Freshwater sediment		552 mg/kg
Marine sediment		552 mg/kg
Secondary poisoning		160 mg/kg
Soil		28 mg/kg
78-93-3	butanone	
Freshwater		55,8 mg/l
Freshwater (intermittent releases)		55,8 mg/l
Marine water		55,8 mg/l
Freshwater sediment		284,7 mg/kg
Marine sediment		284,7 mg/kg
Micro-organisms in sewage treatment plants (STP)		709 mg/l
Soil		22,5 mg/kg

**8.2. Exposure controls**

**Appropriate engineering controls**

Technical measures and the application of suitable work processes have priority over personal protection equipment. Provide adequate ventilation. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means. Fire extinguishing equipment shall be provided. Provide washing facilities at the workplace, provide an eye shower or eyewash bottle and mark them. The floor should not have a floor drain.

**Individual protection measures, such as personal protective equipment**
**Eye/face protection**

Suitable eye protection: goggles. Tightly sealed safety glasses. Eye glasses with side protection. EN 166

**Hand protection**

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the

## Safety Data Sheet

according to UK REACH Regulation

### Ethanol 50 %, denatured (MEK/IPA/BTX)

Revision date: 27.03.2024

Product code: 11575.xxxxx

Page 8 of 17

specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. In case of prolonged or frequently repeated skin contact:

Tested protective gloves are to be worn:

Suitable material:

Butyl rubber. 0,7 mm, penetration time (maximum wearing period):  $\geq 480$  min;

NBR (Nitrile rubber). 0,4 mm, Breakthrough time  $\geq 120$  min.

Before using check leak tightness / impermeability.

#### Skin protection

Protective clothing. Lab apron. (fire retardant.). Wear anti-static footwear and clothing

Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500 (D).

#### Respiratory protection

In case of inadequate ventilation wear respiratory protection. With correct and proper use, and under normal conditions, breathing protection is not required.

Respiratory protection necessary at: Insufficient ventilation. exceeding exposure limit values.

generation/formation of aerosols.

Suitable respiratory protective equipment:

gas filtering equipment (EN 141). Type : a. Identification color: brown.

The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.

The wearing time limitations according to GefStoffV in conjunction with the rules for the use of respiratory protective devices (BGR 190) must be observed.

#### Thermal hazards

Flame-retardant protective clothing. Wear anti-static footwear and clothing

#### Environmental exposure controls

Do not allow to enter into surface water or drains. Make sure spills can be contained (e.g. sump pallets or kerbed areas).

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	liquid	
Colour:	transparent	
Odour:	alcoholic	
Melting point/freezing point:		not determined
Boiling point or initial boiling point and boiling range:		78 °C
Flammability:		not applicable not applicable
Lower explosion limits:		2,5
Upper explosion limits:		15
Flash point:		<23 °C
Auto-ignition temperature:		400 °C
Decomposition temperature:		not determined
pH-Value:		not determined
Viscosity / kinematic:		not determined
Water solubility:		not determined
Solubility in other solvents		
not determined		
Partition coefficient n-octanol/water:		not determined



**Safety Data Sheet**

according to UK REACH Regulation

**Ethanol 50 %, denatured (MEK/IPA/BTX)**

Revision date: 27.03.2024

Product code: 11575.xxxxx

Page 9 of 17

Vapour pressure: (at 20 °C)	58 hPa
Vapour pressure: (at 50 °C)	293 hPa
Density (at 20 °C):	0,88 g/cm <sup>3</sup>
Relative vapour density:	not determined
Particle characteristics:	not applicable

**9.2. Other information****Information with regard to physical hazard classes****Explosive properties**

The product is not: Explosive. In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop. Vapours can travel considerable distances to a source of ignition where they can ignite, flash back, or explode.

**Self-ignition temperature**

Gas: not determined

**Oxidizing properties**

Flammable. In use may form flammable/explosive vapour-air mixture.

**Other safety characteristics**

Evaporation rate: not determined

**SECTION 10: Stability and reactivity****10.1. Reactivity**

Thermal decomposition. Heating may cause a fire or explosion. Vapours can form explosive mixtures with air.

**10.2. Chemical stability**

The product is stable under storage at normal ambient temperatures.

**10.3. Possibility of hazardous reactions**

Chlorine, potassium, sodium, strong oxidising agents, nitric acid, calcium hypochlorite, halogen oxides, di-sulphur difluoride, acetic anhydride + salts + acids, isocyanates, potassium dioxide, perchlorates, potassium permanganate/sulphuric acid, sodium hypochlorite, sodium peroxide, nitrosyl perchlorate, peracids, perchloronitrile, mercury nitrate, oxygen (liquid), sulphuric acid + hydrogen peroxide, silver/nitric acid, silver nitrate, silver nitrate/ammonia, silver oxide/ammonia, nitrogen dioxide, hydrogen peroxide, conc. Alkali/alkaline earth metals, fluorine, reducing agents, acids, acetyl bromide, acetyl chloride, barium perchlorate, bromine trifluoride, cesium oxide, chromium trioxide, chromyl chloride, ethylene oxide, iodine heptafluoride, potassium tert-butoxide, potassium tert-butoxide, butoxide, lithium hydride, phosphorus trioxide, platinum black, nitric acid/potassium permanganate, acid anhydrides, uranium hexafluoride, zirconium (IV) chloride, zirconium (IV) iodide. Alkali metals. Alkaline earth metals. Reducing agents, strong.

**10.4. Conditions to avoid**

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. Keep away from heat. Protect from direct sunlight. Protect from moisture. In use may form flammable/explosive vapour-air mixture.

Heating causes rise in pressure with risk of bursting.

**10.5. Incompatible materials**

Strong acid. Oxidizing agents. Alkali metals. Alkaline earth metals. Peroxides. phosphorus oxides. Nitrogen oxides (NOx). Hydrogenium peroxide. Nitric acid. hydrochloric acid. Sulfuric acid. Perchlorates. Chromium oxides. Acid chlorides.

**10.6. Hazardous decomposition products**

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO<sub>2</sub>). Nitrogen oxides (NOx).

**SECTION 11: Toxicological information****11.1. Information on hazard classes as defined in GB CLP Regulation**

**Safety Data Sheet**

according to UK REACH Regulation

**Ethanol 50 %, denatured (MEK/IPA/BTX)**

Revision date: 27.03.2024

Product code: 11575.xxxxx

Page 10 of 17

**Acute toxicity**

Based on available data, the classification criteria are not met.

**ATEmix calculated**

ATE (oral) &gt; 2000 mg/kg; ATE (dermal) &gt; 2000 mg/kg; ATE (inhalation vapour) &gt; 20 mg/l; ATE (inhalation dust/mist) &gt; 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64-17-5	ethanol				
	oral	LD50 >5000 mg/kg	Rat	ECHA Dossier	
	dermal	LD50 >2000 mg/kg	Rabbit	ECHA Dossier	
	inhalation (4 h) vapour	LC50 124,7 mg/l	Rat	ECHA Dossier	
67-63-0	2-propanol				
	oral	LD50 >5000 mg/kg	Rat	ECHA Dossier	
	dermal	LD50 >5000 mg/kg	Rabbit	ECHA Dossier	
78-93-3	butanone				
	oral	LD50 2054 mg/kg	Ratte	SDB Lieferant	
	dermal	LD50 >2000 mg/kg	Rabbit	ECHA Dossier	
3734-33-6	Denatoniumbenzoate				
	oral	ATE 500 mg/kg			
	dermal	LD50 >2000 mg/kg	Rat	suppliers SDS.	
	inhalation vapour	ATE 11 mg/l			
	inhalation dust/mist	ATE 1,5 mg/l			

**Irritation and corrosivity**

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

**Sensitising effects**

Based on available data, the classification criteria are not met.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.

**STOT-single exposure**

Based on available data, the classification criteria are not met.

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**11.2. Information on other hazards**
**Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

## Safety Data Sheet

according to UK REACH Regulation

### Ethanol 50 %, denatured (MEK/IPA/BTX)

Revision date: 27.03.2024

Product code: 11575.xxxxx

Page 11 of 17

#### Other information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

### SECTION 12: Ecological information

#### 12.1. Toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
64-17-5	ethanol					
	Acute fish toxicity	LC50 14200 mg/l	96 h	Pimephales promelas (fathead minnow)	ECHA Dossier	
	Acute algae toxicity	ErC50 275 mg/l	72 h	Chlorella vulgaris	ECHA Dossier	
	Acute crustacea toxicity	EC50 5012 mg/l	48 h	Ceriodaphnia dubia (water flea)	ECHA Dossier	
	Crustacea toxicity	NOEC 9,6 mg/l	9 d	Daphnia magna	ECHA Dossier	
67-63-0	2-propanol					
	Acute fish toxicity	LC50 9640 mg/l	96 h	Pimephales promelas	ECHA Dossier	OECD Guideline 203
	Acute algae toxicity	ErC50 1800 mg/l	96 h	Scenedesmus quadricauda	ECHA Dossier	
	Acute crustacea toxicity	EC50 >10000 mg/l	48 h	Daphnia magna (24h)	ECHA Dossier	OECD Guideline 202
78-93-3	butanone					
	Acute fish toxicity	LC50 2993 mg/l	96 h	Pimephales promelas	ECHA Dossier	OECD 203
	Acute algae toxicity	ErC50 1972 mg/l	72 h	Pseudokirchnerella subcapitata	ECHA Dossier	OECD 201
	Acute crustacea toxicity	EC50 308 mg/l	48 h	Daphnia magna	ECHA Dossier	OECD 202
3734-33-6	Denatoniumbenzoate					
	Acute fish toxicity	LC50 >1000 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)	suppliers SDS.	
	Acute crustacea toxicity	EC50 13 mg/l	48 h	Daphnia magna (Big water flea)	suppliers SDS.	

#### 12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
64-17-5	ethanol			
	other guideline	84%	20	ECHA Dossier
	Biodegradable.			
67-63-0	2-propanol			
	EU Method C.5/ EU Method C.6	53%	5	ECHA Dossier
	Easily biodegradable (concerning to the criteria of the OECD)			
78-93-3	butanone			
		98%	28	ECHA Dossier
	Readily biodegradable (according to OECD criteria).			

#### 12.3. Bioaccumulative potential

The product has not been tested.

## Safety Data Sheet

according to UK REACH Regulation

### Ethanol 50 %, denatured (MEK/IPA/BTX)

Revision date: 27.03.2024

Product code: 11575.xxxxx

Page 12 of 17

#### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
64-17-5	ethanol	-0,31
67-63-0	2-propanol	0,05
78-93-3	butanone	0,3

#### 12.4. Mobility in soil

The product has not been tested.

#### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

#### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

#### 12.7. Other adverse effects

No information available.

#### Further information

Avoid release to the environment.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

##### Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation. Hazardous waste according to the Waste List Ordinance (AVV). Consult the local waste disposal expert about waste disposal. According to (EWC) European Waste Catalogue, allocation of waste identity numbers/waste descriptions must be carried out in a specific way for every industry and process. Control report for waste code/waste marking according to (EWC) European Waste Catalogue:

##### List of Wastes Code - residues/unused products

070104 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the manufacture, formulation, supply and use (MFSU) of basic organic chemicals; other organic solvents, washing liquids and mother liquors; hazardous waste

##### List of Wastes Code - used product

070104 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the manufacture, formulation, supply and use (MFSU) of basic organic chemicals; other organic solvents, washing liquids and mother liquors; hazardous waste

##### List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

##### Contaminated packaging

Wash with plenty of water. Completely emptied packages can be recycled.

### SECTION 14: Transport information

#### Land transport (ADR/RID)

<b><u>14.1. UN number or ID number:</u></b>	UN 1170
<b><u>14.2. UN proper shipping name:</u></b>	ETHANOL SOLUTION
<b><u>14.3. Transport hazard class(es):</u></b>	3
<b><u>14.4. Packing group:</u></b>	II
Hazard label:	3

**Safety Data Sheet**

according to UK REACH Regulation

**Ethanol 50 %, denatured (MEK/IPA/BTX)**

Revision date: 27.03.2024

Product code: 11575.xxxxx

Page 13 of 17



Classification code: F1  
Special Provisions: 144 601  
Limited quantity: 1 L  
Excepted quantity: E2  
Transport category: 2  
Hazard No: 33  
Tunnel restriction code: D/E

**Inland waterways transport (ADN)**

**14.1. UN number or ID number:** UN 1170  
**14.2. UN proper shipping name:** ETHANOL SOLUTION  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
Hazard label: 3



Classification code: F1  
Special Provisions: 144 601  
Limited quantity: 1 L  
Excepted quantity: E2

**Marine transport (IMDG)**

**14.1. UN number or ID number:** UN 1170  
**14.2. UN proper shipping name:** ETHANOL SOLUTION  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
Hazard label: 3



Special Provisions: 144  
Limited quantity: 1 L  
Excepted quantity: E2  
EmS: F-E, S-D

**Air transport (ICAO-TI/IATA-DGR)**

**14.1. UN number or ID number:** UN 1170  
**14.2. UN proper shipping name:** ETHANOL SOLUTION  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
Hazard label: 3



Special Provisions: A3 A58 A180  
Limited quantity Passenger: 1 L  
Passenger LQ: Y341  
Excepted quantity: E2  
IATA-packing instructions - Passenger: 353  
IATA-max. quantity - Passenger: 5 L

**Safety Data Sheet**

according to UK REACH Regulation

**Ethanol 50 %, denatured (MEK/IPA/BTX)**

Revision date: 27.03.2024

Product code: 11575.xxxxx

Page 14 of 17

IATA-packing instructions - Cargo: 364  
IATA-max. quantity - Cargo: 60 L

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

**14.6. Special precautions for user**

Warning: Combustible liquid. Refer to section 6-8

**14.7. Maritime transport in bulk according to IMO instruments**

not applicable

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Information according to Directive 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

**Additional information**

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

**National regulatory information**

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

**15.2. Chemical safety assessment**

For the following substances of this mixture a chemical safety assessment has been carried out:

ethanol  
2-propanol  
butanone

**SECTION 16: Other information****Changes**

This data sheet contains changes from the previous version in section(s): 1,2,4,6,7,8,9,10,11,14,15,16.

Rev. 1.00 - 19.02.2020 Initial release

Rev. 2,1; 30.05.2023; general adjustment(s)

Rev. 2,2; 27.03.2024; Change of classification/labeling

**Safety Data Sheet**

according to UK REACH Regulation

**Ethanol 50 %, denatured (MEK/IPA/BTX)**

Revision date: 27.03.2024

Product code: 11575.xxxxx

Page 15 of 17

**Abbreviations and acronyms**

Flam. Liq: Flammable liquids  
Acute Tox: Acute toxicity  
Skin Irrit: Skin irritation  
Eye Dam: Eye damage  
Eye Irrit: Eye irritation  
STOT SE: Specific target organ toxicity - single exposure  
Aquatic Chronic: Chronic aquatic hazard  
ADR: Accord européen sur le transport des marchandises dangereuses par Route  
AwSV: Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen  
AGW: Arbeitsplatzgrenzwert  
AVV: Abfallverzeichnisverordnung  
CAS Chemical Abstracts Service  
CLP: Classification, Labelling and Packaging of substances and mixtures  
DNEL: Derived No Effect Level  
d: day(s)  
EAKV: Europäisches Abfallverzeichnis gemäß Entwurf Abfallverzeichnisverordnung  
EINECS: European Inventory of Existing Commercial Substances  
ELINCS: European List of Notified Chemical Substances  
ECHA: European Chemicals Agency  
EWC: European Waste Catalogue  
IARC: INTERNATIONAL AGENCY FOR RESEARCH ON CANCER  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)  
ICAO: International Civil Aviation Organization  
ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)  
GHS: Globally Harmonized System of Classification and Labelling of Chemicals  
GefStoffV: Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany)  
h: hour  
LOAEL: Lowest observed adverse effect level  
LOAEC: Lowest observed adverse effect concentration  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
NOAEL: No observed adverse effect level  
NOAEC: No observed adverse effect level  
NLP: No-Longer Polymers  
N/A: not applicable  
OECD: Organisation for Economic Co-operation and Development  
PNEC: predicted no effect concentration  
PBT: Persistent bioaccumulative toxic  
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail )  
REACH: Registration, Evaluation, Authorisation of Chemicals  
SVHC: substance of very high concern  
TRGS Technische Regeln fuer Gefahrstoffe  
UN: United Nations  
VOC: Volatile Organic Compounds  
VwVwS: Verwaltungsvorschrift wassergefährdender Stoffe  
WGK: Wassergefährdungsklasse  
CLP: Classification, labelling and Packaging  
REACH: Registration, Evaluation and Authorization of Chemicals  
GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals  
UN: United Nations  
CAS: Chemical Abstracts Service  
DNEL: Derived No Effect Level

**Safety Data Sheet**

according to UK REACH Regulation

**Ethanol 50 %, denatured (MEK/IPA/BTX)**

Revision date: 27.03.2024

Product code: 11575.xxxxx

Page 16 of 17

DMEL: Derived Minimal Effect Level  
 PNEC: Predicted No Effect Concentration  
 ATE: Acute toxicity estimate  
 LL50: Lethal loading, 50%  
 EL50: Effect loading, 50%  
 EC50: Effective Concentration 50%  
 ErC50: Effective Concentration 50%, growth rate  
 NOEC: No Observed Effect Concentration  
 BCF: Bio-concentration factor  
 PBT: persistent, bioaccumulative, toxic  
 vPvB: very persistent, very bioaccumulative  
 ADR: Accord européen sur le transport des marchandises dangereuses par Route  
 (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 RID: Regulations concerning the international carriage of dangerous goods by rail  
 ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways  
 (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation  
 intérieures)  
 EmS: Emergency Schedules  
 MFAG: Medical First Aid Guide  
 MARPOL: International Convention for the Prevention of Marine Pollution from Ships  
 IBC: Intermediate Bulk Container  
 For abbreviations and acronyms, see table at <http://abbrev.esdscom.eu>  
 For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety  
 assessment, chapter R.20 (Table of terms and abbreviations).  
 EC/EEC: European Community/European Economic Community  
 EU: European Union  
 M-factor: Multiplying factor  
 IATA: International Air Transport Association  
 DGR: Dangerous Goods Regulations  
 ICAO: International Civil Aviation Organization  
 TI: Technical Instructions  
 VOC: volatile organic compound

**Classification for mixtures and used evaluation method according to GB CLP Regulation**

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Eye Irrit. 2; H319	Calculation method

**Relevant H and EUH statements (number and full text)**

H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

**Further Information**

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations. Classification according to Regulation (EC) No 1272/2008 [CLP] - Classification procedure:

Health hazards: Calculation method.

Environmental hazards: Calculation method.

Physical hazards: On basis of test data and / or calculated and / or estimated.



**Safety Data Sheet**

according to UK REACH Regulation

**Ethanol 50 %, denatured (MEK/IPA/BTX)**

Revision date: 27.03.2024

Product code: 11575.xxxxx

Page 17 of 17

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*