

Safety Data Sheet

according to UK REACH Regulation

Indicating Solution pH 4.2 - 6.3 (Methyl Red)

Revision date: 05.01.2024

Product code: 13660.xxxxx

Page 1 of 17

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Indicating Solution pH 4.2 - 6.3 (Methyl Red)

UFI: 7ST6-0180-V00E-SMAC

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Use as laboratory reagent. Intended for scientific research and development.

Uses advised against

Any non-intended use.

1.3. Details of the supplier of the safety data sheet

Company name: MORPHISTO GmbH
Street: Schumannstr. 142/144
Place: D-63069 Offenbach
Telephone: +49 (0) 69 / 400 3019-60 Telefax: +49 (0) 69 / 400 3019-64
E-mail: info@morphisto.de
Contact person: Morphisto GmbH
E-mail: gefahrstoffmanagement@morphisto.de
Internet: http://www.morphisto.de

1.4. Emergency telephone number:

Poison Information Center Mainz, Germany, Tel: +49(0)6131/19240

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****GB CLP Regulation**Flam. Liq. 2; H225
Eye Irrit. 2; H319

Full text of hazard statements: see SECTION 16.

2.2. Label elements**GB CLP Regulation****Signal word:** Danger**Pictograms:****Hazard statements**H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.**Precautionary statements**P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313 If eye irritation persists: Get medical advice/attention.
P403+P235 Store in a well-ventilated place. Keep cool.

Safety Data Sheet

according to UK REACH Regulation

Indicating Solution pH 4.2 - 6.3 (Methyl Red)

Revision date: 05.01.2024

Product code: 13660.xxxxx

Page 2 of 17

Labelling of packages where the contents do not exceed 125 ml
Signal word: Danger

Pictograms:

2.3. Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulating and toxic (PBT) or very persistent and very bioaccumulating (vPvB) at levels of 0.1% or higher. Ecological information: The substance/mixture does not contain any components that are considered to be hazardous according to REACH Article 57(f) or Commission Delegated Regulation (EU) 2017/2100 or Commission Delegated Regulation (EU) 2018/605 in amounts of 0.1 % or more have endocrine disrupting properties. Toxicological information: The substance/mixture does not contain any components that are to be classified according to REACH Article 57(f) or Commission Delegated Regulation (EU) 2017/2100 or Commission Delegated Regulation (EU) 2018/605 in quantities of 0.1 % or more have endocrine disrupting properties.

SECTION 3: Composition/information on ingredients
3.2. Mixtures
Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
64-17-5	ethanol			95 - < 100 %
	200-578-6	603-002-00-5	01-2119457610-43	
	Flam. Liq. 2, Eye Irrit. 2; H225 H319			
67-63-0	2-propanol			< 1 %
	200-661-7	603-117-00-0	01-2119457558-25	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336			
78-93-3	butanone			< 1 %
	201-159-0	606-002-00-3	01-2119457290-43	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
3734-33-6	Denatoniumbenzoate			< 1 %
	223-095-2			
	Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Dam. 1, Aquatic Chronic 3; H332 H302 H315 H318 H412			

Full text of H and EUH statements: see section 16.

Safety Data Sheet

according to UK REACH Regulation

Indicating Solution pH 4.2 - 6.3 (Methyl Red)

Revision date: 05.01.2024

Product code: 13660.xxxxx

Page 3 of 17

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
64-17-5	200-578-6	ethanol	95 - < 100 %
		inhalation: LC50 = 124,7 mg/l (vapours); dermal: LD50 = >2000 mg/kg; oral: LD50 = >5000 mg/kg Eye Irrit. 2; H319: >= 50 - 100	
67-63-0	200-661-7	2-propanol	< 1 %
		dermal: LD50 = >5000 mg/kg; oral: LD50 = >5000 mg/kg	
78-93-3	201-159-0	butanone	< 1 %
		dermal: LD50 = >2000 mg/kg; oral: LD50 = 2054 mg/kg	
3734-33-6	223-095-2	Denatoniumbenzoate	< 1 %
		inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = >2000 mg/kg; oral: ATE = 500 mg/kg	

Further Information

This product contains no substances of very high concern (SVHC) (>0,1%) which are included in the Candidate List according to Article 59 of REACH.

SECTION 4: First aid measures
4.1. Description of first aid measures
General information

Remove affected person from the danger area and lay down. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After inhalation

Provide fresh air. If unconscious but breathing normally, place in recovery position and seek medical advice. In case of allergic symptoms, especially in the breathing area, seek medical advice immediately.

After contact with skin

Take off contaminated clothing and wash it before reuse. Wash with plenty of water. In case of skin irritation, seek medical treatment.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately. If eye irritation persists: Get medical advice/attention.

After ingestion

Observe risk of aspiration if vomiting occurs. Rinse mouth thoroughly with water. Let water be drunken in little sips (dilution effect). Seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

Acute effects: Mucous membrane irritation after eye contact or inhalation.

Delayed effects: Impairment of inhibitory functions of the central nervous system, skin redness, nausea after ingestion of large amounts.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures
5.1. Extinguishing media
Suitable extinguishing media

Water spray jet, Carbon dioxide (CO2), Foam, Extinguishing powder.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Highly flammable. Vapours can form explosive mixtures with air. The formation of combustible vapours is

Safety Data Sheet

according to UK REACH Regulation

Indicating Solution pH 4.2 - 6.3 (Methyl Red)

Revision date: 05.01.2024

Product code: 13660.xxxxx

Page 4 of 17

possible at temperatures above: 7°C. Vapours are heavier than air and will spread at floor level. In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO₂).

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. In case of fire and/or explosion do not breathe fumes.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Remove all sources of ignition. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment. (refer to chapter 8) Take action to prevent static discharges. Ventilate affected area. Special danger of slipping by leaking/spilling product.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Explosion risk. Do not allow to enter into surface water or drains. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Prevent spread over a wide area (e.g. by containment or oil barriers). In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up**For cleaning up**

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

Other information

Ventilate affected area.
Clear contaminated areas thoroughly.

6.4. Reference to other sections

Safe handling: see section 7
Personal protection equipment: see section 8
Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes.
Wear personal protection equipment. (See section 8.) Use extractor hood (laboratory).

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air. Flammable vapours can accumulate in head space of closed systems. Heating causes rise in pressure with risk of bursting.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat, drink, smoke, sniff. Take off contaminated clothing and wash it before reuse. Always close containers tightly after the removal of product.

Further information on handling

General protection and hygiene measures: refer to chapter 8

7.2. Conditions for safe storage, including any incompatibilities

Safety Data Sheet

according to UK REACH Regulation

Indicating Solution pH 4.2 - 6.3 (Methyl Red)

Revision date: 05.01.2024

Product code: 13660.xxxxx

Page 5 of 17

Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep/Store only in original container. Protect from direct sunlight.

Ensure adequate ventilation of the storage area. Concentrated vapours are heavier than air.

Suitable material for Container: Stainless steel. (1.4301 (V2), 1.4401 (V4)); iron. solvent resistant plastics.

Unsuitable materials for Container: Aluminium. Rubber. various plastics.

Hints on joint storage

Do not store together with: Oxidizing agent. Pyrophoric or self-heating substances. Do not store together with:

Gas. Explosives. Flammable solids. Pyrophoric liquids and solids. Self-heating substances and mixtures.

Substances or mixtures which, in contact with water, emit flammable gases. Oxidizing liquids.ammonium

nitrate. Self-reactive substances and mixtures. Organic peroxides. Non-combustible toxic substances.

Radioactive substances. Infectious substances.

Further information on storage conditions

Recommended storage temperature: 15-25 °C

Protect against: UV-radiation/sunlight. heat. Cold.

7.3. Specific end use(s)

See section 1.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
78-93-3	Butan-2-one (methyl ethyl ketone)	200	600		TWA (8 h)	WEL
		300	899		STEL (15 min)	WEL
64-17-5	Ethanol	1000	1920		TWA (8 h)	WEL
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL

Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
78-93-3	Butan-2-one	butan-2-one	70 µmol/L	urine	Post shift

Safety Data Sheet

according to UK REACH Regulation

Indicating Solution pH 4.2 - 6.3 (Methyl Red)

Revision date: 05.01.2024

Product code: 13660.xxxxx

Page 6 of 17

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
64-17-5	ethanol			
Worker DNEL, acute		inhalation	local	1900 mg/m ³
Worker DNEL, long-term		dermal	systemic	343 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	950 mg/m ³
Consumer DNEL, acute		inhalation	local	950 mg/m ³
Consumer DNEL, long-term		dermal	systemic	206 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	114 mg/m ³
Consumer DNEL, long-term		oral	systemic	87 mg/kg bw/day
67-63-0	2-propanol			
Worker DNEL, long-term		inhalation	systemic	500 mg/m ³
Consumer DNEL, long-term		inhalation	systemic	89 mg/m ³
Worker DNEL, long-term		dermal	systemic	888 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	26 mg/kg bw/day
Consumer DNEL, long-term		dermal	systemic	319 mg/kg bw/day
78-93-3	butanone			
Worker DNEL, long-term		inhalation	systemic	600 mg/m ³
Worker DNEL, long-term		dermal	systemic	1161 mg/kg bw/day

Safety Data Sheet

according to UK REACH Regulation

Indicating Solution pH 4.2 - 6.3 (Methyl Red)

Revision date: 05.01.2024

Product code: 13660.xxxxx

Page 7 of 17

PNEC values

CAS No	Substance		Value
Environmental compartment			
64-17-5	ethanol		
Freshwater			0,96 mg/l
Freshwater (intermittent releases)			2,75 mg/l
Marine water			0,79 mg/l
Marine water (intermittent releases)			2,75 mg/l
Freshwater sediment			3,6 mg/kg
Marine sediment			2,9 mg/kg
Secondary poisoning			0,72 mg/kg
Micro-organisms in sewage treatment plants (STP)			580 mg/l
Soil			0,63 mg/kg
67-63-0	2-propanol		
Freshwater			140,9 mg/l
Marine water			140,9 mg/l
Freshwater sediment			552 mg/kg
Marine sediment			552 mg/kg
Secondary poisoning			160 mg/kg
Soil			28 mg/kg
78-93-3	butanone		
Freshwater			55,8 mg/l
Freshwater (intermittent releases)			55,8 mg/l
Marine water			55,8 mg/l
Freshwater sediment			284,7 mg/kg
Marine sediment			284,7 mg/kg
Micro-organisms in sewage treatment plants (STP)			709 mg/l
Soil			22,5 mg/kg

8.2. Exposure controls

Appropriate engineering controls

Provide adequate ventilation.

If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

Use extractor hood (laboratory).

Individual protection measures, such as personal protective equipment
Eye/face protection

Suitable eye protection: goggles. Tightly sealed safety glasses. EN 166

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is

Safety Data Sheet

according to UK REACH Regulation

Indicating Solution pH 4.2 - 6.3 (Methyl Red)

Revision date: 05.01.2024

Product code: 13660.xxxxx

Page 8 of 17

recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. In case of prolonged or frequently repeated skin contact:

Tested protective gloves are to be worn:

Suitable material:

Butyl rubber. (0,7 mm, Breakthrough time \geq 480 min, penetration time (maximum wearing period): 160 min):

NBR (Nitrile rubber). (0,4 mm, Breakthrough time \geq 120 min, penetration time (maximum wearing period): 40 min)

The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it.

Before using check leak tightness / impermeability. In the case of wanting to use the gloves again, clean them before taking off and air them well.

Skin protection

Protective clothing. (fire retardant.)

Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500 (D).

Respiratory protection

In case of inadequate ventilation wear respiratory protection. With correct and proper use, and under normal conditions, breathing protection is not required.

Respiratory protection necessary at:

Insufficient ventilation.

exceeding exposure limit values

generation/formation of aerosols

Suitable respiratory protective equipment:

gas filtering equipment (EN 141). Type : a

The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.

The wearing time limitations according to GefStoffV in conjunction with the rules for the use of respiratory protective devices (BGR 190) must be observed.

Thermal hazards

Flame-retardant protective clothing. Wear anti-static footwear and clothing

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties
9.1. Information on basic physical and chemical properties

Physical state:	liquid	
Colour:	orange	
Odour:	alcoholic	
Melting point/freezing point:		not determined
Boiling point or initial boiling point and boiling range:		~78 °C
Flammability:		not determined
Lower explosion limits:		2,5 vol. %
Upper explosion limits:		15 vol. %
Flash point:		12 °C
Auto-ignition temperature:		400 °C
Decomposition temperature:		not determined
pH-Value:		not determined
Viscosity / kinematic:		not determined
Water solubility: (at 20 °C)		completely miscible

Safety Data Sheet

according to UK REACH Regulation

Indicating Solution pH 4.2 - 6.3 (Methyl Red)

Revision date: 05.01.2024

Product code: 13660.xxxxx

Page 9 of 17

Solubility in other solvents

not determined

Partition coefficient n-octanol/water:

not determined

Vapour pressure:

58 hPa

(at 20 °C)

Vapour pressure:

293 hPa

(at 50 °C)

Density (at 20 °C):

0,79 g/cm³

Relative vapour density:

not determined

Particle characteristics:

not applicable

9.2. Other information**Information with regard to physical hazard classes**

Explosive properties

The product is not: Explosive. Vapours of flammable solvents can accumulate in the gas phase of closed container, especially during heat treatment. Therefore keep away from fire and sources of ignition.

Self-ignition temperature

Gas:

not determined

Oxidizing properties

none

Other safety characteristics

Evaporation rate:

not determined

Solvent separation test:

not determined

Solvent content:

not determined

Solid content:

not determined

Sublimation point:

not determined

Softening point:

not determined

Pour point:

not determined

Viscosity / dynamic:

not determined

Flow time:

not determined

SECTION 10: Stability and reactivity**10.1. Reactivity**

Highly flammable. No information available.

10.2. Chemical stability

Stable under normal storage and handling conditions.

10.3. Possibility of hazardous reactions

Explosion risk in contact with: Oxidizing agents, strong. nitric acid. Hydrogenium peroxide.

Exothermic reactions with: Alkali metals. Alkaline earth metals. Reducing agents, strong.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. Keep away from heat. Protect from direct sunlight. Protect from moisture.

In use may form flammable/explosive vapour-air mixture.

Heating causes rise in pressure with risk of bursting. Recommended storage temperature: < 40 °C

10.5. Incompatible materials

Materials to avoid: Substances that form flammable gases when in contact with water. Inflammatory substances. Alkali metals. Acid chlorides. Organic peroxides. Oxidizing agents.

10.6. Hazardous decomposition productsIn case of fire may be liberated: Carbon monoxide Carbon dioxide (CO₂).**SECTION 11: Toxicological information**

Safety Data Sheet

according to UK REACH Regulation

Indicating Solution pH 4.2 - 6.3 (Methyl Red)

Revision date: 05.01.2024

Product code: 13660.xxxxx

Page 10 of 17

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64-17-5	ethanol				
	oral	LD50 >5000 mg/kg	Rat	ECHA Dossier	
	dermal	LD50 >2000 mg/kg	Rabbit	ECHA Dossier	
	inhalation (4 h) vapour	LC50 124,7 mg/l	Rat	ECHA Dossier	
67-63-0	2-propanol				
	oral	LD50 >5000 mg/kg	Rat	ECHA Dossier	
	dermal	LD50 >5000 mg/kg	Rabbit	ECHA Dossier	
78-93-3	butanone				
	oral	LD50 2054 mg/kg	Ratte	SDB Lieferant	
	dermal	LD50 >2000 mg/kg	Rabbit	ECHA Dossier	
3734-33-6	Denatoniumbenzoate				
	oral	ATE 500 mg/kg			
	dermal	LD50 >2000 mg/kg	Rat	suppliers SDS.	
	inhalation vapour	ATE 11 mg/l			
	inhalation dust/mist	ATE 1,5 mg/l			

Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

Safety Data Sheet

according to UK REACH Regulation

Indicating Solution pH 4.2 - 6.3 (Methyl Red)

Revision date: 05.01.2024

Product code: 13660.xxxxx

Page 11 of 17

Other information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP]. Depending on the ingested quantity the following symptoms can be induced: a reduction of inhibitions, euphoria but also dysphoria, aggressiveness, impaired motoric skills, impaired responsiveness, blurred vision and fatigue.

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
64-17-5	ethanol					
	Acute fish toxicity	LC50 mg/l	14200	96 h	Pimephales promelas (fathead minnow)	ECHA Dossier
	Acute algae toxicity	ErC50 mg/l	275 mg/l	72 h	Chlorella vulgaris	ECHA Dossier
	Acute crustacea toxicity	EC50 mg/l	5012	48 h	Ceriodaphnia dubia (water flea)	ECHA Dossier
	Crustacea toxicity	NOEC	9,6 mg/l	9 d	Daphnia magna	ECHA Dossier
67-63-0	2-propanol					
	Acute fish toxicity	LC50 mg/l	9640	96 h	Pimephales promelas	ECHA Dossier OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	1800	96 h	Scenedesmus quadricauda	ECHA Dossier
	Acute crustacea toxicity	EC50 mg/l	>10000	48 h	Daphnia magna (24h)	ECHA Dossier OECD Guideline 202
78-93-3	butanone					
	Acute fish toxicity	LC50 mg/l	2993	96 h	Pimephales promelas	ECHA Dossier OECD 203
	Acute algae toxicity	ErC50 mg/l	1972	72 h	Pseudokirchnerella subcapitata	ECHA Dossier OECD 201
	Acute crustacea toxicity	EC50	308 mg/l	48 h	Daphnia magna	ECHA Dossier OECD 202
3734-33-6	Denatoniumbenzoate					
	Acute fish toxicity	LC50 mg/l	>1000	96 h	Oncorhynchus mykiss (Rainbow trout)	suppliers SDS.
	Acute crustacea toxicity	EC50	13 mg/l	48 h	Daphnia magna (Big water flea)	suppliers SDS.

12.2. Persistence and degradability

No information available.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
64-17-5	ethanol			
	other guideline	84%	20	ECHA Dossier
	Biodegradable.			
67-63-0	2-propanol			
	EU Method C.5/ EU Method C.6	53%	5	ECHA Dossier
	Easily biodegradable (concerning to the criteria of the OECD)			
78-93-3	butanone			
		98%	28	ECHA Dossier
	Readily biodegradable (according to OECD criteria).			

Safety Data Sheet

according to UK REACH Regulation

Indicating Solution pH 4.2 - 6.3 (Methyl Red)

Revision date: 05.01.2024

Product code: 13660.xxxxx

Page 12 of 17

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
64-17-5	ethanol	-0,31
67-63-0	2-propanol	0,05
78-93-3	butanone	0,3

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Avoid release to the environment.

SECTION 13: Disposal considerations
13.1. Waste treatment methods
Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation. Consult the local waste disposal expert about waste disposal. Non-contaminated packages may be recycled. According to (EWC) European Waste Catalogue, allocation of waste identity numbers/waste descriptions must be carried out in a specific way for every industry and process.

Control report for waste code/ waste marking according to (EWC) European Waste Catalogue:

List of Wastes Code - residues/unused products

160506 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; laboratory chemicals, consisting of or containing hazardous substances, including mixtures of laboratory chemicals; hazardous waste

List of Wastes Code - used product

160506 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; laboratory chemicals, consisting of or containing hazardous substances, including mixtures of laboratory chemicals; hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Wash with plenty of water. Completely emptied packages can be recycled.

SECTION 14: Transport information
Land transport (ADR/RID)

- 14.1. UN number or ID number:** UN 1170
14.2. UN proper shipping name: ETHANOL
14.3. Transport hazard class(es): 3
14.4. Packing group: II

Safety Data Sheet

according to UK REACH Regulation

Indicating Solution pH 4.2 - 6.3 (Methyl Red)

Revision date: 05.01.2024

Product code: 13660.xxxxx

Page 13 of 17

Hazard label: 3


 Classification code: F1
 Special Provisions: 144 601
 Limited quantity: 1 L
 Excepted quantity: E2
 Transport category: 2
 Hazard No: 33
 Tunnel restriction code: D/E

Inland waterways transport (ADN)
14.1. UN number or ID number: UN 1170
14.2. UN proper shipping name: ETHANOL
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3

 Classification code: F1
 Special Provisions: 144 601
 Limited quantity: 1 L
 Excepted quantity: E2

Marine transport (IMDG)
14.1. UN number or ID number: UN 1170
14.2. UN proper shipping name: ETHANOL
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3

 Special Provisions: 144
 Limited quantity: 1 L
 Excepted quantity: E2
 EmS: F-E, S-D

Air transport (ICAO-TI/IATA-DGR)
14.1. UN number or ID number: UN 1170
14.2. UN proper shipping name: ETHANOL
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3

 Special Provisions: A3 A58 A180
 Limited quantity Passenger: 1 L
 Passenger LQ: Y341
 Excepted quantity: E2
 IATA-packing instructions - Passenger: 353

Safety Data Sheet

according to UK REACH Regulation

Indicating Solution pH 4.2 - 6.3 (Methyl Red)

Revision date: 05.01.2024

Product code: 13660.xxxxx

Page 14 of 17

IATA-max. quantity - Passenger:	5 L
IATA-packing instructions - Cargo:	364
IATA-max. quantity - Cargo:	60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: Combustible liquid. Refer to section 6-8

14.7. Maritime transport in bulk according to IMO instruments

not relevant

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Directive 2010/75/EU on industrial emissions: not determined

Directive 2004/42/EC on VOC in paints and varnishes: not determined

Information according to Directive 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

Additional information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

ethanol
2-propanol
butanone**SECTION 16: Other information****Changes**

This data sheet contains changes from the previous version in section(s): 1,2,3,4,5,6,7,8,9,10,12,13,14,15,16.

Rev. 2,0; 21.08.22, Individual safety data sheet based on 10369_collect

Rev. 2,1: 12.12.23, general adjustment(s)

Safety Data Sheet

according to UK REACH Regulation

Indicating Solution pH 4.2 - 6.3 (Methyl Red)

Revision date: 05.01.2024

Product code: 13660.xxxxx

Page 15 of 17

Abbreviations and acronyms

Flam. Liq: Flammable liquids
Acute Tox: Acute toxicity
Skin Irrit: Skin irritation
Eye Dam: Eye damage
Eye Irrit: Eye irritation
STOT SE: Specific target organ toxicity - single exposure
Aquatic Chronic: Chronic aquatic hazard
ADR: Accord européen sur le transport des marchandises dangereuses par Route
AwSV: Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen
AGW: Arbeitsplatzgrenzwert
AVV: Abfallverzeichnisverordnung
CAS Chemical Abstracts Service
CLP: Classification, Labelling and Packaging of substances and mixtures
DNEL: Derived No Effect Level
d: day(s)
EAKV: Europäisches Abfallverzeichnis gemäß Entwurf Abfallverzeichnisverordnung
EINECS: European Inventory of Existing Commercial Substances
ELINCS: European List of Notified Chemical Substances
ECHA: European Chemicals Agency
EWC: European Waste Catalogue
IARC: INTERNATIONAL AGENCY FOR RESEARCH ON CANCER
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
ICAO: International Civil Aviation Organization
ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
GefStoffV: Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany)
h: hour
LOAEL: Lowest observed adverse effect level
LOAEC: Lowest observed adverse effect concentration
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
NOAEL: No observed adverse effect level
NOAEC: No observed adverse effect level
NLP: No-Longer Polymers
N/A: not applicable
OECD: Organisation for Economic Co-operation and Development
PNEC: predicted no effect concentration
PBT: Persistent bioaccumulative toxic
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
REACH: Registration, Evaluation, Authorisation of Chemicals
SVHC: substance of very high concern
TRGS Technische Regeln fuer Gefahrstoffe
UN: United Nations
VOC: Volatile Organic Compounds
VwVwS: Verwaltungsvorschrift wassergefährdender Stoffe
WGK: Wassergefährdungsklasse
CLP: Classification, labelling and Packaging
REACH: Registration, Evaluation and Authorization of Chemicals
GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals
UN: United Nations
CAS: Chemical Abstracts Service
DNEL: Derived No Effect Level

Safety Data Sheet

according to UK REACH Regulation

Indicating Solution pH 4.2 - 6.3 (Methyl Red)

Revision date: 05.01.2024

Product code: 13660.xxxxx

Page 16 of 17

DMEL: Derived Minimal Effect Level
 PNEC: Predicted No Effect Concentration
 ATE: Acute toxicity estimate
 LL50: Lethal loading, 50%
 EL50: Effect loading, 50%
 EC50: Effective Concentration 50%
 ErC50: Effective Concentration 50%, growth rate
 NOEC: No Observed Effect Concentration
 BCF: Bio-concentration factor
 PBT: persistent, bioaccumulative, toxic
 vPvB: very persistent, very bioaccumulative
 ADR: Accord européen sur le transport des marchandises dangereuses par Route
 (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 RID: Regulations concerning the international carriage of dangerous goods by rail
 ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
 (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation
 intérieures)
 EmS: Emergency Schedules
 MFAG: Medical First Aid Guide
 MARPOL: International Convention for the Prevention of Marine Pollution from Ships
 IBC: Intermediate Bulk Container
 For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety
 assessment, chapter R.20 (Table of terms and abbreviations).
 EC/EEC: European Community/European Economic Community
 EU: European Union
 M-factor: Multiplying factor
 IATA: International Air Transport Association
 DGR: Dangerous Goods Regulations
 ICAO: International Civil Aviation Organization
 TI: Technical Instructions
 VOC: volatile organic compound

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Eye Irrit. 2; H319	Calculation method

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations. Classification according to Regulation (EC) No 1272/2008 [CLP]

- Classification procedure:

Health hazards: Calculation method.

Environmental hazards: Calculation method.

Physical hazards: On basis of test data and / or calculated and / or estimated.

Safety Data Sheet

according to UK REACH Regulation

Indicating Solution pH 4.2 - 6.3 (Methyl Red)

Revision date: 05.01.2024

Product code: 13660.xxxxx

Page 17 of 17

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)