

Safety Data Sheet

according to UK REACH Regulation

Picric acid mixture to detect austenite

Revision date: 19.09.2023

Product code: 11554.xxxxx

Page 1 of 16

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Picric acid mixture to detect austenite

UFI: 8YY0-21MY-U006-PP3G

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Use as laboratory reagent.

Uses advised against

Any non-intended use.

1.3. Details of the supplier of the safety data sheet

Company name: MORPHISTO GmbH
Street: Schumannstr. 142/144
Place: D-63069 Offenbach
Telephone: +49 (0) 69 / 400 3019-60 Telefax: +49 (0) 69 / 400 3019-64
E-mail: info@morphisto.de
Contact person: Morphisto GmbH
E-mail: gefahrstoffmanagement@morphisto.de
Internet: http://www.morphisto.de

1.4. Emergency telephone number:

Poison Information Center Mainz, Germany, Tel: +49(0)6131/19240

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Met. Corr. 1; H290
Flam. Liq. 2; H225
Skin Corr. 1; H314
Eye Dam. 1; H318

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

nitric acid %
hydrochloric acid %

Signal word: Danger

Pictograms:



Hazard statements

H225 Highly flammable liquid and vapour.
H290 May be corrosive to metals.
H314 Causes severe skin burns and eye damage.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Safety Data Sheet

according to UK REACH Regulation

Picric acid mixture to detect austenite

Revision date: 19.09.2023

Product code: 11554.xxxxx

Page 2 of 16

P260	Do not breathe mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.

Special labelling of certain mixtures

EUH071 Corrosive to the respiratory tract.

Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

Pictograms:



Hazard statements

H314

Precautionary statements

P260-P280-P303+P361+P353-P305+P351+P338-P310

2.3. Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulating and toxic (PBT) or very persistent and very bioaccumulating (vPvB) at levels of 0.1% or higher. Ecological information: The substance/mixture does not contain any components that are considered to be hazardous according to REACH Article 57(f) or Commission Delegated Regulation (EU) 2017/2100 or Commission Delegated Regulation (EU) 2018/605 in amounts of 0.1 % or more have endocrine disrupting properties. Toxicological information: The substance/mixture does not contain any components that are to be classified according to REACH Article 57(f) or Commission Delegated Regulation (EU) 2017/2100 or Commission Delegated Regulation (EU) 2018/605 in quantities of 0.1 % or more have endocrine disrupting properties.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Safety Data Sheet

according to UK REACH Regulation

Picric acid mixture to detect austenite

Revision date: 19.09.2023

Product code: 11554.xxxxx

Page 3 of 16

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
64-17-5	Ethanol			65 - < 70 %
	200-578-6	603-002-00-5	01-2119457610-43	
	Flam. Liq. 2, Eye Irrit. 2; H225 H319			
7697-37-2	nitric acid ... %			10 - < 15 %
	231-714-2	007-030-00-3	01-2119487297-23	
	Ox. Liq. 3, Met. Corr. 1, Acute Tox. 3, Skin Corr. 1A, Eye Dam. 1; H272 H290 H331 H314 H318 EUH071			
7647-01-0	hydrochloric acid %			1 - < 5 %
	231-595-7	017-002-01-X	01-2119484862-27	
	Met. Corr. 1, Skin Corr. 1B, Eye Dam. 1, STOT SE 3; H290 H314 H318 H335			
88-89-1	picric acid			1 - < 5 %
	201-865-9	609-009-00-X		
	Expl. 1.1, Acute Tox. 3, Acute Tox. 3, Acute Tox. 3; H201 H331 H311 H301			
78-93-3	butanone			< 1 %
	201-159-0	606-002-00-3	01-2119457290-43	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
64-17-5	200-578-6	Ethanol	65 - < 70 %
	inhalation: LC50 = 124,7 mg/l (vapours); dermal: LD50 = >2000 mg/kg; oral: LD50 = >5000 mg/kg Eye Irrit. 2; H319: >= 50 - 100		
7697-37-2	231-714-2	nitric acid ... %	10 - < 15 %
	inhalation: ATE 2,65 mg/l (vapours) Ox. Liq. 3; H272: >= 65 - 100 Skin Corr. 1A; H314: >= 20 - 100 Skin Corr. 1B; H314: >= 5 - < 20		
7647-01-0	231-595-7	hydrochloric acid %	1 - < 5 %
	oral: LD50 = 2222 mg/kg Skin Corr. 1B; H314: >= 25 - 100 Skin Irrit. 2; H315: >= 10 - < 25 Eye Irrit. 2; H319: >= 10 - < 25 STOT SE 3; H335: >= 10 - 100		
88-89-1	201-865-9	picric acid	1 - < 5 %
	inhalation: ATE = 3 mg/l (vapours); inhalation: LC50 = 0,51 mg/l (dusts or mists); dermal: LD50 = 300,1 mg/kg; oral: LD50 = 200 mg/kg		
78-93-3	201-159-0	butanone	< 1 %
	dermal: LD50 = >2000 mg/kg; oral: LD50 = 2054 mg/kg		

Further Information

This product contains no substances of very high concern (SVHC) (>0,1%) which are included in the Candidate List according to Article 59 of REACH.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove affected person from the danger area and lay down. First aider: Pay attention to self-protection!
In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Safety Data Sheet

according to UK REACH Regulation

Picric acid mixture to detect austenite

Revision date: 19.09.2023

Product code: 11554.xxxxx

Page 4 of 16

After inhalation

Medical treatment necessary. Provide fresh air. Call a physician immediately. Put victim at rest, cover with a blanket and keep warm. In case of breathing difficulties administer oxygen. In case of irregular breathing or respiratory arrest provide artificial respiration.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

After ingestion

Observe risk of aspiration if vomiting occurs. Do NOT induce vomiting. Adverse human health effects and symptoms: Gastric perforation. Do not allow a neutralisation agent to be drunk. Do NOT induce vomiting. Rinse mouth thoroughly with water. Let water be drunk in little sips (dilution effect). Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

By swallowing danger of perforation of the esophagus and the stomach exists (strong corrosive effects).

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Aspiration hazard: Gastric lavage under endotracheal intubation

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Water spray jet, Carbon dioxide (CO₂), Foam, Extinguishing powder

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Highly flammable. Vapours can form explosive mixtures with air. In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO₂). Nitrogen oxides (NO_x). Hydrogen chloride (HCl).

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit. In case of fire and/or explosion do not breathe fumes.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment. Remove persons to safety.

Avoid exposure. Do not allow to dry. Risk of explosion in case of drying up.

Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Explosion risk. Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Safety Data Sheet

according to UK REACH Regulation

Picric acid mixture to detect austenite

Revision date: 19.09.2023

Product code: 11554.xxxxx

Page 5 of 16

6.3. Methods and material for containment and cleaning up**For cleaning up**

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Ventilate affected area.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Wear suitable protective clothing. (See section 8.)

Provide adequate ventilation as well as local exhaustion at critical locations.

Use extractor hood (laboratory).

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat, drink, smoke, sniff. Always close containers tightly after the removal of product. Wash contaminated clothing prior to re-use. Used working clothes should not be worn outside the work area. Street clothing should be stored separately from work clothing.

Further information on handling

Flammable vapours can accumulate in head space of closed systems.

Avoid contact with skin, eyes and clothes.

Conditions to avoid: Generation/formation of aerosols

Always remove adhering product residues from lids and closures before closing the product.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaust at critical locations. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Unsuitable container/equipment material: Metal. Make sure spills can be contained (e.g. sump pallets or kerbed areas).

Recommended storage temperature: 15-25 °C

Storage: Just as long as necessary.

Hints on joint storage

Do not store together with: Oxidizing agent. Pyrophoric or self-heating substances. Do not store together with: Gas. Explosives. Flammable solids. Pyrophoric liquids and solids. Self-heating substances and mixtures.

Substances or mixtures which, in contact with water, emit flammable gases. Oxidizing liquids. Oxidizing solids. ammonium nitrate. Self-reactive substances and mixtures. Organic peroxides. Non-combustible toxic substances. Radioactive substances. Infectious substances.

Further information on storage conditions

Keep away from heat. Protect from sunlight. Store small packages in a suitable, robust cabinet.

Safety Data Sheet

according to UK REACH Regulation

Picric acid mixture to detect austenite

Revision date: 19.09.2023

Product code: 11554.xxxxx

Page 6 of 16

7.3. Specific end use(s)

See section 1.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
78-93-3	Butan-2-one (methyl ethyl ketone)	200	600		TWA (8 h)	WEL
		300	899		STEL (15 min)	WEL
64-17-5	Ethanol	1000	1920		TWA (8 h)	WEL
7647-01-0	Hydrogen chloride (gas and aerosol mists)	1	2		TWA (8 h)	WEL
		5	8		STEL (15 min)	WEL
7697-37-2	Nitric acid	1	2.6		STEL (15 min)	WEL
88-89-1	Picric acid	-	0.1		TWA (8 h)	WEL
		-	0.3		STEL (15 min)	WEL

Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
78-93-3	Butan-2-one	butan-2-one	70 µmol/L	urine	Post shift

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value	
64-17-5	Ethanol	DNEL type			
		Worker DNEL, acute	inhalation	local	1900 mg/m ³
		Worker DNEL, long-term	dermal	systemic	343 mg/kg bw/day
		Worker DNEL, long-term	inhalation	systemic	950 mg/m ³
		Consumer DNEL, acute	inhalation	local	950 mg/m ³
		Consumer DNEL, long-term	dermal	systemic	206 mg/kg bw/day
		Consumer DNEL, long-term	inhalation	systemic	114 mg/m ³
		Consumer DNEL, long-term	oral	systemic	87 mg/kg bw/day
7647-01-0	hydrochloric acid %	Worker DNEL, acute			
		inhalation	local	15 mg/m ³	
		inhalation	local	8 mg/m ³	

Safety Data Sheet

according to UK REACH Regulation

Picric acid mixture to detect austenite

Revision date: 19.09.2023

Product code: 11554.xxxxx

Page 7 of 16

PNEC values

CAS No	Substance	
Environmental compartment		Value
64-17-5	Ethanol	
Freshwater		0,96 mg/l
Freshwater (intermittent releases)		2,75 mg/l
Marine water		0,79 mg/l
Marine water (intermittent releases)		2,75 mg/l
Freshwater sediment		3,6 mg/kg
Marine sediment		2,9 mg/kg
Secondary poisoning		0,72 mg/kg
Micro-organisms in sewage treatment plants (STP)		580 mg/l
Soil		0,63 mg/kg

8.2. Exposure controls



Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray. Provide adequate ventilation.

If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means. Use extractor hood (laboratory).

Individual protection measures, such as personal protective equipment

Eye/face protection

Suitable eye protection: goggles. Tightly sealed safety glasses. EN 166

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. In case of prolonged or frequently repeated skin contact:

Tested protective gloves are to be worn:

Suitable material:

Butyl rubber. (0,7 mm, Breakthrough time \geq 480 min, penetration time (maximum wearing period): 160 min):

NBR (Nitrile rubber). (0,4 mm, Breakthrough time \geq 120 min, penetration time (maximum wearing period): 40 min)

The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it.

Before using check leak tightness / impermeability. In the case of wanting to use the gloves again, clean them before taking off and air them well.

Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing Protective clothing. (fire retardant.)

Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500 (D).

Respiratory protection

In case of inadequate ventilation wear respiratory protection. With correct and proper use, and under normal conditions, breathing protection is not required.

Respiratory protection necessary at:

Safety Data Sheet

according to UK REACH Regulation

Picric acid mixture to detect austenite

Revision date: 19.09.2023

Product code: 11554.xxxxx

Page 8 of 16

Insufficient ventilation.

generation/formation of aerosols

exceeding exposure limit values

Suitable respiratory protective equipment: Combination filtering device (EN 14387) Type: ABEK-P2/3

The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.

Thermal hazards

Flame-retardant protective clothing. Wear anti-static footwear and clothing

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	liquid	
Colour:	yellow	
Odour:	characteristic/Alcohol	
Melting point/freezing point:		not determined
Boiling point or initial boiling point and boiling range:		not determined
Flammability:		not determined
Lower explosion limits:		not determined
Upper explosion limits:		not determined
Flash point:		12 °C
Auto-ignition temperature:		not determined
Decomposition temperature:		not determined
pH-Value (at 20 °C):		0-1
Viscosity / kinematic:		not determined
Water solubility: (at 20 °C)		completely miscible
Solubility in other solvents		not determined
Partition coefficient n-octanol/water:		not determined
Vapour pressure:		not determined
Density:		not determined
Relative vapour density:		not determined
Particle characteristics:		not applicable

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

The product is not: Explosive. Explosive when dry.

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

Self-ignition temperature

Gas: not determined

Oxidizing properties

none

Other safety characteristics

Evaporation rate: not determined

Solvent separation test: not determined

Solid content: not determined

Sublimation point: not determined

Softening point: not determined

Safety Data Sheet

according to UK REACH Regulation

Picric acid mixture to detect austenite

Revision date: 19.09.2023

Product code: 11554.xxxxx

Page 9 of 16

Pour point: not determined
Viscosity / dynamic: not determined
Flow time: not determined

Further Information

No information available.

SECTION 10: Stability and reactivity**10.1. Reactivity**

Corrosive to metals. Possibility of hazardous reactions. Highly flammable

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Exothermic reaction with: Base, Peroxides, Oxidizing agent. Reacts with : Reducing agent Oxidizing agents. Aluminium. Ammonia. Base. Heavy metal salts. fluorine. potassium. organic materials.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. Keep away from heat. In case of warming: Explosion hazard Ignition hazard. Do not allow to dry. Risk of explosion in case of drying up.

10.5. Incompatible materials

Metal. Keep away from: Base, Oxidizing agent, Peroxides. Reducing agent Oxidizing agents. Aluminium. Ammonia. Base. Heavy metal salts. fluorine. potassium. Alkali metals. Alkalis (alkalis). Steel. copper.

10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO₂). Nitrogen oxides (NO_x). Hydrogen chloride (HCl). Chlorine. nitrosyl chloride.

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in GB CLP Regulation****Acute toxicity**

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) 18018 mg/kg; ATE (dermal) 27036 mg/kg; ATE (inhalation vapour) 23,83 mg/l; ATE (inhalation dust/mist) 45,95 mg/l

Safety Data Sheet

according to UK REACH Regulation

Picric acid mixture to detect austenite

Revision date: 19.09.2023

Product code: 11554.xxxxx

Page 10 of 16

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64-17-5	Ethanol				
	oral	LD50 >5000 mg/kg	Rat	ECHA Dossier	
	dermal	LD50 >2000 mg/kg	Rabbit	ECHA Dossier	
	inhalation (4 h) vapour	LC50 124,7 mg/l	Rat	ECHA Dossier	
7697-37-2	nitric acid ... %				
	inhalation vapour	ATE 2,65 mg/l			
7647-01-0	hydrochloric acid %				
	oral	LD50 2222 mg/kg	Rat	suppliers SDS.	
88-89-1	picric acid				
	oral	LD50 200 mg/kg	Rat	RTECS	
	dermal	LD50 300,1 mg/kg			
	inhalation vapour	ATE 3 mg/l			
	inhalation (4 h) dust/mist	LC50 0,51 mg/l			
78-93-3	butanone				
	oral	LD50 2054 mg/kg	Ratte	SDB Lieferant	
	dermal	LD50 >2000 mg/kg	Rabbit	ECHA Dossier	

Irritation and corrosivity

Causes severe skin burns and eye damage. (On basis of test data)

Causes serious eye damage. (On basis of test data)

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards
Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

Other information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP]. Depending on the ingested quantity the following symptoms can be induced: a reduction of inhibitions, euphoria but also dysphoria, aggressiveness, impaired motoric skills, impaired responsiveness, blurred vision and fatigue.

Safety Data Sheet

according to UK REACH Regulation

Picric acid mixture to detect austenite

Revision date: 19.09.2023

Product code: 11554.xxxxx

Page 11 of 16

SECTION 12: Ecological information
12.1. Toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
64-17-5	Ethanol					
	Acute fish toxicity	LC50 14200 mg/l	96 h	Pimephales promelas (fathead minnow)	ECHA Dossier	
	Acute algae toxicity	ErC50 275 mg/l	72 h	Chlorella vulgaris	ECHA Dossier	
	Acute crustacea toxicity	EC50 5012 mg/l	48 h	Ceriodaphnia dubia (water flea)	ECHA Dossier	
	Crustacea toxicity	NOEC 9,6 mg/l	9 d	Daphnia magna	ECHA Dossier	
7647-01-0	hydrochloric acid %					
	Acute algae toxicity	ErC50 0,73 mg/l	72 h	Chlorella vulgaris	suppliers SDS.	OECD 201
	Acute crustacea toxicity	EC50 0,45 mg/l	48 h	Daphnia magna	suppliers SDS.	OECD 202
	Acute bacteria toxicity	(EC50 0,23 mg/l)	3 h	Activated sludge	ECHA	OECD 209
78-93-3	butanone					
	Acute fish toxicity	LC50 2993 mg/l	96 h	Pimephales promelas	ECHA Dossier	OECD 203
	Acute algae toxicity	ErC50 1972 mg/l	72 h	Pseudokirchnerella subcapitata	ECHA Dossier	OECD 201
	Acute crustacea toxicity	EC50 308 mg/l	48 h	Daphnia magna	ECHA Dossier	OECD 202

12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
64-17-5	Ethanol			
	other guideline	84%	20	ECHA Dossier
	Biodegradable.			
78-93-3	butanone			
		98%	28	ECHA Dossier
	Readily biodegradable (according to OECD criteria).			

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
64-17-5	Ethanol	-0,31
78-93-3	butanone	0,3

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

Safety Data Sheet

according to UK REACH Regulation

Picric acid mixture to detect austenite

Revision date: 19.09.2023

Product code: 11554.xxxxx

Page 12 of 16

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

The product has not been tested.

Further information

Avoid release to the environment. Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation. Consult the local waste disposal expert about waste disposal. Non-contaminated packages may be recycled. According to (EWC) European Waste Catalogue, allocation of waste identity numbers/waste descriptions must be carried out in a specific way for every industry and process.

Control report for waste code/ waste marking according to (EWC) European Waste Catalogue:

List of Wastes Code - residues/unused products

160506 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; laboratory chemicals, consisting of or containing hazardous substances, including mixtures of laboratory chemicals; hazardous waste

List of Wastes Code - used product

160506 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; laboratory chemicals, consisting of or containing hazardous substances, including mixtures of laboratory chemicals; hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Wash with plenty of water. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information**Land transport (ADR/RID)****14.1. UN number or ID number:**

UN 2924

14.2. UN proper shipping name:

FLAMMABLE LIQUID, CORROSIVE, N.O.S. (ethanol, Salpetersäure)

14.3. Transport hazard class(es):

3

14.4. Packing group:

II

Hazard label:

3+8



Classification code:

FC

Special Provisions:

274

Limited quantity:

1 L

Excepted quantity:

E2

Transport category:

2

Hazard No:

338

Tunnel restriction code:

D/E

Safety Data Sheet

according to UK REACH Regulation

Picric acid mixture to detect austenite

Revision date: 19.09.2023

Product code: 11554.xxxxx

Page 13 of 16

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 2924
14.2. UN proper shipping name: FLAMMABLE LIQUID, CORROSIVE, N.O.S. (ethanol, Salpetersäure)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3+8



Classification code: FC
 Special Provisions: 274
 Limited quantity: 1 L
 Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number or ID number: UN 2924
14.2. UN proper shipping name: FLAMMABLE LIQUID, CORROSIVE, N.O.S. (ethanol, nitric acid)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3+8



Special Provisions: 274
 Limited quantity: 1 L
 Excepted quantity: E2
 EmS: F-E, S-C

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 2924
14.2. UN proper shipping name: FLAMMABLE LIQUID, CORROSIVE, N.O.S. (ethanol, nitric acid)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3+8



Special Provisions: A3
 Limited quantity Passenger: 0.5 L
 Passenger LQ: Y340
 Excepted quantity: E2
 IATA-packing instructions - Passenger: 352
 IATA-max. quantity - Passenger: 1 L
 IATA-packing instructions - Cargo: 363
 IATA-max. quantity - Cargo: 5 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: Combustible liquid. strongly corrosive. Refer to section 6-8

14.7. Maritime transport in bulk according to IMO instruments

not relevant

Safety Data Sheet

according to UK REACH Regulation

Picric acid mixture to detect austenite

Revision date: 19.09.2023

Product code: 11554.xxxxx

Page 14 of 16

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

2010/75/EU (VOC): not determined

2004/42/EC (VOC): not determined

Information according to 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

Additional information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

Ethanol

nitric acid ... %

hydrochloric acid %

butanone

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 2,3,4,5,6,7,8,9,10,11,12,13,14,15,16.

Rev. 1.00; 13.10.2014 Initial release

Rev. 2.00; 22.12.2017, Changes in chapter: 1 -16.

Rev. 3.0; 19.09.2023; Change of classification/labeling

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

AwSV: Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen

AGW: Arbeitsplatzgrenzwert

AVV: Abfallverzeichnisverordnung

CAS Chemical Abstracts Service

CLP: Classification, Labelling and Packaging of substances and mixtures

DNEL: Derived No Effect Level

d: day(s)

EAKV: Europäisches Abfallverzeichnis gemäß Entwurf Abfallverzeichnisverordnung

EINECS: European Inventory of Existing Commercial chemical Substances

ELINCS: European List of Notified Chemical Substances

ECHA: European Chemicals Agency

EWC: European Waste Catalogue

IARC: INTERNATIONAL AGENCY FOR RESEARCH ON CANCER

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

GefStoffV: Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany)

Safety Data Sheet

according to UK REACH Regulation

Picric acid mixture to detect austenite

Revision date: 19.09.2023

Product code: 11554.xxxxx

Page 15 of 16

h: hour

LOAEL: Lowest observed adverse effect level

LOAEC: Lowest observed adverse effect concentration

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NOAEL: No observed adverse effect level

NOAEC: No observed adverse effect level

NLP: No-Longer Polymers

N/A: not applicable

OECD: Organisation for Economic Co-operation and Development

PNEC: predicted no effect concentration

PBT: Persistent bioaccumulative toxic

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

REACH: Registration, Evaluation, Authorisation of Chemicals

SVHC: substance of very high concern

TRGS Technische Regeln fuer Gefahrstoffe

UN: United Nations

VOC: Volatile Organic Compounds

VwVwS: Verwaltungsvorschrift wassergefaehrdender Stoffe

WGK: Wassergefaehrungsklasse

CLP: Classification, labelling and Packaging

REACH: Registration, Evaluation and Authorization of Chemicals

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

UN: United Nations

CAS: Chemical Abstracts Service

DNEL: Derived No Effect Level

DMEL: Derived Minimal Effect Level

PNEC: Predicted No Effect Concentration

ATE: Acute toxicity estimate

LL50: Lethal loading, 50%

EL50: Effect loading, 50%

EC50: Effective Concentration 50%

ErC50: Effective Concentration 50%, growth rate

NOEC: No Observed Effect Concentration

BCF: Bio-concentration factor

PBT: persistent, bioaccumulative, toxic

vPvB: very persistent, very bioaccumulative

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Regulations concerning the international carriage of dangerous goods by rail

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
(Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)

EmS: Emergency Schedules

MFAG: Medical First Aid Guide

MARPOL: International Convention for the Prevention of Marine Pollution from Ships

IBC: Intermediate Bulk Container

For abbreviations and acronyms, see table at <http://abbrev.esdscom.eu>

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

Safety Data Sheet

according to UK REACH Regulation

Picric acid mixture to detect austenite

Revision date: 19.09.2023

Product code: 11554.xxxxx

Page 16 of 16

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Met. Corr. 1; H290	On basis of test data
Flam. Liq. 2; H225	On basis of test data
Skin Corr. 1; H314	On basis of test data
Eye Dam. 1; H318	On basis of test data

Relevant H and EUH statements (number and full text)

H201	Explosive; mass explosion hazard.
H225	Highly flammable liquid and vapour.
H272	May intensify fire; oxidiser.
H290	May be corrosive to metals.
H301	Toxic if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH071	Corrosive to the respiratory tract.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations. Classification according to Regulation (EC) No 1272/2008 [CLP]

- Classification procedure:

Health hazards: Calculation method.

Environmental hazards: Calculation method.

Physical hazards: On basis of test data and / or calculated and / or estimated.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)