

**Safety Data Sheet**

according to UK REACH Regulation

**Rhodamine for Fat Staining**

Revision date: 04.01.2024

Product code: 12298.xxxxx

Page 1 of 15

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Rhodamine for Fat Staining

UFI: RU13-N15A-Q00D-TNNG

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**

Use as laboratory reagent. Intended for scientific research and development.

**Uses advised against**

Any non-intended use.

**1.3. Details of the supplier of the safety data sheet**

Company name:	MORPHISTO GmbH	
Street:	Schumannstr. 142/144	
Place:	D-63069 Offenbach	
Telephone:	+49 (0) 69 / 400 3019-60	Telefax: +49 (0) 69 / 400 3019-64
E-mail:	info@morphisto.de	
Contact person:	Morphisto GmbH	
E-mail:	gefahrstoffmanagement@morphisto.de	
Internet:	http://www.morphisto.de	

**1.4. Emergency telephone number:**

Poison Information Center Mainz, Germany, Tel: +49(0)6131/19240

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****GB CLP Regulation**

Flam. Liq. 2; H225

Eye Dam. 1; H318

Full text of hazard statements: see SECTION 16.

**2.2. Label elements****GB CLP Regulation****Hazard components for labelling**

propan-1-ol

Signal word: Danger

Pictograms:

**Hazard statements**

H225

Highly flammable liquid and vapour.

H318

Causes serious eye damage.

**Precautionary statements**

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233

Keep container tightly closed.

P280

Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

## Safety Data Sheet

according to UK REACH Regulation

### Rhodamine for Fat Staining

Revision date: 04.01.2024

Product code: 12298.xxxxx

Page 2 of 15

P310 Immediately call a POISON CENTER/doctor.

P403+P235 Store in a well-ventilated place. Keep cool.

**Labelling of packages where the contents do not exceed 125 ml**

**Signal word:** Danger

**Pictograms:**



#### Hazard statements

H318

#### Precautionary statements

P280-P305+P351+P338-P310

#### 2.3. Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulating and toxic (PBT) or very persistent and very bioaccumulating (vPvB) at levels of 0.1% or higher. Ecological information: The substance/mixture does not contain any components that are considered to be hazardous according to REACH Article 57(f) or Commission Delegated Regulation (EU) 2017/2100 or Commission Delegated Regulation (EU) 2018/605 in amounts of 0.1 % or more have endocrine disrupting properties. Toxicological information: The substance/mixture does not contain any components that are to be classified according to REACH Article 57(f) or Commission Delegated Regulation (EU) 2017/2100 or Commission Delegated Regulation (EU) 2018/605 in quantities of 0.1 % or more have endocrine disrupting properties.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

##### Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
64-17-5	Ethanol			95 - < 100 %
	200-578-6	603-002-00-5	01-2119457610-43	
	Flam. Liq. 2, Eye Irrit. 2; H225 H319			
71-23-8	propan-1-ol			1 - < 5 %
	200-746-9	603-003-00-0	01-2119486761-29	
	Flam. Liq. 2, Eye Dam. 1, STOT SE 3; H225 H318 H336			
78-93-3	butanone			< 1 %
	201-159-0	606-002-00-3	01-2119457290-43	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			

Full text of H and EUH statements: see section 16.

##### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
Specific Conc. Limits, M-factors and ATE			
64-17-5	200-578-6	Ethanol	95 - < 100 %
		inhalation: LC50 = 124,7 mg/l (vapours); dermal: LD50 = >2000 mg/kg; oral: LD50 = >5000 mg/kg Eye Irrit. 2; H319: >= 50 - 100	
71-23-8	200-746-9	propan-1-ol	1 - < 5 %
		dermal: LD50 = 40321 mg/kg	
78-93-3	201-159-0	butanone	< 1 %
		dermal: LD50 = >2000 mg/kg; oral: LD50 = 2054 mg/kg	

**Safety Data Sheet**

according to UK REACH Regulation

**Rhodamine for Fat Staining**

Revision date: 04.01.2024

Product code: 12298.xxxxx

Page 3 of 15

**Further Information**

This product contains no substances of very high concern (SVHC) (>0,1%) which are included in the Candidate List according to Article 59 of REACH.

**SECTION 4: First aid measures****4.1. Description of first aid measures****General information**

Remove affected person from the danger area and lay down. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

**After inhalation**

Provide fresh air. If unconscious but breathing normally, place in recovery position and seek medical advice. In case of allergic symptoms, especially in the breathing area, seek medical advice immediately.

**After contact with skin**

Take off contaminated clothing and wash it before reuse. Wash with plenty of water. In case of skin irritation, seek medical treatment.

**After contact with eyes**

Rinse immediately carefully and thoroughly with eye-bath or water. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

**After ingestion**

Rinse mouth thoroughly with water. Let water be drunk in little sips (dilution effect). Seek medical advice.

**4.2. Most important symptoms and effects, both acute and delayed**

Acute effects: Mucous membrane irritation after eye contact or inhalation.

Delayed effects: Impairment of inhibitory functions of the central nervous system, skin redness, nausea after ingestion of large amounts.

**4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptomatically.

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**

Water spray jet, Carbon dioxide (CO<sub>2</sub>), Foam, Extinguishing powder.

**Unsuitable extinguishing media**

High power water jet.

**5.2. Special hazards arising from the substance or mixture**

Highly flammable. Vapours can form explosive mixtures with air. The formation of combustible vapours is possible at temperatures above: 7°C. Vapours are heavier than air and will spread at floor level. In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO<sub>2</sub>).

**5.3. Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus. In case of fire and/or explosion do not breathe fumes.

**Additional information**

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment. (See section 8. ) Take action to

**Safety Data Sheet**

according to UK REACH Regulation

**Rhodamine for Fat Staining**

Revision date: 04.01.2024

Product code: 12298.xxxxx

Page 4 of 15

prevent static discharges. Ventilate affected area. Special danger of slipping by leaking/spilling product.

**6.2. Environmental precautions**

Do not allow uncontrolled discharge of product into the environment. Explosion risk. Do not allow to enter into surface water or drains. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Prevent spread over a wide area (e.g. by containment or oil barriers). In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

**6.3. Methods and material for containment and cleaning up****For cleaning up**

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

**Other information**

Ventilate affected area.  
Clear contaminated areas thoroughly.

**6.4. Reference to other sections**

Safe handling: see section 7  
Personal protection equipment: see section 8  
Disposal: see section 13

**SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes.  
Wear personal protection equipment. (See section 8.) Use extractor hood (laboratory).

**Advice on protection against fire and explosion**

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air. Flammable vapours can accumulate in head space of closed systems. Heating causes rise in pressure with risk of bursting.

**Advice on general occupational hygiene**

Take off contaminated clothing and wash it before reuse. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat, drink, smoke, sniff. Always close containers tightly after the removal of product.

**Further information on handling**

General protection and hygiene measures: refer to chapter 8

**7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

Keep container tightly closed in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep/Store only in original container. Protect from direct sunlight.

Ensure adequate ventilation of the storage area. Concentrated vapours are heavier than air.

Suitable material for Container: Stainless steel. (1.4301 (V2), 1.4401 (V4)); iron. solvent resistant plastics.

Unsuitable materials for Container: Aluminium. Rubber. various plastics.

**Hints on joint storage**

Do not store together with: Oxidizing agent. Pyrophoric or self-heating substances. Do not store together with: Gas. Explosives. Flammable solids. Pyrophoric liquids and solids. Self-heating substances and mixtures. Substances or mixtures which, in contact with water, emit flammable gases. Oxidizing liquids. ammonium nitrate. Self-reactive substances and mixtures. Organic peroxides. Non-combustible toxic substances. Radioactive substances. Infectious substances.

**Further information on storage conditions**

Recommended storage temperature: 15 - 25 °C

Protect against: UV-radiation/sunlight. heat. Cold.

## Safety Data Sheet

according to UK REACH Regulation

### Rhodamine for Fat Staining

Revision date: 04.01.2024

Product code: 12298.xxxxx

Page 5 of 15

#### 7.3. Specific end use(s)

See section 1.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
78-93-3	Butan-2-one (methyl ethyl ketone)	200	600		TWA (8 h)	WEL
		300	899		STEL (15 min)	WEL
64-17-5	Ethanol	1000	1920		TWA (8 h)	WEL
71-23-8	Propan-1-ol	200	500		TWA (8 h)	WEL
		250	625		STEL (15 min)	WEL

##### Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
78-93-3	Butan-2-one	butan-2-one	70 µmol/L	urine	Post shift

##### DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
64-17-5	Ethanol			
Worker DNEL, acute		inhalation	local	1900 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	343 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	950 mg/m <sup>3</sup>
Consumer DNEL, acute		inhalation	local	950 mg/m <sup>3</sup>
Consumer DNEL, long-term		dermal	systemic	206 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	114 mg/m <sup>3</sup>
Consumer DNEL, long-term		oral	systemic	87 mg/kg bw/day
78-93-3	butanone			
Worker DNEL, long-term		inhalation	systemic	600 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	1161 mg/kg bw/day

**Safety Data Sheet**

according to UK REACH Regulation

**Rhodamine for Fat Staining**

Revision date: 04.01.2024

Product code: 12298.xxxxx

Page 6 of 15

**PNEC values**

CAS No	Substance	Value
Environmental compartment		
64-17-5	Ethanol	
Freshwater		0,96 mg/l
Freshwater (intermittent releases)		2,75 mg/l
Marine water		0,79 mg/l
Marine water (intermittent releases)		2,75 mg/l
Freshwater sediment		3,6 mg/kg
Marine sediment		2,9 mg/kg
Secondary poisoning		0,72 mg/kg
Micro-organisms in sewage treatment plants (STP)		580 mg/l
Soil		0,63 mg/kg
78-93-3	butanone	
Freshwater		55,8 mg/l
Freshwater (intermittent releases)		55,8 mg/l
Marine water		55,8 mg/l
Freshwater sediment		284,7 mg/kg
Marine sediment		284,7 mg/kg
Micro-organisms in sewage treatment plants (STP)		709 mg/l
Soil		22,5 mg/kg

**8.2. Exposure controls**

**Appropriate engineering controls**

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray. Provide adequate ventilation.

If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

Use extractor hood (laboratory).

**Individual protection measures, such as personal protective equipment**
**Eye/face protection**

Suitable eye protection: goggles. Tightly sealed safety glasses. EN 166

**Hand protection**

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. In case of prolonged or frequently repeated skin contact:

Tested protective gloves are to be worn:

Suitable material:

Butyl rubber. (0,7 mm, Breakthrough time  $\geq$ 480 min, penetration time (maximum wearing period): 160 min):

NBR (Nitrile rubber). (0,4 mm, Breakthrough time  $\geq$ 120 min, penetration time (maximum wearing period): 40 min)

The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard

## Safety Data Sheet

according to UK REACH Regulation

### Rhodamine for Fat Staining

Revision date: 04.01.2024

Product code: 12298.xxxxx

Page 7 of 15

EN 374 derived from it.

Before using check leak tightness / impermeability. In the case of wanting to use the gloves again, clean them before taking off and air them well.

#### Skin protection

Protective clothing. (fire retardant.)

Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500 (D).

#### Respiratory protection

In case of inadequate ventilation wear respiratory protection. With correct and proper use, and under normal conditions, breathing protection is not required.

Respiratory protection necessary at:

Insufficient ventilation.

exceeding exposure limit values

generation/formation of aerosols

Suitable respiratory protective equipment:

gas filtering equipment (EN 141). Type : a

The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.

The wearing time limitations according to GefStoffV in conjunction with the rules for the use of respiratory protective devices (BGR 190) must be observed.

#### Thermal hazards

Flame-retardant protective clothing. Wear anti-static footwear and clothing . . .

#### Environmental exposure controls

Do not allow to enter into surface water or drains.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	liquid	
Colour:	red	
Odour:	characteristic	
Melting point/freezing point:		not determined
Boiling point or initial boiling point and boiling range:		78 °C
Flammability:		not determined
Lower explosion limits:		not determined
Upper explosion limits:		not determined
Flash point:		15 °C
Auto-ignition temperature:		not determined
Decomposition temperature:		not determined
pH-Value:		not determined
Viscosity / kinematic:		not determined
Water solubility:		completely miscible
(at 20 °C)		
Solubility in other solvents		
not determined		
Partition coefficient n-octanol/water:		not determined
Vapour pressure:		58 hPa
(at 20 °C)		
Vapour pressure:		293 hPa
(at 50 °C)		
Density (at 20 °C):		0,79 g/cm <sup>3</sup>

**Safety Data Sheet**

according to UK REACH Regulation

**Rhodamine for Fat Staining**

Revision date: 04.01.2024

Product code: 12298.xxxxx

Page 8 of 15

Relative vapour density: not determined  
Particle characteristics: not applicable

**9.2. Other information****Information with regard to physical hazard classes****Explosive properties**

The product is not: Explosive. Vapours of flammable solvents can accumulate in the gas phase of closed container, especially during heat treatment. Therefore keep away from fire and sources of ignition.

**Self-ignition temperature**

Gas: not determined

**Oxidizing properties**

none

**Other safety characteristics**

Evaporation rate: not determined

Solvent separation test: not determined

Solvent content: not determined

Solid content: not determined

Sublimation point: not determined

Softening point: not determined

Pour point: not determined

Viscosity / dynamic: not determined

Flow time: not determined

**SECTION 10: Stability and reactivity****10.1. Reactivity**

Highly flammable

**10.2. Chemical stability**

Stable under normal storage and handling conditions.

**10.3. Possibility of hazardous reactions**

Explosion risk in contact with: Oxidizing agents, strong. nitric acid. Hydrogenium peroxide.

Exothermic reactions with: Alkali metals. Alkaline earth metals. Reducing agents, strong.

**10.4. Conditions to avoid**

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. Keep away from heat. Protect from direct sunlight. Protect from moisture.

In use may form flammable/explosive vapour-air mixture.

Heating causes rise in pressure with risk of bursting. Recommended storage temperature: < 40 °C

**10.5. Incompatible materials**

Materials to avoid: Substances that form flammable gases when in contact with water. Organic peroxides.

Inflammatory substances. Alkali metals. Acid chlorides. Organic peroxides. Oxidizing agents.

**10.6. Hazardous decomposition products**

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO<sub>2</sub>).

**SECTION 11: Toxicological information****11.1. Information on hazard classes as defined in GB CLP Regulation****Acute toxicity**

Based on available data, the classification criteria are not met.

**ATEmix calculated**

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l



**Safety Data Sheet**

according to UK REACH Regulation

**Rhodamine for Fat Staining**

Revision date: 04.01.2024

Product code: 12298.xxxxx

Page 9 of 15

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64-17-5	Ethanol				
	oral	LD50 >5000 mg/kg	Rat	ECHA Dossier	
	dermal	LD50 >2000 mg/kg	Rabbit	ECHA Dossier	
	inhalation (4 h) vapour	LC50 124,7 mg/l	Rat	ECHA Dossier	
71-23-8	propan-1-ol				
	dermal	LD50 40321 mg/kg	Kaninchen		
78-93-3	butanone				
	oral	LD50 2054 mg/kg	Ratte	SDB Lieferant	
	dermal	LD50 >2000 mg/kg	Rabbit	ECHA Dossier	

**Irritation and corrosivity**

Causes serious eye damage.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

**Sensitising effects**

Based on available data, the classification criteria are not met.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.

**STOT-single exposure**

Based on available data, the classification criteria are not met.

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**11.2. Information on other hazards**
**Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

**Other information**

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP]. Depending on the ingested quantity the following symptoms can be induced: a reduction of inhibitions, euphoria but also dysphoria, aggressiveness, impaired motoric skills, impaired responsiveness, blurred vision and fatigue.

**SECTION 12: Ecological information**
**12.1. Toxicity**

Based on available data, the classification criteria are not met.

## Safety Data Sheet

according to UK REACH Regulation

### Rhodamine for Fat Staining

Revision date: 04.01.2024

Product code: 12298.xxxxx

Page 10 of 15

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
64-17-5	Ethanol					
	Acute fish toxicity	LC50 mg/l	14200	96 h	Pimephales promelas (fathead minnow)	ECHA Dossier
	Acute algae toxicity	ErC50	275 mg/l	72 h	Chlorella vulgaris	ECHA Dossier
	Acute crustacea toxicity	EC50 mg/l	5012	48 h	Ceriodaphnia dubia (water flea)	ECHA Dossier
	Crustacea toxicity	NOEC	9,6 mg/l	9 d	Daphnia magna	ECHA Dossier
71-23-8	propan-1-ol					
	Acute fish toxicity	LC50 mg/l	4555	96 h		ECHA Dossier
	Acute crustacea toxicity	EC50 mg/l	3644	48 h		ECHA Dossier
78-93-3	butanone					
	Acute fish toxicity	LC50 mg/l	2993	96 h	Pimephales promelas	ECHA Dossier OECD 203
	Acute algae toxicity	ErC50 mg/l	1972	72 h	Pseudokirchnerella subcapitata	ECHA Dossier OECD 201
	Acute crustacea toxicity	EC50	308 mg/l	48 h	Daphnia magna	ECHA Dossier OECD 202

#### 12.2. Persistence and degradability

No information available.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
64-17-5	Ethanol			
	other guideline	84%	20	ECHA Dossier
	Biodegradable.			
78-93-3	butanone			
		98%	28	ECHA Dossier
	Readily biodegradable (according to OECD criteria).			

#### 12.3. Bioaccumulative potential

The product has not been tested.

#### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
64-17-5	Ethanol	-0,31
71-23-8	propan-1-ol	0,2
78-93-3	butanone	0,3

#### 12.4. Mobility in soil

The product has not been tested.

#### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

#### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

#### 12.7. Other adverse effects

No information available.

**Safety Data Sheet**

according to UK REACH Regulation

**Rhodamine for Fat Staining**

Revision date: 04.01.2024

Product code: 12298.xxxxx

Page 11 of 15

**Further information**

Avoid release to the environment. Do not allow to enter into surface water or drains.

**SECTION 13: Disposal considerations****13.1. Waste treatment methods****Disposal recommendations**

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation. Consult the local waste disposal expert about waste disposal. Non-contaminated packages may be recycled. According to (EWC) European Waste Catalogue, allocation of waste identity numbers/waste descriptions must be carried out in a specific way for every industry and process.

Control report for waste code/ waste marking according to (EWC) European Waste Catalogue:

**List of Wastes Code - residues/unused products**

160506 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; laboratory chemicals, consisting of or containing hazardous substances, including mixtures of laboratory chemicals; hazardous waste

**List of Wastes Code - used product**

160506 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; laboratory chemicals, consisting of or containing hazardous substances, including mixtures of laboratory chemicals; hazardous waste

**List of Wastes Code - contaminated packaging**

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

**Contaminated packaging**

Wash with plenty of water. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself. Non-contaminated packages may be recycled.

**SECTION 14: Transport information****Land transport (ADR/RID)**

<b>14.1. UN number or ID number:</b>	UN 1170
<b>14.2. UN proper shipping name:</b>	ETHANOL
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3



Classification code:	F1
Special Provisions:	144 601
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	33
Tunnel restriction code:	D/E

**Inland waterways transport (ADN)**

<b>14.1. UN number or ID number:</b>	UN 1170
<b>14.2. UN proper shipping name:</b>	ETHANOL
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II

**Safety Data Sheet**

according to UK REACH Regulation

**Rhodamine for Fat Staining**

Revision date: 04.01.2024

Product code: 12298.xxxxx

Page 12 of 15

Hazard label: 3



Classification code: F1

Special Provisions: 144 601

Limited quantity: 1 L

Excepted quantity: E2

**Marine transport (IMDG)**
**14.1. UN number or ID number:** UN 1170

**14.2. UN proper shipping name:** ETHANOL

**14.3. Transport hazard class(es):** 3

**14.4. Packing group:** II

Hazard label: 3



Special Provisions: 144

Limited quantity: 1 L

Excepted quantity: E2

EmS: F-E, S-D

**Air transport (ICAO-TI/IATA-DGR)**
**14.1. UN number or ID number:** UN 1170

**14.2. UN proper shipping name:** ETHANOL

**14.3. Transport hazard class(es):** 3

**14.4. Packing group:** II

Hazard label: 3



Special Provisions: A3 A58 A180

Limited quantity Passenger: 1 L

Passenger LQ: Y341

Excepted quantity: E2

IATA-packing instructions - Passenger: 353

IATA-max. quantity - Passenger: 5 L

IATA-packing instructions - Cargo: 364

IATA-max. quantity - Cargo: 60 L

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

**14.6. Special precautions for user**

Warning: Combustible liquid. Refer to section 6-8

**14.7. Maritime transport in bulk according to IMO instruments**

not relevant

**SECTION 15: Regulatory information**
**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**
**EU regulatory information**

**Safety Data Sheet**

according to UK REACH Regulation

**Rhodamine for Fat Staining**

Revision date: 04.01.2024

Product code: 12298.xxxxx

Page 13 of 15

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Directive 2010/75/EU on industrial emissions: not determined

Directive 2004/42/EC on VOC in paints and varnishes: not determined

Information according to Directive 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

**Additional information**

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

**National regulatory information**

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

**15.2. Chemical safety assessment**

For the following substances of this mixture a chemical safety assessment has been carried out:

Ethanol  
propan-1-ol  
butanone**SECTION 16: Other information****Changes**

This data sheet contains changes from the previous version in section(s): 1,2,3,5,6,7,9,11,12,13,14,15,16.

Rev. 2,0; Individual safety data sheet based on 10369\_collect

Rev. 2,1; 04.01.2024; general adjustment(s)

**Safety Data Sheet**

according to UK REACH Regulation

**Rhodamine for Fat Staining**

Revision date: 04.01.2024

Product code: 12298.xxxxx

Page 14 of 15

**Abbreviations and acronyms**

Flam. Liq: Flammable liquids  
Eye Dam: Eye damage  
Eye Irrit: Eye irritation  
STOT SE: Specific target organ toxicity - single exposure  
ADR: Accord européen sur le transport des marchandises dangereuses par Route  
AwSV: Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen  
AGW: Arbeitsplatzgrenzwert  
AVV: Abfallverzeichnisverordnung  
CAS: Chemical Abstracts Service  
CLP: Classification, Labelling and Packaging of substances and mixtures  
DNEL: Derived No Effect Level  
d: day(s)  
EAKV: Europäisches Abfallverzeichnis gemäß Entwurf Abfallverzeichnisverordnung  
EINECS: European Inventory of Existing Commercial chemical Substances  
ELINCS: European List of Notified Chemical Substances  
ECHA: European Chemicals Agency  
EWC: European Waste Catalogue  
IARC: INTERNATIONAL AGENCY FOR RESEARCH ON CANCER  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)  
ICAO: International Civil Aviation Organization  
ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)  
GHS: Globally Harmonized System of Classification and Labelling of Chemicals  
GefStoffV: Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany)  
h: hour  
LOAEL: Lowest observed adverse effect level  
LOAEC: Lowest observed adverse effect concentration  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
NOAEL: No observed adverse effect level  
NOAEC: No observed adverse effect level  
NLP: No-Longer Polymers  
N/A: not applicable  
OECD: Organisation for Economic Co-operation and Development  
PNEC: predicted no effect concentration  
PBT: Persistent bioaccumulative toxic  
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail )  
REACH: Registration, Evaluation, Authorisation of Chemicals  
SVHC: substance of very high concern  
TRGS Technische Regeln fuer Gefahrstoffe  
UN: United Nations  
VOC: Volatile Organic Compounds  
VwVwS: Verwaltungsvorschrift wassergefährdender Stoffe  
WGK: Wassergefährdungsklasse  
CLP: Classification, labelling and Packaging  
REACH: Registration, Evaluation and Authorization of Chemicals  
GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals  
UN: United Nations  
CAS: Chemical Abstracts Service  
DNEL: Derived No Effect Level  
DMEL: Derived Minimal Effect Level  
PNEC: Predicted No Effect Concentration  
ATE: Acute toxicity estimate

**Safety Data Sheet**

according to UK REACH Regulation

**Rhodamine for Fat Staining**

Revision date: 04.01.2024

Product code: 12298.xxxxx

Page 15 of 15

LL50: Lethal loading, 50%  
 EL50: Effect loading, 50%  
 EC50: Effective Concentration 50%  
 ErC50: Effective Concentration 50%, growth rate  
 NOEC: No Observed Effect Concentration  
 BCF: Bio-concentration factor  
 PBT: persistent, bioaccumulative, toxic  
 vPvB: very persistent, very bioaccumulative  
 ADR: Accord européen sur le transport des marchandises dangereuses par Route  
 (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 RID: Regulations concerning the international carriage of dangerous goods by rail  
 ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways  
 (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation  
 intérieures)  
 EmS: Emergency Schedules  
 MFAG: Medical First Aid Guide  
 MARPOL: International Convention for the Prevention of Marine Pollution from Ships  
 IBC: Intermediate Bulk Container  
 For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety  
 assessment, chapter R.20 (Table of terms and abbreviations).

**Classification for mixtures and used evaluation method according to GB CLP Regulation**

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Eye Dam. 1; H318	Calculation method

**Relevant H and EUH statements (number and full text)**

H225 Highly flammable liquid and vapour.  
 H318 Causes serious eye damage.  
 H319 Causes serious eye irritation.  
 H336 May cause drowsiness or dizziness.  
 EUH066 Repeated exposure may cause skin dryness or cracking.

**Further Information**

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations. Classification according to Regulation (EC) No 1272/2008 [CLP] - Classification procedure:

Health hazards: Calculation method.

Environmental hazards: Calculation method.

Physical hazards: On basis of test data and / or calculated and / or estimated.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*