

according to UK REACH Regulation

## **SCHAFFER's Fixative (NaPh-buffered Formaline & Methanol)**

Revision date: 22.09.2023 Product code: 15201.xxxxx Page 1 of 15

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

SCHAFFER's Fixative (NaPh-buffered Formaline & Methanol)

UFI: G33C-X1VR-V001-3P9S

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

### Use of the substance/mixture

Use as laboratory reagent.

### Uses advised against

Any non-intended use.

## 1.3. Details of the supplier of the safety data sheet

Company name: MORPHISTO GmbH
Street: Schumannstr. 142/144
Place: D-63069 Offenbach

Telephone: +49 (0) 69 / 400 3019-60 Telefax: +49 (0) 69 / 400 3019-64

E-mail: info@morphisto.de
Contact person: Morphisto GmbH

E-mail: gefahrstoffmanagement@morphisto.de

Internet: http://www.morphisto.de

**1.4. Emergency telephone** Poison Information Center Mainz, Germany, Tel: +49(0)6131/19240

number:

### **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

## **GB CLP Regulation**

Flam. Liq. 2; H225 Acute Tox. 3; H301 Acute Tox. 3; H311 Acute Tox. 3; H331 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Muta. 2; H341 Carc. 1B; H350 STOT SE 1; H370 STOT SE 3; H335

Full text of hazard statements: see SECTION 16.

## 2.2. Label elements

### **GB CLP Regulation**

# Hazard components for labelling

methanol formaldehyde %

Signal word: Danger

Pictograms:









according to UK REACH Regulation

## SCHAFFER's Fixative (NaPh-buffered Formaline & Methanol)

Revision date: 22.09.2023 Product code: 15201.xxxxx Page 2 of 15

#### **Hazard statements**

H225 Highly flammable liquid and vapour.

H301+H311+H331 Toxic if swallowed, in contact with skin or if inhaled.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H335 May cause respiratory irritation.
 H341 Suspected of causing genetic defects.

H350 May cause cancer.

H370 Causes damage to organs.

## **Precautionary statements**

P201 Obtain special instructions before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smokina.

P260 Do not breathe mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P308+P311 IF exposed or concerned: Call a POISON CENTER/doctor.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.

### Special labelling of certain mixtures

Restricted to professional users.

### Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

Pictograms:







## Hazard statements

H301+H311+H331-H317-H341-H350-H370

### **Precautionary statements**

P201-P260-P280-P301+P310-P308+P311

## 2.3. Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulating and toxic (PBT) or very persistent and very bioaccumulating (vPvB) at levels of 0.1% or higher. Ecological information: The substance/mixture does not contain any components that are considered to be hazardous according to REACH Article 57(f) or Commission Delegated Regulation (EU) 2017/2100 or Commission Delegated Regulation (EU) 2018/605 in amounts of 0.1 % or more have endocrine disrupting properties. Toxicological information: The substance/mixture does not contain any components that are to be classified according to REACH Article 57(f) or Commission Delegated Regulation (EU) 2017/2100 or Commission Delegated Regulation (EU) 2018/605 in quantities of 0.1 % or more have endocrine disrupting properties.

# **SECTION 3: Composition/information on ingredients**

## 3.2. Mixtures



according to UK REACH Regulation

## SCHAFFER's Fixative (NaPh-buffered Formaline & Methanol)

Revision date: 22.09.2023 Product code: 15201.xxxxx Page 3 of 15

### **Hazardous components**

CAS No	Chemical name	Chemical name		
	EC No	Index No	REACH No	
	Classification (GB CLP F	Regulation)	•	
67-56-1	methanol			60 - < 65 %
	200-659-6	603-001-00-X	01-2119433307-44	
	Flam. Liq. 2, Acute Tox.	3, Acute Tox. 3, Acute Tox. 3, STOT	SE 1; H225 H331 H311 H301 H370	
50-00-0	formaldehyde %			10 - < 15 %
	200-001-8	605-001-00-5	01-2119488953-20	
	Carc. 1B, Muta. 2, Acute Tox. 3, Acute Tox. 3, Acute Tox. 3, Skin Corr. 1B, Skin Sens. 1; H350 H341 H331 H311 H301 H314 H317			

Full text of H and EUH statements: see section 16.

### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. I	Limits, M-factors and ATE	
67-56-1	200-659-6	methanol	60 - < 65 %
		= 3 mg/l (vapours); inhalation: ATE = 0,5 mg/l (dusts or mists); dermal: LD50 = ral: LD50 = 2528 mg/kg	
50-00-0	200-001-8	formaldehyde %	10 - < 15 %
	ATE = 300 mg/l	0 = <463 mg/l (vapours); inhalation: ATE = 0,5 mg/l (dusts or mists); dermal: kg; oral: LD50 = 640 mg/kg Skin Corr. 1B; H314: >= 25 - 100 Skin Irrit. 2; 25 Eye Irrit. 2; H319: >= 5 - < 25 Skin Sens. 1; H317: >= 0,2 - 100 STOT SE 100	

### **Further Information**

This product contains no substances of very high concern (SVHC) (>0,1%) which are included in the Candidate List according to Article 59 of REACH.

# **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

### **General information**

First aider: Pay attention to self-protection! Remove affected person from the danger area and lay down. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Remove contaminated, saturated clothing immediately.

## After inhalation

Provide fresh air. If breathing is irregular or stopped, administer artificial respiration. No mouth-to-mouth or mouth-to-nose resuscitation. Use Ambu bag or ventilator. In case of accident by inhalation: remove casualty to fresh air and keep at rest. Call a physician immediately.

## After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. Call a physician immediately.

### After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Consult an ophthalmologist.

## After ingestion

Observe risk of aspiration if vomiting occurs. Rinse mouth thoroughly with water. Let water be drunken in little sips (dilution effect). Do NOT induce vomiting. Never give anything by mouth to an unconscious person or a person with cramps. Call a physician immediately.





according to UK REACH Regulation

## **SCHAFFER's Fixative (NaPh-buffered Formaline & Methanol)**

Revision date: 22.09.2023 Product code: 15201.xxxxx Page 4 of 15

### 4.2. Most important symptoms and effects, both acute and delayed

Possible harmful effect(s) on human beings and possible symptom(s): Headache. drowsiness. Nausea. vomiting. eye defects.

Ingestion: Toxic: danger of very serious irreversible effects if swallowed. Fatal if swallowed. (> 100 ml) If swallowed there is a risk of going blind.

Inhalation: Toxic: danger of very serious irreversible effects through inhalation.

Skin contact: Large-scale skin contact may cause severe poisoning. Has de-greasing effect on the skin.

Repeated exposure may cause skin dryness or cracking.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. First Aid, decontamination, treatment of symptoms.

### **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

### Suitable extinguishing media

Water spray jet, Carbon dioxide (CO2), Foam, Extinguishing powder.

### Unsuitable extinguishing media

High power water jet.

### 5.2. Special hazards arising from the substance or mixture

Highly flammable. Vapours can form explosive mixtures with air. In case of fire may be liberated: Carbon monoxide (CO). Carbon dioxide (CO2). Formaldehyde

# 5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

## Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

### **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

### General advice

Remove all sources of ignition. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment. Ventilate affected area. Remove persons to safety. Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection.

### 6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Explosion risk. Do not allow to enter into surface water or drains. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Eliminate leaks immediately. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

## 6.3. Methods and material for containment and cleaning up

# For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

### Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Treat the recovered material as prescribed in the section on waste disposal.

The contaminated area should be cleaned up immediately with: a concentrated aqueous sodium bisulfite solution. Rinse with water.



according to UK REACH Regulation

## SCHAFFER's Fixative (NaPh-buffered Formaline & Methanol)

Revision date: 22.09.2023 Product code: 15201.xxxxx Page 5 of 15

### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

## **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

### Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray. Technical ventilation of workplace.

Wear suitable protective clothing. (See section 8.)

Avoid exposure - obtain special instructions before use.

Avoid contact with skin, eyes and clothes.

## Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

### Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat, drink, smoke, sniff. Always close containers tightly after the removal of product. Wash contaminated clothing prior to re-use. Used working clothes should not be worn outside the work area. Street clothing should be stored seperately from work clothing.

## Further information on handling

Flammable vapours can accumulate in head space of closed systems.

General protection and hygiene measures: refer to chapter 8

## 7.2. Conditions for safe storage, including any incompatibilities

## Requirements for storage rooms and vessels

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaustion at critical locations. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep locked up. Recommended storage temperature: 15-25 °C

### Hints on joint storage

Do not store together with: Oxidizing agent. Pyrophoric or self-heating substances. Do not store together with: Gas. Explosives. Flammable solids. Pyrophoric liquids and solids. Self-heating substances and mixtures. Substances or mixtures which, in contact with water, emit flammable gases. Oxidizing liquids. Oxidizing solids. ammonium nitrate. Self-reactive substances and mixtures. Organic peroxides. Non-combustible toxic substances. Radioactive substances. Infectious substances.

## Further information on storage conditions

Keep/Store only in original container. Ensure adequate ventilation of the storage area. Store small packages in a suitable, robust cabinet.

Protect against: UV-radiation/sunlight.

### 7.3. Specific end use(s)

See section 1.

## **SECTION 8: Exposure controls/personal protection**

## 8.1. Control parameters



according to UK REACH Regulation

# **SCHAFFER's Fixative (NaPh-buffered Formaline & Methanol)**

Revision date: 22.09.2023 Product code: 15201.xxxxx Page 6 of 15

# **Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
50-00-0	Formaldehyde	2	2.5		TWA (8 h)	WEL
		2	2.5		STEL (15 min)	WEL
67-56-1	Methanol	200	266		TWA (8 h)	WEL
		250	333		STEL (15 min)	WEL

# **DNEL/DMEL values**

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
67-56-1	methanol			
Worker DNEL,	acute	inhalation	local	260 mg/m³
Worker DNEL,	acute	dermal	systemic	40 mg/kg bw/day
Worker DNEL,	acute	inhalation	systemic	260 mg/m³
Worker DNEL,	long-term	inhalation	local	260 mg/m³
Worker DNEL,	long-term	dermal	systemic	40 mg/kg bw/day
Worker DNEL,	long-term	inhalation	systemic	260 mg/m³
50-00-0	formaldehyde %			
Worker DNEL,	acute	inhalation	systemic	1 mg/m³
Worker DNEL,	long-term	dermal	systemic	240 mg/kg bw/day
Worker DNEL,	long-term	inhalation	systemic	0,5 mg/m³
Worker DNEL, long-term		inhalation	local	0,375 mg/m³
Worker DNEL,	acute	inhalation	local	0,75 mg/m³
Worker DNEL,	long-term	dermal	local	0,037 mg/cm <sup>2</sup>

# PNEC values

CAS No	Substance	
Environmenta	I compartment	Value
67-56-1	methanol	
Freshwater	20,8 mg/l	
Marine water		2,08 mg/l
Marine water	(intermittent releases)	1540 mg/l
Freshwater se	ediment	77 mg/kg
Marine sediment		7,7 mg/kg
Micro-organisms in sewage treatment plants (STP)		100 mg/l
Soil		3,18 mg/kg
50-00-0	formaldehyde %	
Freshwater		0,44 mg/l
Freshwater (in	ntermittent releases)	4,44 mg/l
Marine water		0,44 mg/l
Freshwater sediment		2,3 mg/kg
Marine sediment 2,3 mg/kg		2,3 mg/kg
Micro-organisms in sewage treatment plants (STP) 0,19 mg/l		
Soil		0,2 mg/kg



according to UK REACH Regulation

## SCHAFFER's Fixative (NaPh-buffered Formaline & Methanol)

Revision date: 22.09.2023 Product code: 15201.xxxxx Page 7 of 15

### 8.2. Exposure controls











### Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe qas/fumes/vapour/spray. Technical ventilation of workplace.

### Individual protection measures, such as personal protective equipment

## Eye/face protection

Suitable eye protection: goggles. Tightly sealed safety glasses. EN 166

### Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Pull-over gloves of rubber. EN ISO 374

Suitable material:

(penetration time (maximum wearing period): >= 8 h):

Butyl rubber. (0,5 mm)

(penetration time (maximum wearing period): >= 4 h):

FKM (fluororubber). (0,4 mm)

(penetration time (maximum wearing period): >= 1 h):

CR (polychloroprenes, Chloroprene rubber). (0,5 mm)

Before using check leak tightness / impermeability. In the case of wanting to use the gloves again, clean them before taking off and air them well.

### Skin protection

Wear fire resistant or flame retardant clothing.

Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500 (D).

### Respiratory protection

In case of inadequate ventilation wear respiratory protection. Respiratory protection necessary at:

Insufficient ventilation.

insufficient absorbtion.

exceeding exposure limit values.

Suitable respiratory protective equipment: Protective respiration apparatus not using surrounding air (breathing apparatus) (DIN EN 133).

## Thermal hazards

Flame-retardant protective clothing. Wear anti-static footwear and clothing .

### **Environmental exposure controls**

Do not empty into drains.

# **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state: liquid
Colour: colourless
Odour: characteristic

Melting point/freezing point:

Boiling point or initial boiling point and

not determined
not determined

boiling range:

Flammability: not determined



according to UK REACH Regulation

## **SCHAFFER's Fixative (NaPh-buffered Formaline & Methanol)**

Revision date: 22.09.2023 Product code: 15201.xxxxx Page 8 of 15

Lower explosion limits: not determined not determined Upper explosion limits: Flash point: 9.7 °C 430 °C Auto-ignition temperature: Decomposition temperature: not determined pH-Value: not determined Viscosity / kinematic: not determined Water solubility: miscible.

(at 20 °C)

Solubility in other solvents

Alcohol.

Partition coefficient n-octanol/water: not determined Vapour pressure: 129 hPa

(at 20 °C)

Density (at 20 °C): 0,84 g/cm³
Relative vapour density: not determined
Particle characteristics: not applicable

### 9.2. Other information

### Information with regard to physical hazard classes

Explosive properties

The product is not: Explosive.

Oxidizing properties

none

## Other safety characteristics

Solid content: not determined
Pour point: not determined
Viscosity / dynamic: not determined

## **SECTION 10: Stability and reactivity**

# 10.1. Reactivity

Highly flammable

## 10.2. Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

## 10.3. Possibility of hazardous reactions

No information available.

### 10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. Keep away from heat.

In case of warming: Explosion hazard Ignition hazard.

Heating causes rise in pressure with risk of bursting.

# 10.5. Incompatible materials

Materials to avoid: Oxidizing agents, strong. acid. Slowly corrodes aluminium and zink under hydrogen evolution.

## 10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon monoxide (CO). Carbon dioxide (CO2). Formaldehyde.

## **SECTION 11: Toxicological information**

# 11.1. Information on hazard classes as defined in GB CLP Regulation



according to UK REACH Regulation

## **SCHAFFER's Fixative (NaPh-buffered Formaline & Methanol)**

Revision date: 22.09.2023 Product code: 15201.xxxxx Page 9 of 15

### **Acute toxicity**

Toxic if swallowed.

Toxic in contact with skin.

Toxic if inhaled.

### **ATEmix** calculated

ATE (oral) 132,7 mg/kg; ATE (dermal) 398,0 mg/kg; ATE (inhalation vapour) 3,980 mg/l; ATE (inhalation dust/mist) 0,6630 mg/l

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
67-56-1	methanol					
	oral	LD50 mg/kg	2528	Rat	ECHA Dossier	
	dermal	LD50 mg/kg	17100	Rabbit	ECHA Dossier	
	inhalation vapour	ATE	3 mg/l			
	inhalation dust/mist	ATE	0,5 mg/l			
50-00-0	formaldehyde %					
	oral	LD50 mg/kg	640	Rat	ECHA	OECD 401
	dermal	ATE mg/kg	300			
	inhalation (4 h) vapour	LC50 mg/l	<463	Rat	ECHA	
	inhalation dust/mist	ATE	0,5 mg/l			

### Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

# Sensitising effects

May cause an allergic skin reaction. (formaldehyde ... %)

# Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of causing genetic defects. (formaldehyde ... %)

May cause cancer. (formaldehyde ... %)

Reproductive toxicity: Based on available data, the classification criteria are not met.

## STOT-single exposure

Causes damage to organs. (methanol)

May cause respiratory irritation. (formaldehyde ... %)

### STOT-repeated exposure

Based on available data, the classification criteria are not met.

### Aspiration hazard

Based on available data, the classification criteria are not met.

## 11.2. Information on other hazards

# **Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

### Other information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP]. Special hazards arising from the substance or mixture!

## **SECTION 12: Ecological information**



according to UK REACH Regulation

# **SCHAFFER's Fixative (NaPh-buffered Formaline & Methanol)**

Revision date: 22.09.2023 Product code: 15201.xxxxx Page 10 of 15

### 12.1. Toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h]   [d]	Species	Source	Method
67-56-1	methanol						
	Acute fish toxicity	LC50 mg/l	15400	96 h	Lepomis macrochirus	ECHA Dossier	
	Acute algae toxicity	ErC50 mg/l	22000	96 h	Pseudokirchneriella subcapitata	ECHA Dossier	
	Acute crustacea toxicity	EC50 mg/l	>1000	48 h	Daphnia magna	ECHA Dossier	OECD 202
50-00-0	formaldehyde %						
	Acute fish toxicity	LC50 mg/l	24,1	96 h	Pimephales promelas	ECHA Dossier	
	Acute algae toxicity	ErC50 mg/l	4,89	72 h	Desmodesmus subspicatus	ECHA Dossier	
	Acute crustacea toxicity	EC50	5,8 mg/l	48 h	Daphnia pulex (water flea)	ECHA Dossier	

## 12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name							
	Method	Value	d	Source				
	Evaluation		-	-				
67-56-1	methanol							
	other guideline	96%	20	ECHA Dossier				
	Easily biodegradable (concerning to the crit	teria of the OECD)						
50-00-0	formaldehyde %							
	OECD Guideline 301 C	91 %	14	ECHA Dossier				
	Easily biodegradable (concerning to the criteria of the OECD)							
	OECD Guideline 301 D	90	28	ECHA Dossier				
	Product is biodegradable.							

# 12.3. Bioaccumulative potential

The product has not been tested.

## Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
67-56-1	methanol	-0,77
50-00-0	formaldehyde %	0,35

# **BCF**

CAS No	Chemical name	BCF	Species	Source
67-56-1	methanol	<10		

## 12.4. Mobility in soil

No information available.

## 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

## 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.



according to UK REACH Regulation

## SCHAFFER's Fixative (NaPh-buffered Formaline & Methanol)

Revision date: 22.09.2023 Product code: 15201.xxxxx Page 11 of 15

### 12.7. Other adverse effects

No information available.

#### **Further information**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Do not allow uncontrolled discharge of product into the environment.

## **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

### **Disposal recommendations**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation. Consult the local waste disposal expert about waste disposal. Non-contaminated packages may be recycled. According to (EWC) European Waste Catalogue, allocation of waste identity numbers/waste descriptions must be carried out in a specific way for every industry and process. Control report for waste code/ waste marking according to (EWC) European Waste Catalogue:

### List of Wastes Code - residues/unused products

160506 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and

discarded chemicals; laboratory chemicals, consisting of or containing hazardous substances,

including mixtures of laboratory chemicals; hazardous waste

### List of Wastes Code - used product

160506 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and

discarded chemicals; laboratory chemicals, consisting of or containing hazardous substances,

including mixtures of laboratory chemicals; hazardous waste

## List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND

PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by

hazardous substances; hazardous waste

### Contaminated packaging

Hazardous waste according to Directive 2008/98/EC (waste framework directive). Handle contaminated packages in the same way as the substance itself.

## **SECTION 14: Transport information**

### Land transport (ADR/RID)

14.1. UN number or ID number:UN 123014.2. UN proper shipping name:METHANOL

 14.3. Transport hazard class(es):
 3

 14.4. Packing group:
 II

 Hazard label:
 3+6.1



Classification code: FT1
Special Provisions: 279
Limited quantity: 1 L
Excepted quantity: E2
Transport category: 2
Hazard No: 336
Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1230



according to UK REACH Regulation

# **SCHAFFER's Fixative (NaPh-buffered Formaline & Methanol)**

Revision date: 22.09.2023 Product code: 15201.xxxxx Page 12 of 15

14.2. UN proper shipping name: METHANOL

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3+6.1



Classification code: FT1
Special Provisions: 279 802
Limited quantity: 1 L
Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number or ID number:UN 123014.2. UN proper shipping name:METHANOL

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3+6.1



Special Provisions: 279
Limited quantity: 1 L
Excepted quantity: E2
EmS: F-E, S-D

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:UN 123014.2. UN proper shipping name:METHANOL

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3+6.1



Special Provisions:

Limited quantity Passenger:

Passenger LQ:

Excepted quantity:

A113

Limited quantity Passenger:

1 L

Y341

Excepted quantity:

E2

IATA-packing instructions - Passenger:352IATA-max. quantity - Passenger:1 LIATA-packing instructions - Cargo:364IATA-max. quantity - Cargo:60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: Combustible liquid. Acute Toxicity. See section 8.

14.7. Maritime transport in bulk according to IMO instruments

not relevant

## **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture



according to UK REACH Regulation

## **SCHAFFER's Fixative (NaPh-buffered Formaline & Methanol)**

Product code: 15201.xxxxx Revision date: 22.09.2023 Page 13 of 15

### **EU** regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Information according to 2012/18/EU H2 ACUTE TOXIC

(SEVESO III):

Additional information: P5c

### **Additional information**

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

### National regulatory information

**Employment restrictions:** Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or

nursing mothers.

Water hazard class (D): 3 - highly hazardous to water

Skin resorption/Sensitization: Permeates easily through outer skin and causes poisoning. Causes

allergic hypersensitivity reactions.

### 15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

methanol

formaldehyde ... %

## **SECTION 16: Other information**

## Changes

Rev.2,0; 25.09.2022; Recreation from collect SDB 12121.collect

## Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

CAS Chemical Abstracts Service DNEL: Derived No Effect Level

IARC: INTERNATIONAL AGENCY FOR RESEARCH ON CANCER

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

GHS: Globally Harmonized System of Classification and Labelling of Chemicals GefStoffV: Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany)

LOAEL: Lowest observed adverse effect level

LOAEC: Lowest observed adverse effect concentration

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NOAEL: No observed adverse effect level NOAEC: No observed adverse effect level NTP: National Toxicology Program

N/A: not applicable

OSHA: Occupational Safety and Health Administration

PNEC: predicted no effect concentration PBT: Persistent bioaccumulative toxic

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de

fer (Regulations Concerning the International Transport of Dangerous Goods by Rail )

SARA: Superfund Amendments and Reauthorization Act

SVHC: substance of very high concern



### according to UK REACH Regulation

## SCHAFFER's Fixative (NaPh-buffered Formaline & Methanol)

Revision date: 22.09.2023 Product code: 15201.xxxxx Page 14 of 15

TRGS Technische Regeln fuerGefahrstoffe TSCA: Toxic Substances Control Act VOC: Volatile Organic Compounds

VwVwS: Verwaltungsvorschrift wassergefaehrdender Stoffe

WGK: Wassergefaehrdungsklasse

CLP: Classification, labelling and Packaging

REACH: Registration, Evaluation and Authorization of Chemicals

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

**UN: United Nations** 

CAS: Chemical Abstracts Service
DNEL: Derived No Effect Level
DMEL: Derived Minimal Effect Level
PNEC: Predicted No Effect Concentration

ATE: Acute toxicity estimate LL50: Lethal loading, 50% EL50: Effect loading, 50%

EC50: Effective Concentration 50%

ErC50: Effective Concentration 50%, growth rate NOEC: No Observed Effect Concentration

BCF: Bio-concentration factor

PBT: persistent, bioaccumulative, toxic vPvB: very persistent, very bioaccumulative

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Regulations concerning the international carriage of dangerous goods by rail

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)

EmS: Emergency Schedules MFAG: Medical First Aid Guide

MARPOL: International Convention for the Prevention of Marine Pollution from Ships

IBC: Intermediate Bulk Container

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

## Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Acute Tox. 3; H301	Calculation method
Acute Tox. 3; H311	Calculation method
Acute Tox. 3; H331	Calculation method
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
Skin Sens. 1; H317	Calculation method
Muta. 2; H341	Calculation method
Carc. 1B; H350	Calculation method
STOT SE 1; H370	Calculation method
STOT SE 3; H335	Calculation method

## Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.

H301 Toxic if swallowed.

H301+H311+H331 Toxic if swallowed, in contact with skin or if inhaled.

H311 Toxic in contact with skin.



according to UK REACH Regulation

	SCHAFFER's Fixative (NaPh-buffered Formaline & Methanol)	
Revision date: 22.09.2023	Product code: 15201.xxxxx	Page 15 of 15
H314	Causes severe skin burns and eye damage.	
H315	Causes skin irritation.	
H317	May cause an allergic skin reaction.	
H319	Causes serious eye irritation.	
H331	Toxic if inhaled.	
H335	May cause respiratory irritation.	
H341	Suspected of causing genetic defects.	
H350	May cause cancer.	
H370	Causes damage to organs.	
Further Information		

#### Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations. The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)