

Safety Data Sheet

according to UK REACH Regulation

Hydrochloric Acid in Ethanol (3 % / 90 %)

Revision date: 26.07.2023

Product code: 12255.xxxxx

Page 1 of 18

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Hydrochloric Acid in Ethanol (3 % / 90 %)

UFI: 95X2-V1G8-J003-CYKQ

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Any non-intended use.

Uses advised against

Any non-intended use.

1.3. Details of the supplier of the safety data sheet

Company name: MORPHISTO GmbH
Street: Schumannstr. 142/144
Place: D-63069 Offenbach
Telephone: +49 (0) 69 / 400 3019-60 Telefax: +49 (0) 69 / 400 3019-64
E-mail: info@morphisto.de
Contact person: Morphisto GmbH
E-mail: gefahrstoffmanagement@morphisto.de
Internet: http://www.morphisto.de

1.4. Emergency telephone number:

Poison Information Center Mainz, Germany, Tel: +49(0)6131/19240

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Met. Corr. 1; H290
Flam. Liq. 2; H225
Eye Irrit. 2; H319

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Signal word: Danger

Pictograms:



Hazard statements

H225 Highly flammable liquid and vapour.
H290 May be corrosive to metals.
H319 Causes serious eye irritation.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P337+P313 If eye irritation persists: Get medical advice/attention.
P370+P378 In case of fire: Use sand, extinguishing powder or alcohol-resistant foam to extinguish.
P390 Absorb spillage to prevent material damage.

Safety Data Sheet

according to UK REACH Regulation

Hydrochloric Acid in Ethanol (3 % / 90 %)

Revision date: 26.07.2023

Product code: 12255.xxxxx

Page 2 of 18

Labelling of packages where the contents do not exceed 125 ml
Signal word: Danger

Pictograms:


2.3. Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulating and toxic (PBT) or very persistent and very bioaccumulating (vPvB) at levels of 0.1% or higher. Ecological information: The substance/mixture does not contain any components that are considered to be hazardous according to REACH Article 57(f) or Commission Delegated Regulation (EU) 2017/2100 or Commission Delegated Regulation (EU) 2018/605 in amounts of 0.1 % or more have endocrine disrupting properties. Toxicological information: The substance/mixture does not contain any components that are to be classified according to REACH Article 57(f) or Commission Delegated Regulation (EU) 2017/2100 or Commission Delegated Regulation (EU) 2018/605 in quantities of 0.1 % or more have endocrine disrupting properties.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
64-17-5	ethanol			85 - < 90 %
	200-578-6	603-002-00-5	01-2119457610-43	
	Flam. Liq. 2, Eye Irrit. 2; H225 H319			
7647-01-0	hydrochloric acid %			1 - < 5 %
	231-595-7	017-002-01-X	01-2119484862-27	
	Met. Corr. 1, Skin Corr. 1B, Eye Dam. 1, STOT SE 3; H290 H314 H318 H335			
67-63-0	2-propanol			< 1 %
	200-661-7	603-117-00-0	01-2119457558-25	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336			
78-93-3	butanone			< 1 %
	201-159-0	606-002-00-3	01-2119457290-43	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
3734-33-6	Denatoniumbenzoate			< 1 %
	223-095-2			
	Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Dam. 1, Aquatic Chronic 3; H332 H302 H315 H318 H412			

Full text of H and EUH statements: see section 16.

Safety Data Sheet

according to UK REACH Regulation

Hydrochloric Acid in Ethanol (3 % / 90 %)

Revision date: 26.07.2023

Product code: 12255.xxxxx

Page 3 of 18

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
64-17-5	200-578-6	ethanol	85 - < 90 %
		inhalation: LC50 = 124,7 mg/l (vapours); dermal: LD50 = >2000 mg/kg; oral: LD50 = >5000 mg/kg Eye Irrit. 2; H319: >= 50 - 100	
7647-01-0	231-595-7	hydrochloric acid %	1 - < 5 %
		oral: LD50 = 2222 mg/kg Skin Corr. 1B; H314: >= 25 - 100 Skin Irrit. 2; H315: >= 10 - < 25 Eye Irrit. 2; H319: >= 10 - < 25 STOT SE 3; H335: >= 10 - 100	
67-63-0	200-661-7	2-propanol	< 1 %
		dermal: LD50 = >5000 mg/kg; oral: LD50 = >5000 mg/kg	
78-93-3	201-159-0	butanone	< 1 %
		dermal: LD50 = >2000 mg/kg; oral: LD50 = 2054 mg/kg	
3734-33-6	223-095-2	Denatoniumbenzoate	< 1 %
		inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = >2000 mg/kg; oral: ATE = 500 mg/kg	

Further Information

This product contains no substances of very high concern (SVHC) (>0,1%) which are included in the Candidate List according to Article 59 of REACH.

SECTION 4: First aid measures
4.1. Description of first aid measures
General information

Remove affected person from the danger area and lay down. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After inhalation

Provide fresh air. In case of accident by inhalation: remove casualty to fresh air and keep at rest. If unconscious but breathing normally, place in recovery position and seek medical advice. In case of allergic symptoms, especially in the breathing area, seek medical advice immediately.

After contact with skin

Wash with plenty of water. Take off contaminated clothing and wash it before reuse. In case of skin irritation, seek medical treatment.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately. Rinse immediately carefully and thoroughly with eye-bath or water. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

After ingestion

Observe risk of aspiration if vomiting occurs. Rinse mouth thoroughly with water. Let water be drunken in little sips (dilution effect). Seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

Acute effects: Mucous membrane irritation after eye contact or inhalation.

Delayed effects: Impairment of inhibitory functions of the central nervous system, skin redness, nausea after ingestion of large amounts.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

Percutaneously absorbed and inhaled substance causes next to irritation of affected mucous membranes only an indicated impairment of the inhibitory functions of the central nervous system, clinically recognizable as the beginning of a euphoric stage. At the same time face and skin redness is caused by dilation of peripheral blood vessels in the body.

Safety Data Sheet

according to UK REACH Regulation

Hydrochloric Acid in Ethanol (3 % / 90 %)

Revision date: 26.07.2023

Product code: 12255.xxxxx

Page 4 of 18

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**Water spray jet, Carbon dioxide (CO₂), Foam, Extinguishing powder.**Unsuitable extinguishing media**

High power water jet.

5.2. Special hazards arising from the substance or mixture

Highly flammable. Vapours can form explosive mixtures with air.

Vapours are heavier than air and will spread at floor level.

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO₂). Hydrogen chloride (HCl).**5.3. Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus. In case of fire and/or explosion do not breathe fumes.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Remove all sources of ignition. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment. Ventilate affected area. Special danger of slipping by leaking/spilling product.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Explosion risk. Do not allow to enter into surface water or drains. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Prevent spread over a wide area (e.g. by containment or oil barriers). In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up**For cleaning up**

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

Other information

Ventilate affected area.

Clear contaminated areas thoroughly.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes.

Wear personal protection equipment. (See section 8.)

Use extractor hood (laboratory).

Safety Data Sheet

according to UK REACH Regulation

Hydrochloric Acid in Ethanol (3 % / 90 %)

Revision date: 26.07.2023

Product code: 12255.xxxxx

Page 5 of 18

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air. Flammable vapours can accumulate in head space of closed systems. Heating causes rise in pressure with risk of bursting.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat, drink, smoke, sniff. Always close containers tightly after the removal of product. Protect skin by using skin protective cream.

Further information on handling

General protection and hygiene measures: refer to chapter 8

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Unsuitable container/equipment material: Metal. Keep/Store only in original container. Protect from direct sunlight. Ensure adequate ventilation of the storage area. Concentrated vapours are heavier than air. Suitable material for Container: Stainless steel. (1.4301 (V2), 1.4401 (V4)); iron. solvent resistant plastics. Unsuitable materials for Container: Aluminium. Rubber. various plastics.

Hints on joint storage

Do not store together with: Oxidizing agent. Pyrophoric or self-heating substances. Do not store together with: Gas. Explosives. Flammable solids. Pyrophoric liquids and solids. Self-heating substances and mixtures. Substances or mixtures which, in contact with water, emit flammable gases. Oxidizing liquids. Oxidizing solids. ammonium nitrate. Self-reactive substances and mixtures. Organic peroxides. Non-combustible toxic substances. Radioactive substances. Infectious substances.

Further information on storage conditions

Recommended storage temperature: 15-25 °C
 Protect against: UV-radiation/sunlight. heat. Cold.
 Store small packages in a suitable, robust cabinet.

7.3. Specific end use(s)

See section 1.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
78-93-3	Butan-2-one (methyl ethyl ketone)	200	600		TWA (8 h)	WEL
		300	899		STEL (15 min)	WEL
64-17-5	Ethanol	1000	1920		TWA (8 h)	WEL
7647-01-0	Hydrogen chloride (gas and aerosol mists)	1	2		TWA (8 h)	WEL
		5	8		STEL (15 min)	WEL
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL

Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
78-93-3	Butan-2-one	butan-2-one	70 µmol/L	urine	Post shift

Safety Data Sheet

according to UK REACH Regulation

Hydrochloric Acid in Ethanol (3 % / 90 %)

Revision date: 26.07.2023

Product code: 12255.xxxxx

Page 6 of 18

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
64-17-5	ethanol			
Worker DNEL, acute		inhalation	local	1900 mg/m ³
Worker DNEL, long-term		dermal	systemic	343 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	950 mg/m ³
Consumer DNEL, acute		inhalation	local	950 mg/m ³
Consumer DNEL, long-term		dermal	systemic	206 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	114 mg/m ³
Consumer DNEL, long-term		oral	systemic	87 mg/kg bw/day
7647-01-0	hydrochloric acid %			
Worker DNEL, acute		inhalation	local	15 mg/m ³
Worker DNEL, long-term		inhalation	local	8 mg/m ³
67-63-0	2-propanol			
Worker DNEL, long-term		inhalation	systemic	500 mg/m ³
Consumer DNEL, long-term		inhalation	systemic	89 mg/m ³
Worker DNEL, long-term		dermal	systemic	888 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	26 mg/kg bw/day
Consumer DNEL, long-term		dermal	systemic	319 mg/kg bw/day
78-93-3	butanone			
Worker DNEL, long-term		inhalation	systemic	600 mg/m ³
Worker DNEL, long-term		dermal	systemic	1161 mg/kg bw/day

Safety Data Sheet

according to UK REACH Regulation

Hydrochloric Acid in Ethanol (3 % / 90 %)

Revision date: 26.07.2023

Product code: 12255.xxxxx

Page 7 of 18

PNEC values

CAS No	Substance	Value
Environmental compartment		
64-17-5	ethanol	
Freshwater		0,96 mg/l
Freshwater (intermittent releases)		2,75 mg/l
Marine water		0,79 mg/l
Marine water (intermittent releases)		2,75 mg/l
Freshwater sediment		3,6 mg/kg
Marine sediment		2,9 mg/kg
Secondary poisoning		0,72 mg/kg
Micro-organisms in sewage treatment plants (STP)		580 mg/l
Soil		0,63 mg/kg
67-63-0	2-propanol	
Freshwater		140,9 mg/l
Marine water		140,9 mg/l
Freshwater sediment		552 mg/kg
Marine sediment		552 mg/kg
Secondary poisoning		160 mg/kg
Soil		28 mg/kg
78-93-3	butanone	
Freshwater		55,8 mg/l
Freshwater (intermittent releases)		55,8 mg/l
Marine water		55,8 mg/l
Freshwater sediment		284,7 mg/kg
Marine sediment		284,7 mg/kg
Micro-organisms in sewage treatment plants (STP)		709 mg/l
Soil		22,5 mg/kg

8.2. Exposure controls

Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray. Provide adequate ventilation.

If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

Use extractor hood (laboratory).

Individual protection measures, such as personal protective equipment
Eye/face protection

Suitable eye protection: goggles. Tightly sealed safety glasses. EN 166

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the

Safety Data Sheet

according to UK REACH Regulation

Hydrochloric Acid in Ethanol (3 % / 90 %)

Revision date: 26.07.2023

Product code: 12255.xxxxx

Page 8 of 18

specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. In case of prolonged or frequently repeated skin contact:

Tested protective gloves are to be worn:

Suitable material:

Butyl rubber. (0,7 mm, Breakthrough time ≥ 480 min, penetration time (maximum wearing period): 160 min):

NBR (Nitrile rubber). (0,4 mm, Breakthrough time ≥ 120 min, penetration time (maximum wearing period): 40 min)

The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it.

Before using check leak tightness / impermeability. In the case of wanting to use the gloves again, clean them before taking off and air them well.

Skin protection

Protective clothing. (fire retardant.)

Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500 (D).

Respiratory protection

In case of inadequate ventilation wear respiratory protection. With correct and proper use, and under normal conditions, breathing protection is not required.

Respiratory protection necessary at:

Insufficient ventilation.

exceeding exposure limit values

generation/formation of aerosols

Suitable respiratory protective equipment:

gas filtering equipment (EN 141). Type : a

The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.

The wearing time limitations according to GefStoffV in conjunction with the rules for the use of respiratory protective devices (BGR 190) must be observed.

Thermal hazards

Flame-retardant protective clothing. Wear anti-static footwear and clothing

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	liquid	
Colour:	colourless	
Odour:	Ethanol.	
Melting point/freezing point:		not determined
Boiling point or initial boiling point and boiling range:		56,1 °C
Flammability:		not determined
Lower explosion limits:		2,5 vol. %
Upper explosion limits:		15 vol. %
Flash point:		12 °C
Auto-ignition temperature:		400 °C
Decomposition temperature:		not determined
pH-Value:		No information available.
Viscosity / kinematic:		not determined
Water solubility:		completely miscible

Safety Data Sheet

according to UK REACH Regulation

Hydrochloric Acid in Ethanol (3 % / 90 %)

Revision date: 26.07.2023

Product code: 12255.xxxxx

Page 9 of 18

Solubility in other solvents

not determined

Partition coefficient n-octanol/water:

not determined

Vapour pressure:

190 hPa

(at 20 °C)

Density (at 20 °C):

0,82 g/cm³

Relative vapour density:

not determined

Particle characteristics:

not applicable

9.2. Other information**Information with regard to physical hazard classes**

Explosive properties

The product is not: Explosive. In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop. Vapours can travel considerable distances to a source of ignition where they can ignite, flash back, or explode.

Self-ignition temperature

Gas:

not determined

Oxidizing properties

none

Other safety characteristics

Evaporation rate:

not determined

Solvent separation test:

not determined

Solvent content:

not determined

Solid content:

not determined

Sublimation point:

not determined

Softening point:

not determined

Pour point:

not determined

Viscosity / dynamic:

not determined

Flow time:

not determined

SECTION 10: Stability and reactivity**10.1. Reactivity**

Corrosive to metals. Highly flammable.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Explosion risk in contact with: Oxidizing agents, strong. nitric acid. Hydrogenium peroxide.

Exothermic reactions with: Alkali metals. Alkaline earth metals. Reducing agents, strong.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. Keep away from heat. Protect from direct sunlight. Protect from moisture.

In use may form flammable/explosive vapour-air mixture.

Heating causes rise in pressure with risk of bursting. Recommended storage temperature: < 40 °C

10.5. Incompatible materials

Keep away from: Metal. Strong acid. Oxidizing agents. Alkali metals. Alkaline earth metals. Peroxides.

phosphorus oxides. Nitrogen oxides (NO_x). Hydrogenium peroxide. Nitric acid. hydrochloric acid. Sulfuric acid.

Perchlorates. Chromium oxides. Acid chlorides.

10.6. Hazardous decomposition productsIn case of fire may be liberated: Carbon monoxide Carbon dioxide (CO₂). Hydrogen chloride (HCl).**SECTION 11: Toxicological information**

Safety Data Sheet

according to UK REACH Regulation

Hydrochloric Acid in Ethanol (3 % / 90 %)

Revision date: 26.07.2023

Product code: 12255.xxxxx

Page 10 of 18

11.1. Information on hazard classes as defined in GB CLP Regulation
Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64-17-5	ethanol				
	oral	LD50 mg/kg	>5000	Rat	ECHA Dossier
	dermal	LD50 mg/kg	>2000	Rabbit	ECHA Dossier
	inhalation (4 h) vapour	LC50 mg/l	124,7	Rat	ECHA Dossier
7647-01-0	hydrochloric acid %				
	oral	LD50 mg/kg	2222	Rat	suppliers SDS.
67-63-0	2-propanol				
	oral	LD50 mg/kg	>5000	Rat	ECHA Dossier
	dermal	LD50 mg/kg	>5000	Rabbit	ECHA Dossier
78-93-3	butanone				
	oral	LD50 mg/kg	2054	Ratte	SDB Lieferant
	dermal	LD50 mg/kg	>2000	Rabbit	ECHA Dossier
3734-33-6	Denatoniumbenzoate				
	oral	ATE mg/kg	500		
	dermal	LD50 mg/kg	>2000	Rat	suppliers SDS.
	inhalation vapour	ATE	11 mg/l		
	inhalation dust/mist	ATE	1,5 mg/l		

Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Safety Data Sheet

according to UK REACH Regulation

Hydrochloric Acid in Ethanol (3 % / 90 %)

Revision date: 26.07.2023

Product code: 12255.xxxxx

Page 11 of 18

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

Other information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP]. Depending on the ingested quantity the following symptoms can be induced: a reduction of inhibitions, euphoria but also dysphoria, aggressiveness, impaired motoric skills, impaired responsiveness, blurred vision and fatigue.

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
64-17-5	ethanol					
	Acute fish toxicity	LC50 14200 mg/l	96 h	Pimephales promelas (fathead minnow)	ECHA Dossier	
	Acute algae toxicity	ErC50 275 mg/l	72 h	Chlorella vulgaris	ECHA Dossier	
	Acute crustacea toxicity	EC50 5012 mg/l	48 h	Ceriodaphnia dubia (water flea)	ECHA Dossier	
	Crustacea toxicity	NOEC 9,6 mg/l	9 d	Daphnia magna	ECHA Dossier	
67-63-0	2-propanol					
	Acute fish toxicity	LC50 9640 mg/l	96 h	Pimephales promelas	ECHA Dossier	OECD Guideline 203
	Acute algae toxicity	ErC50 1800 mg/l	96 h	Scenedesmus quadricauda	ECHA Dossier	
	Acute crustacea toxicity	EC50 >10000 mg/l	48 h	Daphnia magna (24h)	ECHA Dossier	OECD Guideline 202
78-93-3	butanone					
	Acute fish toxicity	LC50 2993 mg/l	96 h	Pimephales promelas	ECHA Dossier	OECD 203
	Acute algae toxicity	ErC50 1972 mg/l	72 h	Pseudokirchnerella subcapitata	ECHA Dossier	OECD 201
	Acute crustacea toxicity	EC50 308 mg/l	48 h	Daphnia magna	ECHA Dossier	OECD 202
3734-33-6	Denatoniumbenzoate					
	Acute fish toxicity	LC50 >1000 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)	suppliers SDS.	
	Acute crustacea toxicity	EC50 13 mg/l	48 h	Daphnia magna (Big water flea)	suppliers SDS.	

12.2. Persistence and degradability

The product has not been tested.

Safety Data Sheet

according to UK REACH Regulation

Hydrochloric Acid in Ethanol (3 % / 90 %)

Revision date: 26.07.2023

Product code: 12255.xxxxx

Page 12 of 18

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
64-17-5	ethanol			
	other guideline	84%	20	ECHA Dossier
	Biodegradable.			
67-63-0	2-propanol			
	EU Method C.5/ EU Method C.6	53%	5	ECHA Dossier
	Easily biodegradable (concerning to the criteria of the OECD)			
78-93-3	butanone			
		98%	28	ECHA Dossier
	Readily biodegradable (according to OECD criteria).			

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
64-17-5	ethanol	-0,31
67-63-0	2-propanol	0,05
78-93-3	butanone	0,3

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

The product has not been tested.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Avoid release to the environment. Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations
13.1. Waste treatment methods
Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation. Consult the local waste disposal expert about waste disposal. Non-contaminated packages may be recycled. According to (EWC) European Waste Catalogue, allocation of waste identity numbers/waste descriptions must be carried out in a specific way for every industry and process.

Control report for waste code/ waste marking according to (EWC) European Waste Catalogue:

List of Wastes Code - residues/unused products

160506 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; laboratory chemicals, consisting of or containing hazardous substances, including mixtures of laboratory chemicals; hazardous waste

List of Wastes Code - used product

160506 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; laboratory chemicals, consisting of or containing hazardous substances, including mixtures of laboratory chemicals; hazardous waste

Safety Data Sheet

according to UK REACH Regulation

Hydrochloric Acid in Ethanol (3 % / 90 %)

Revision date: 26.07.2023

Product code: 12255.xxxxx

Page 13 of 18

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Wash with plenty of water. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN 2924
14.2. UN proper shipping name: FLAMMABLE LIQUID, CORROSIVE, N.O.S. (Ethanol, Chlorwasserstoffsäure)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3+8



Classification code: FC
 Special Provisions: 274
 Limited quantity: 1 L
 Excepted quantity: E2
 Transport category: 2
 Hazard No: 338
 Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 2924
14.2. UN proper shipping name: FLAMMABLE LIQUID, CORROSIVE, N.O.S. (Ethanol, Chlorwasserstoffsäure)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3+8



Classification code: FC
 Special Provisions: 274
 Limited quantity: 1 L
 Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number or ID number: UN 2924
14.2. UN proper shipping name: FLAMMABLE LIQUID, CORROSIVE, N.O.S. (ethanol, hydrochloric acid)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3+8



Special Provisions: 274

Safety Data Sheet

according to UK REACH Regulation

Hydrochloric Acid in Ethanol (3 % / 90 %)

Revision date: 26.07.2023

Product code: 12255.xxxxx

Page 14 of 18

Limited quantity: 1 L
 Excepted quantity: E2
 EmS: F-E, S-C

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 2924
14.2. UN proper shipping name: FLAMMABLE LIQUID, CORROSIVE, N.O.S. (ethanol, hydrochloric acid)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3+8



Special Provisions: A3
 Limited quantity Passenger: 0.5 L
 Passenger LQ: Y340
 Excepted quantity: E2
 IATA-packing instructions - Passenger: 352
 IATA-max. quantity - Passenger: 1 L
 IATA-packing instructions - Cargo: 363
 IATA-max. quantity - Cargo: 5 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: Combustible liquid. strongly corrosive. Refer to section 6-8

14.7. Maritime transport in bulk according to IMO instruments

not relevant

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Directive 2010/75/EU on industrial emissions: not determined

Directive 2004/42/EC on VOC in paints and varnishes: not determined

Information according to Directive 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

Additional information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

- ethanol
- hydrochloric acid %
- 2-propanol

Safety Data Sheet

according to UK REACH Regulation

Hydrochloric Acid in Ethanol (3 % / 90 %)

Revision date: 26.07.2023

Product code: 12255.xxxxx

Page 15 of 18

butanone

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s):
1,2,3,4,5,6,7,8,9,10,11,12,13,14,15,16.

Rev. 2,00, 11.02.23, Individual safety data sheet based on 10372_collect

Rev. 2,1; 26.07.2023; general adjustment(s)

Safety Data Sheet

according to UK REACH Regulation

Hydrochloric Acid in Ethanol (3 % / 90 %)

Revision date: 26.07.2023

Product code: 12255.xxxxx

Page 16 of 18

Abbreviations and acronyms

Met. Corr: Corrosive to metals
Flam. Liq: Flammable liquids
Acute Tox: Acute toxicity
Skin Corr: Skin corrosion
Skin Irrit: Skin irritation
Eye Dam: Eye damage
Eye Irrit: Eye irritation
STOT SE: Specific target organ toxicity - single exposure
Aquatic Chronic: Chronic aquatic hazard
ADR: Accord européen sur le transport des marchandises dangereuses par Route
AwSV: Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen
AGW: Arbeitsplatzgrenzwert
AVV: Abfallverzeichnisverordnung
CAS Chemical Abstracts Service
CLP: Classification, Labelling and Packaging of substances and mixtures
DNEL: Derived No Effect Level
d: day(s)
EAKV: Europäisches Abfallverzeichnis gemäß Entwurf Abfallverzeichnisverordnung
EINECS: European INventory of Existing Commercial chemical Substances
ELINCS: European List of Notified Chemical Substances
ECHA: European Chemicals Agency
EWC: European Waste Catalogue
IARC: INTERNATIONAL AGENCY FOR RESEARCH ON CANCER
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
ICAO: International Civil Aviation Organization
ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
GefStoffV: Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany)
h: hour
LOAEL: Lowest observed adverse effect level
LOAEC: Lowest observed adverse effect concentration
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
NOAEL: No observed adverse effect level
NOAEC: No observed adverse effect level
NLP: No-Longer Polymers
N/A: not applicable
OECD: Organisation for Economic Co-operation and Development
PNEC: predicted no effect concentration
PBT: Persistent bioaccumulative toxic
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
REACH: Registration, Evaluation, Authorisation of Chemicals
SVHC: substance of very high concern
TRGS Technische Regeln fuer Gefahrstoffe
UN: United Nations
VOC: Volatile Organic Compounds
VwVwS: Verwaltungsvorschrift wassergefährdender Stoffe
WGK: Wassergefährdungsklasse
CLP: Classification, labelling and Packaging
REACH: Registration, Evaluation and Authorization of Chemicals
GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals
UN: United Nations

Safety Data Sheet

according to UK REACH Regulation

Hydrochloric Acid in Ethanol (3 % / 90 %)

Revision date: 26.07.2023

Product code: 12255.xxxxx

Page 17 of 18

CAS: Chemical Abstracts Service
 DNEL: Derived No Effect Level
 DMEL: Derived Minimal Effect Level
 PNEC: Predicted No Effect Concentration
 ATE: Acute toxicity estimate
 LL50: Lethal loading, 50%
 EL50: Effect loading, 50%
 EC50: Effective Concentration 50%
 ErC50: Effective Concentration 50%, growth rate
 NOEC: No Observed Effect Concentration
 BCF: Bio-concentration factor
 PBT: persistent, bioaccumulative, toxic
 vPvB: very persistent, very bioaccumulative
 ADR: Accord européen sur le transport des marchandises dangereuses par Route
 (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 RID: Regulations concerning the international carriage of dangerous goods by rail
 ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
 (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation
 intérieures)
 EmS: Emergency Schedules
 MFAG: Medical First Aid Guide
 MARPOL: International Convention for the Prevention of Marine Pollution from Ships
 IBC: Intermediate Bulk Container
 For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety
 assessment, chapter R.20 (Table of terms and abbreviations).

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Met. Corr. 1; H290	On basis of test data
Flam. Liq. 2; H225	On basis of test data
Eye Irrit. 2; H319	Calculation method

Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.
 H290 May be corrosive to metals.
 H302 Harmful if swallowed.
 H314 Causes severe skin burns and eye damage.
 H315 Causes skin irritation.
 H318 Causes serious eye damage.
 H319 Causes serious eye irritation.
 H332 Harmful if inhaled.
 H335 May cause respiratory irritation.
 H336 May cause drowsiness or dizziness.
 H412 Harmful to aquatic life with long lasting effects.
 EUH066 Repeated exposure may cause skin dryness or cracking.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations. Classification according to Regulation (EC) No 1272/2008 [CLP]
 - Classification procedure:
 Health hazards: Calculation method.
 Environmental hazards: Calculation method.
 Physical hazards: On basis of test data and / or calculated and / or estimated.

The above information describes exclusively the safety requirements of the product and is based on our

Safety Data Sheet

according to UK REACH Regulation

Hydrochloric Acid in Ethanol (3 % / 90 %)

Revision date: 26.07.2023

Product code: 12255.xxxxx

Page 18 of 18

present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)