

Safety Data Sheet

according to UK REACH Regulation

Xylene - Peanut Oil

Revision date: 29.04.2024

Product code: 13237.xxxxx

Page 1 of 16

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Xylene - Peanut Oil

UFI: FFN5-W193-A003-X6U2

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Use as laboratory reagent. Intended for scientific research and development.

Uses advised against

Any non-intended use.

1.3. Details of the supplier of the safety data sheet

Company name: MORPHISTO GmbH
Street: Schumannstr. 142/144
Place: D-63069 Offenbach
Telephone: +49 (0) 69 / 400 3019-60 Telefax: +49 (0) 69 / 400 3019-64
E-mail: info@morphisto.de
Contact person: Morphisto GmbH
E-mail: gefahrstoffmanagement@morphisto.de
Internet: http://www.morphisto.de

1.4. Emergency telephone number:

Poison Information Center Mainz, Germany, Tel: +49(0)6131/19240

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Flam. Liq. 3; H226
Acute Tox. 4; H332
Asp. Tox. 1; H304
Skin Irrit. 2; H315
Eye Irrit. 2; H319
STOT SE 3; H335
STOT RE 2; H373

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

xylene
ethylbenzene

Signal word: Danger

Pictograms:



Hazard statements

H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H319 Causes serious eye irritation.

Safety Data Sheet

according to UK REACH Regulation

Xylene - Peanut Oil

Revision date: 29.04.2024

Product code: 13237.xxxxx

Page 2 of 16

H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe mist/vapours/spray.
P280	Wear protective gloves/protective clothing and eye protection/face protection.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331	Do NOT induce vomiting.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.

Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

Pictograms:



Hazard statements

H304

Precautionary statements

P301+P310-P331

2.3. Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulating and toxic (PBT) or very persistent and very bioaccumulating (vPvB) at levels of 0.1% or higher. Ecological information: The substance/mixture does not contain any components that are considered to be hazardous according to REACH Article 57(f) or Commission Delegated Regulation (EU) 2017/2100 or Commission Delegated Regulation (EU) 2018/605 in amounts of 0.1 % or more have endocrine disrupting properties. Toxicological information: The substance/mixture does not contain any components that are to be classified according to REACH Article 57(f) or Commission Delegated Regulation (EU) 2017/2100 or Commission Delegated Regulation (EU) 2018/605 in quantities of 0.1 % or more have endocrine disrupting properties.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Safety Data Sheet

according to UK REACH Regulation

Xylene - Peanut Oil

Revision date: 29.04.2024

Product code: 13237.xxxxx

Page 3 of 16

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
1330-20-7	xylene			35 - < 40 %
	215-535-7	601-022-00-9	01-2119488216-32	
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1; H226 H332 H312 H315 H319 H335 H373 H304			
100-41-4	ethylbenzene			10 - < 15 %
	202-849-4	601-023-00-4	01-2119489370-35	
	Flam. Liq. 2, Acute Tox. 4, STOT RE 2, Asp. Tox. 1, Aquatic Chronic 3; H225 H332 H373 H304 H412			
108-88-3	toluene			< 1 %
	203-625-9	601-021-00-3	01-2119471310-51	
	Flam. Liq. 2, Repr. 2, Skin Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1, Aquatic Chronic 3; H225 H361d H315 H336 H373 H304 H412			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
1330-20-7	215-535-7	xylene	35 - < 40 %
		inhalation: LC50 = 6700 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = 12126 mg/kg; oral: LD50 = 3523 mg/kg	
100-41-4	202-849-4	ethylbenzene	10 - < 15 %
		inhalation: LC50 = 17,2 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = 15400 mg/kg; oral: LD50 = 3500 mg/kg	
108-88-3	203-625-9	toluene	< 1 %
		inhalation: LC50 = 28,1 mg/l (vapours); dermal: LD50 = >5000 mg/kg; oral: LD50 = 5580 mg/kg	

Further Information

This product contains no substances of very high concern (SVHC) (>0,1%) which are included in the Candidate List according to Article 59 of REACH.

SECTION 4: First aid measures
4.1. Description of first aid measures
General information

Remove affected person from the danger area and lay down. Provide fresh air. No mouth-to-mouth or mouth-to-nose resuscitation. Use Ambu bag or ventilator. Remove contaminated, saturated clothing immediately.

After inhalation

Provide fresh air. If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor/ .

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately. Rinse immediately carefully and thoroughly with eye-bath or water. If eye irritation persists: Get medical advice/attention.

Safety Data Sheet

according to UK REACH Regulation

Xylene - Peanut Oil

Revision date: 29.04.2024

Product code: 13237.xxxxx

Page 4 of 16

After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Rinse mouth thoroughly with water. Immediately call a POISON CENTER/doctor/. Let water be drunk in little sips (dilution effect). Do NOT induce vomiting. Observe risk of aspiration if vomiting occurs.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms of poisoning may develop several hours following exposure. Victim should be under medical observation for at least 48 hours after exposure.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Carbon dioxide (CO₂), Foam, Extinguishing powder.
Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

Water. High power water jet.

5.2. Special hazards arising from the substance or mixture

Flammable. Vapours can form explosive mixtures with air. In case of fire may be liberated: Carbon monoxide (CO). Carbon dioxide (CO₂).

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Explosion risk. Do not allow to enter into surface water or drains.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up**For cleaning up**

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

Other information

Clear contaminated areas thoroughly.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

Safety Data Sheet

according to UK REACH Regulation

Xylene - Peanut Oil

Revision date: 29.04.2024

Product code: 13237.xxxxx

Page 5 of 16

7.1. Precautions for safe handling

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Wear suitable protective clothing. (See section 8.). Avoid contact with skin, eyes and clothes. Take off contaminated clothing and wash it before reuse. Always close containers tightly after the removal of product. Make sure spills can be contained (e.g. sump pallets or kerbed areas).

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air. Wear anti-static footwear and clothing Use only antistatically equipped (spark-free) tools. Have fire-extinguishers in readiness before opening containers.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat, drink, smoke, sniff. Always close containers tightly after the removal of product.

Further information on handling

Flammable vapours can accumulate in head space of closed systems.

When using do not eat, drink, smoke, sniff. This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaustion at critical locations. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep locked up. Protect from sunlight.

Suitable material for Container: Stainless steel.

Unsuitable material:PVC (Polyvinyl chloride). Other general rubber products. PE (polyethylene).

Hints on joint storage

Do not store together with: Oxidizing agent. Pyrophoric or self-heating substances. Substances that form flammable gases when in contact with water. Organic peroxides. Oxidizing substances. Explosive substances. Infectious substances. Radioactive materials. Food and fodder

Further information on storage conditions

Store small packages in a suitable, robust cabinet. Recommended storage temperature: 15-25 °C.

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
100-41-4	Ethylbenzene	100	441		TWA (8 h)	WEL
		125	552		STEL (15 min)	WEL
108-88-3	Toluene	50	191		TWA (8 h)	WEL
		100	384		STEL (15 min)	WEL
1330-20-7	Xylene: mixed isomers	50	220		TWA (8 h)	WEL
		100	441		STEL (15 min)	WEL

Safety Data Sheet

according to UK REACH Regulation

Xylene - Peanut Oil

Revision date: 29.04.2024

Product code: 13237.xxxxx

Page 6 of 16

Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
1330-20-7	Xylene, o-, m-, p- or mixed isomers	methyl hippuric acid (creatinine)	650 mmol/mol	urine	Post shift

DNEL/DMEL values

CAS No	Substance	DNEL type	Exposure route	Effect	Value
1330-20-7	xylene	Worker DNEL, acute	inhalation	local	289 mg/m ³
		Worker DNEL, acute	inhalation	systemic	289 mg/m ³
		Worker DNEL, long-term	inhalation	systemic	77 mg/m ³
		Worker DNEL, long-term	dermal	systemic	180 mg/kg bw/day
100-41-4	ethylbenzene	Worker DNEL, acute	inhalation	local	293 mg/m ³
		Worker DNEL, long-term	inhalation	systemic	77 mg/m ³
		Worker DNEL, long-term	dermal	systemic	180 mg/kg bw/day
108-88-3	toluene	Worker DNEL, long-term	dermal	systemic	384 mg/kg bw/day
		Worker DNEL, long-term	inhalation	local	192 mg/m ³
		Worker DNEL, long-term	inhalation	systemic	192 mg/m ³
		Worker DNEL, acute	inhalation	local	384 mg/m ³
		Worker DNEL, acute	inhalation	systemic	384 mg/m ³

Safety Data Sheet

according to UK REACH Regulation

Xylene - Peanut Oil

Revision date: 29.04.2024

Product code: 13237.xxxxx

Page 7 of 16

PNEC values

CAS No	Substance	Value
Environmental compartment		
1330-20-7	xylene	
Freshwater		0,327 mg/l
Freshwater (intermittent releases)		0,327 mg/l
Marine water		0,327 mg/l
Marine water (intermittent releases)		0,327 mg/l
Freshwater sediment		12,46 mg/kg
Marine sediment		12,46 mg/kg
Micro-organisms in sewage treatment plants (STP)		6,58 mg/l
Soil		2,31 mg/kg
100-41-4	ethylbenzene	
Freshwater		0,1 mg/l
Freshwater (intermittent releases)		0,1 mg/l
Marine water		0,01 mg/l
Marine water (intermittent releases)		0,1 mg/l
Freshwater sediment		13,7 mg/kg
Marine sediment		1,37 mg/kg
Micro-organisms in sewage treatment plants (STP)		9,6 mg/l
Soil		2,68 mg/kg
108-88-3	toluene	
Freshwater		0,68 mg/l
Marine water		0,68 mg/l
Freshwater sediment		16,39 mg/kg
Marine sediment		16,39 mg/kg
Micro-organisms in sewage treatment plants (STP)		13,61 mg/l
Soil		2,89 mg/kg

8.2. Exposure controls

Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray. Technical measures and the application of suitable work processes have priority over personal protection equipment. Provide washing facilities at the workplace, provide an eye shower or eyewash bottle and mark them. Use extractor hood (laboratory). Additional information: refer to section 7. No further action is necessary.

Individual protection measures, such as personal protective equipment
Eye/face protection

Suitable eye protection: goggles. Tightly sealed safety glasses. EN 166

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the

Safety Data Sheet

according to UK REACH Regulation

Xylene - Peanut Oil

Revision date: 29.04.2024

Product code: 13237.xxxxx

Page 8 of 16

specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Pull-over gloves of rubber. EN ISO 374

Suitable material:

FKM (fluororubber). (0,4 mm)

(penetration time (maximum wearing period): ≥ 8 h):

Before using check leak tightness / impermeability.

Skin protection

Use of protective clothing. Suitable protective clothing: Lab apron.

Respiratory protection

In case of inadequate ventilation wear respiratory protection. Respiratory protection necessary at:

Generation/formation of aerosols

exceeding exposure limit values

Suitable respiratory protective equipment: gas filtering equipment (EN 141). Typ: a

Details on the requirements for use and maximum concentrations can be found in the "Rules for the use of respiratory protective devices" (BGR 190).

Environmental exposure controls

Do not allow uncontrolled discharge of product into the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	liquid	
Colour:	yellowish	
Odour:	hydrocarbons, aromatic.	
Melting point/freezing point:		not determined
Boiling point or initial boiling point and boiling range:		not determined
Flammability:		not determined
Lower explosion limits:		not determined
Upper explosion limits:		not determined
Flash point:		25 °C
Auto-ignition temperature:		not determined
Decomposition temperature:		not determined
pH-Value:		not determined
Viscosity / kinematic:		not determined
Water solubility:		not determined
Solubility in other solvents		not determined
Partition coefficient n-octanol/water:		not determined
Vapour pressure:		8,21 hPa
(at 20 °C)		
Vapour pressure:		not determined
Density (at 20 °C):		0,89 g/cm ³
Relative vapour density:		not determined
Particle characteristics:		not applicable

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

The product is not: Explosive. In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

Sustaining combustion:

Sustaining combustion

Safety Data Sheet

according to UK REACH Regulation

Xylene - Peanut Oil

Revision date: 29.04.2024

Product code: 13237.xxxxx

Page 9 of 16

Oxidizing properties

The product is not: oxidising.

Other safety characteristics

Evaporation rate:

not determined

Solid content:

not determined

Further Information

No information available.

SECTION 10: Stability and reactivity**10.1. Reactivity**

No information available.

10.2. Chemical stability

Stable under normal storage and handling conditions.

10.3. Possibility of hazardous reactions

No information available.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. In case of warming: Ignition hazard. Vapours can travel considerable distances to a source of ignition where they can ignite, flash back, or explode. Vapours of flammable solvents can accumulate in the gas phase of closed container, especially during heat treatment. Therefore keep away from fire and sources of ignition.

10.5. Incompatible materials

Materials to avoid: Strong acid. Oxidizing agents, strong.

10.6. Hazardous decomposition productsIn case of fire may be liberated: Carbon monoxide (CO). Carbon dioxide (CO₂).**SECTION 11: Toxicological information****11.1. Information on hazard classes as defined in GB CLP Regulation****Acute toxicity**

Harmful if inhaled.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) 2937 mg/kg; ATE (inhalation vapour) 24,22 mg/l; ATE (inhalation dust/mist) 3,006 mg/l

Safety Data Sheet

according to UK REACH Regulation

Xylene - Peanut Oil

Revision date: 29.04.2024

Product code: 13237.xxxxx

Page 10 of 16

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
1330-20-7	xylene				
	oral	LD50 mg/kg 3523	Rat	Study report (1986)	EU Method B.1
	dermal	LD50 mg/kg 12126	Rabbit	Publication (1962)	Single dermal dose under occlusion follo
	inhalation (4 h) vapour	LC50 6700 mg/l	Rat	Toxicol Appl Pharmacol 33:543-558. (1975)	EU Method B.2
	inhalation dust/mist	ATE 1,5 mg/l			
100-41-4	ethylbenzene				
	oral	LD50 mg/kg 3500	Rat	GESTIS	
	dermal	LD50 mg/kg 15400	Rabbit	GESTIS	
	inhalation (4 h) vapour	LC50 17,2 mg/l	Rat		
	inhalation dust/mist	ATE 1,5 mg/l			
108-88-3	toluene				
	oral	LD50 mg/kg 5580	Rat		
	dermal	LD50 mg/kg >5000	Rabbit	GESTIS	
	inhalation (4 h) vapour	LC50 28,1 mg/l	Rat	GESTIS	

Irritation and corrosivity

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye irritation: Causes serious eye irritation.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation. (xylene)

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (xylene; ethylbenzene)

Aspiration hazard

May be fatal if swallowed and enters airways.

11.2. Information on other hazards
Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

Other information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information
12.1. Toxicity

Based on available data, the classification criteria are not met.

Safety Data Sheet

according to UK REACH Regulation

Xylene - Peanut Oil

Revision date: 29.04.2024

Product code: 13237.xxxxx

Page 11 of 16

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
1330-20-7	xylene					
	Acute fish toxicity	LC50	4,6 mg/l	96 h	Oncorhynchus mykiss	ECHA
	Acute algae toxicity	ErC50	4,6 mg/l	72 h	Pseudokirchneriella subcapitata	ECHA
	Acute crustacea toxicity	EL50 mg/l	> 3,4	48 h	Ceriodaphnia dubia	Ecotoxicology and Environmental Safety 3 US EPA 600/4-91-003
	Fish toxicity	NOEC mg/l	0,894	21 d	Oncorhynchus mykiss	ECHA
	Crustacea toxicity	NOEC mg/l	0,96	7 d	Ceriodaphnia dubia	ECHA
	Acute bacteria toxicity	EC50 mg/l ()	> 175	0,5 h	Activated sludge	Research Journal WPCF 60(10) 1850-1856 () OECD Guideline 209
100-41-4	ethylbenzene					
	Acute fish toxicity	LC50	4,2 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)	ECHA
	Acute algae toxicity	ErC50	3,6 mg/l	96 h	Pseudokirchneriella subcapitata	GESTIS
	Acute crustacea toxicity	EC50 mg/l	1,85	48 h	Daphnia magna (Big water flea)	ECHA
	Crustacea toxicity	NOEC	1 mg/l	7 d	Ceriodaphnia dubia (water flea)	ECHA
108-88-3	toluene					
	Acute fish toxicity	LC50 mg/l	31,7	96 h	Pimephales promelas (fathead minnow)	suppliers SDS.
	Acute algae toxicity	ErC50 mg/l	12,5	72 h	Selenastrum capricornutum	GESTIS
	Acute crustacea toxicity	EC50 mg/l	9,24	48 h	Daphnia magna (Big water flea)	suppliers SDS.

12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name				
	Method	Value	d	Source	
	Evaluation				
1330-20-7	xylene				
	OECD 301F / ISO 9408 / EEC 92/69 annex V, C.4-D	87,8%	28	OECD 301F / ISO 9408 / EEC 92/69 annex V, C.4-D	
	Easily biodegradable (concerning to the criteria of the OECD)				

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
1330-20-7	xylene	3,2
100-41-4	ethylbenzene	3,15
108-88-3	toluene	2,73

Safety Data Sheet

according to UK REACH Regulation

Xylene - Peanut Oil

Revision date: 29.04.2024

Product code: 13237.xxxxx

Page 12 of 16

BCF

CAS No	Chemical name	BCF	Species	Source
1330-20-7	xylene	5,5 - 12,2	Oncorhynchus mykiss	Appl. Sci. Branch, E

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Do not allow uncontrolled discharge of product into the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods
Disposal recommendations

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation. Consult the local waste disposal expert about waste disposal.

List of Wastes Code - residues/unused products

160506 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; laboratory chemicals, consisting of or containing hazardous substances, including mixtures of laboratory chemicals; hazardous waste

List of Wastes Code - used product

160506 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; laboratory chemicals, consisting of or containing hazardous substances, including mixtures of laboratory chemicals; hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Hazardous waste according to Directive 2008/98/EC (waste framework directive). Handle contaminated packages in the same way as the substance itself. Non-contaminated packages may be recycled.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:	UN 1307
14.2. UN proper shipping name:	XYLENES
14.3. Transport hazard class(es):	3
14.4. Packing group:	III
Hazard label:	3



Classification code: F1

Safety Data Sheet

according to UK REACH Regulation

Xylene - Peanut Oil

Revision date: 29.04.2024

Product code: 13237.xxxxx

Page 13 of 16

Limited quantity: 5 L
 Excepted quantity: E1
 Transport category: 3
 Hazard No: 30
 Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1307
14.2. UN proper shipping name: XYLENES
14.3. Transport hazard class(es): 3
14.4. Packing group: III
 Hazard label: 3



Classification code: F1
 Limited quantity: 5 L
 Excepted quantity: E1

Marine transport (IMDG)

14.1. UN number or ID number: UN 1307
14.2. UN proper shipping name: XYLENES
14.3. Transport hazard class(es): 3
14.4. Packing group: III
 Hazard label: 3



Special Provisions: 223
 Limited quantity: 5 L
 Excepted quantity: E1
 EmS: F-E, S-D

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1307
14.2. UN proper shipping name: XYLENES
14.3. Transport hazard class(es): 3
14.4. Packing group: III
 Hazard label: 3



Special Provisions: A3
 Limited quantity Passenger: 10 L
 Passenger LQ: Y344
 Excepted quantity: E1
 IATA-packing instructions - Passenger: 355
 IATA-max. quantity - Passenger: 60 L
 IATA-packing instructions - Cargo: 366
 IATA-max. quantity - Cargo: 220 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: Combustible liquid. Refer to section 6-8

Safety Data Sheet

according to UK REACH Regulation

Xylene - Peanut Oil

Revision date: 29.04.2024

Product code: 13237.xxxxx

Page 14 of 16

14.7. Maritime transport in bulk according to IMO instruments

not relevant

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 48, Entry 75

Information according to Directive 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

Additional information

This preparation is hazardous in the sense of regulation (EC) No 1272/2008 [GHS].

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 2 - obviously hazardous to water

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

xylene

ethylbenzene

toluene

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 1,4,6,7,9,10,14,15,16.

06.02.2011; Rev. 1.0 Neuerungstellung

15.07.2014; Rev. 1.1 Revision

17.02.2021; Rev. 1,2 Revision Changes in section: 1 - 16.

Rev. 2,0; 16.08.2023: general adjustment(s)

Rev. 2,1; 29.04.2023; Change of transport labelling

Safety Data Sheet

according to UK REACH Regulation

Xylene - Peanut Oil

Revision date: 29.04.2024

Product code: 13237.xxxxx

Page 15 of 16

Abbreviations and acronyms

Flam. Liq: Flammable liquids
Acute Tox: Acute toxicity
Asp. Tox: Aspiration hazard
Skin Irrit: Skin irritation
Eye Irrit: Eye irritation
Repr: Reproductive toxicity
STOT SE: Specific target organ toxicity - single exposure
STOT RE: Specific target organ toxicity - repeated exposure
Aquatic Chronic: Chronic aquatic hazard
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations
Concerning the International Transport of Dangerous Goods by Rail)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
ICAO: International Civil Aviation Organization
ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
OSHA: Occupational Safety and Health Administration
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
NOEL: No observed effect level
NOAEL: No observed adverse effect level
LOAEL: Lowest observed adverse effect level
NOAEC: No observed adverse effect level
LOAEC: Lowest observed adverse effect concentration
DNEL: Derived No Effect Level
PNEC: predicted no effect concentration
TSCA: Toxic Substances Control Act
IARC: INTERNATIONAL AGENCY FOR RESEARCH ON CANCER
NTP: National Toxicology Program
SARA: Superfund Amendments and Reauthorization Act
GefStoffV: Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany)
PBT: Persistent bioaccumulative toxic
SVHC: substance of very high concern
CLP: Classification, labelling and Packaging
REACH: Registration, Evaluation and Authorization of Chemicals
GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals
UN: United Nations
CAS: Chemical Abstracts Service
DNEL: Derived No Effect Level
DMEL: Derived Minimal Effect Level
PNEC: Predicted No Effect Concentration
ATE: Acute toxicity estimate
LL50: Lethal loading, 50%
EL50: Effect loading, 50%
EC50: Effective Concentration 50%
ErC50: Effective Concentration 50%, growth rate
NOEC: No Observed Effect Concentration
BCF: Bio-concentration factor
PBT: persistent, bioaccumulative, toxic
vPvB: very persistent, very bioaccumulative

Safety Data Sheet

according to UK REACH Regulation

Xylene - Peanut Oil

Revision date: 29.04.2024

Product code: 13237.xxxxx

Page 16 of 16

ADR: Accord européen sur le transport des marchandises dangereuses par Route
 (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 RID: Regulations concerning the international carriage of dangerous goods by rail
 ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
 (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation
 intérieures)
 EmS: Emergency Schedules
 MFAG: Medical First Aid Guide
 MARPOL: International Convention for the Prevention of Marine Pollution from Ships
 IBC: Intermediate Bulk Container
 VOC: Volatile Organic Compounds
 For abbreviations and acronyms, see table at <http://abbrev.esdscom.eu>
 For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety
 assessment, chapter R.20 (Table of terms and abbreviations).

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Flam. Liq. 3; H226	On basis of test data
Acute Tox. 4; H332	Calculation method
Asp. Tox. 1; H304	Calculation method
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
STOT SE 3; H335	Calculation method
STOT RE 2; H373	Calculation method

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations. The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)